

Model No.

AC-AA-88-5010-000
 AC-AA-APERIO-HUB-AH30RN6-6144
 AC-AA-SAR-79-5000-32D
 AC-LSP-CUSTOM
 AC-SALTO-NEO-CUSTOM
 AC-SALTO-SP-PART-CUSTOM
 AC-SALTO-XS4-ANSI-MINI-CUSTOM
 AC-SCH-AD-400-993M-70-MT-RHO-626-J-RHR4B134
 AC-SCH-AD-400-CY-40-MT-RHO-626-B-LH4B1324710025134
 AC-SCH-AD-400-CY-40-MT-RHO-626-B-RH4B1324710025134
 AC-SCH-AD-400-CY-40-MT-RHO-626-BRHR4B1324710025134
 AC-SCH-AD-400-CY-40-SI-RHO-626-B-LH4B1324710025134
 AC-SCH-AD-400-CY-40-SI-RHO-626-B-RH4B1324710025134
 AC-SCH-AD-400-CY-70-MT-RHO-612-B-RH4B1324710025134
 AC-SCH-AD-400-CY-70-MT-RHO-626-JLHR4B1324710025134
 AC-SCH-AD-400-CY-70-MT-RHO-626-JRHR4B1324710025134
 AC-SCH-AD-400-MS-70-MT-RHO-626-JLH4B0966310072134
 AC-SCH-AD-400-MS-70-MT-RHO626BLH4B0966310072134
 AC-SCH-AD-400-MS-70-MT-RHO626BRH4B0966310072134
 AC-SCH-AD-400-MS-70-MTRHO626BLHR4B0966310072134
 AC-SCH-AD-400-MS-70-MTRHO626BRHR4B0966310072134
 AC-SCH-AD400-CY70MTRHO626BRH4B1324710025134
 AC-SCH-AD400CY70MTRHO626BDLHR4B1324710025134
 AC-SCH-AD400MS70SIRHO626BLHR4B0966310072134
 AC-SCH-CONTROL-FE410F-CUSTOM
 AC-SCH-NDEBSIJRHO626-13-247-47267101
 AC-HID-PIVCLASS-20HNKS-03-0004XR
 AC-HID-PIVCLASS-20HTKS-03-0004XR
 AC-HID-PIVCLASS-20KHTKS-03-0004XR
 AC-HID-PIVCLASS-40HNKS-03-0004XR
 AC-HID-PIVCLASS-40HNKS-03-00059X
 AC-HID-PIVCLASS-40HTKS-03-0004XR
 AC-HID-PIVCLASS-40HTKS-03-00059X
 AC-HID-PIVCLASS-40KHNS-03-0004XR
 AC-HID-PIVCLASS-40KHNS-03-00059X
 AC-HID-PIVCLASS-40KHTKS-03-0004XR
 AC-HID-PIVCLASS-40KHTKS-03-00059X
 AC-HID-PIVCLASS-91000-MS
 AC-HID-PIVCLASS-91000BBNNN
 AC-HID-PIVCLASS-920NHRNEK0001T
 AC-HID-PIVCLASS-920PHRNEK00004
 AC-HID-PIVCLASS-920PHRNEK00005
 AC-HID-PIVCLASS-921NHPNEK000UG
 AC-HID-PIVCLASS-921NHPNEK0019D
 AC-HID-PIVCLASS-921NHPNEK0032R
 AC-HID-PIVCLASS-921NHPTEK000UG

AC-HID-PIVCLASS-921NHPTEK0033E
AC-HID-PIVCLASS-921NHRNEK0004M
AC-HID-PIVCLASS-921NHRNEK0013W
AC-HID-PIVCLASS-921PHPNEK000R2
AC-HID-PIVCLASS-921PHPNEK000UE
AC-HID-PIVCLASS-921PHPNEK0032N
AC-HID-PIVCLASS-921PHPNEK0033G
AC-HID-PIVCLASS-921PHPNEK0033H
AC-HID-PIVCLASS-921PHPTEK0033J
AC-HID-PIVCLASS-921PHRNEK0002D
AC-HID-PIVCLASS-921PHRNEK0002G
AC-HID-PIVCLASS-921PHRNEK0005P
AC-HID-PIVCLASS-921PHRNEK0006F
AC-HID-PIVCLASS-921PHRNEK0032W
AC-HID-PIVCLASS-921PHRTEK0002D
AC-HID-PIVCLASS-921PHRTEK0002G
AC-HID-PIVCLASS-921PHRTEK0032W
AC-HID-PIVCLASS-923NPPNEK0000L
AC-HID-PIVCLASS-923PPPNEK0033T
AC-HID-PIVCLASS-923PPPTEK000P4
AC-HID-PIVCLASS-924NPRNEK00504
AC-HID-PIVCLASS-924NPRTEK00504
AC-HID-PIVCLASS-928NFNTEK000TE
AC-HID-PIVCLASS-E91000-MS
AC-HID-PIVCLASS-E920PHPTEK000P2
AC-HID-PIVCLASS-EA-LICENSE2
AC-HID-PIVCLASS-PVC-CM
AC-HID-PIVCLASS-PVC-CM-MS
AC-HID-PIVCLASS-PVC-D/S
AC-HID-PIVCLASS-PVC-D/S-MS
AC-HID-PIVCLASS-PVC-FXRDR-MS
AC-HID-PIVCLASS-PVCP-D/S-18-00
AC-HID-PIVCLASS-PVCP-D/S-MS
AC-SALTO-ADAPTER-RING-SP220418.38-IM
AC-SALTO-ADAPTER-RING-SP220495-14-IM
AC-SALTO-ADAPTER-RING-SP220495-18-IM
AC-SALTO-AELEMENT-AEBOIMBA3A8
AC-SALTO-AELEMENT-AEBOIPBA3A8
AC-SALTO-AELEMENT-AEB1IMBA3A8
AC-SALTO-AELEMENT-AEB1IPBA3A8
AC-SALTO-AELEMENT-FUSION-READER-ANSI-AFB7PMB4A8
AC-SALTO-AELEMENT-HANDLE-R1SJRIM080
AC-SALTO-AELEMENT-HANDLE-R3SJRIM081
AC-SALTO-AELEMENT-HANDLE-R3SWRPM081
AC-SALTO-AELEMENT-MORTISE-LOCK-LA1T1770A24IMSRH
AC-SALTO-AELEMENT-MORTISE-LOCK-LA1T1770F24IMSRH
AC-SALTO-AELEMENT-MORTISE-LOCKS-LA1T1770A24PMSLH

AC-SALTO-AELEMENT-MORTISE-LOCKS-LA1T1770F74PMSRH
AC-SALTO-AELEMENT-READER-ANSI-AEB0PMB3A8
AC-SALTO-AELEMENT-READER-ANSI-AFB2IMB4A8M
AC-SALTO-AELEMENT-READER-ANSI-AFB2PMB3A8
AC-SALTO-ASSEMBLY-TOOL-NEOXX-PADLOCK-SP226009
AC-SALTO-BLUENET-BLACK-GATEWAYB3CUS
AC-SALTO-BLUENET-WHITE-GATEWAYW3CUS
AC-SALTO-CLUTCH-MECHANISM-SP00946-W67AKO
AC-SALTO-CONTROL-UNIT-IP-CLEARCOVER-CU42E0TUS
AC-SALTO-CONTROL-UNIT-IP-GREYCOVER-CU42E0GUS
AC-SALTO-CONTROL-UNIT-IP-NOCOVER-CU42E0US
AC-SALTO-CONTROL-UNIT-RS485-CLEARCOVER-CU4200TUS
AC-SALTO-CONTROL-UNIT-RS485-GREYCOVER-CU4200GUS
AC-SALTO-CONTROL-UNIT-RS485-NOCOVER-CU4200US
AC-SALTO-COPLE95IMCA
AC-SALTO-COVER-PLATE-ANSI-WIDE-COPLE110IMCA
AC-SALTO-CREDENTIAL-BRACELET-WBM01KNL-5
AC-SALTO-CREDENTIAL-BRACELET-WBM01KNM-5
AC-SALTO-CREDENTIAL-BRACELET-WBM01KNS-5
AC-SALTO-CREDENTIAL-CARD-MIFARE-PCM04KB
AC-SALTO-CREDENTIAL-CONSTRUCTION-HID-PCH002C
AC-SALTO-CREDENTIAL-CONSTRUCTION-MIFARE-PCM01KC
AC-SALTO-CREDENTIAL-CR80-CARD-HID-ICLASS-PCH004-50
AC-SALTO-CREDENTIAL-CR80-CARD-MIFARE-PCD04KB-50
AC-SALTO-CREDENTIAL-CR80-CARD-MIFARE-PCM01KB-50
AC-SALTO-CREDENTIAL-CR80-CARD-MIFARE-PCM04KBH-50
AC-SALTO-CREDENTIAL-FOB-DESFIRE-PFD04KB-10
AC-SALTO-CREDENTIAL-FOB-DESFIRE-PFD04KN-10
AC-SALTO-CREDENTIAL-FOB-MIFARE-PFM04KB-10
AC-SALTO-CREDENTIAL-FOB-SVN-BLUE-PFD04KBSVNKS-5
AC-SALTO-CREDENTIAL-FOB-SVN-GREEN-PFD04KGSVNKS-5
AC-SALTO-CREDENTIAL-FOB-SVN-RED-PFD04KRSVNKS-5
AC-SALTO-CREDENTIAL-FOB-SVN-SILVER-PFD04KSSVNKS-5
AC-SALTO-CREDENTIAL-FOB-SVN-WHITE-PFD04KWSVNKS-5
AC-SALTO-CYLINDRICAL-CARTRIDGE-ALIGNMENT-KIT-1848
AC-SALTO-CYLINDRICAL-CARTRIDGE-LOCK-LC1KC60IM
AC-SALTO-CYLINDRICAL-CARTRIDGE-LOCK-LC1KC70IM
AC-SALTO-DEADBOLT-GEO-LD51C70CS
AC-SALTO-DEADBOLT-NEO-LD51C60CS
AC-SALTO-DEADBOLT-NEO-NBB3141N00CSBN
AC-SALTO-DOOR-DETECTOR-ESCUTCHEON-RFDTCTS18W01
AC-SALTO-DOOR-DETECTOR-ESCUTCHEON-RFDTCTW18W01
AC-SALTO-ELEVATOR-FEATURE-SOFTWARE-SPACE-OPT-0035
AC-SALTO-EMERGENCY-POWER-SUPPLY-EPS100
AC-SALTO-ENCODER-DESFIRE-EC904B0US
AC-SALTO-ENCODER-DESFIRE-ECB04B0US
AC-SALTO-ENCODER-HID-ECJ04B0US

AC-SALTO-EXPANSION-UNIT-RS485-NOCOVER-CU4EB8US
AC-SALTO-INSTALLATION-TOOL-NEO-SP220764
AC-SALTO-INSTALLATION-TOOL-NEO-SP225542
AC-SALTO-LOCKER-LOCK-DEFIRE-ANTHRASITE-LB050A30
AC-SALTO-LOCKER-LOCK-DEFIRE-WHITE-LB050M30
AC-SALTO-LOCKER-LOCK-HID-ANTHRACITE-LJ050A30
AC-SALTO-LOCKER-LOCK-HID-WHITE-LJ050M30
AC-SALTO-LOCKSET-PIN-SPO1047-325
AC-SALTO-MOBILE-USER-LICENSE-SPACE-OPT-0016-1
AC-SALTO-MODULAR-XS-WALL-READER-WRMB004B
AC-SALTO-MORTISE-LOCK-LA1T0570A21IM8LH
AC-SALTO-MORTISE-LOCK-LA1T0570A21IM8RH
AC-SALTO-MORTISE-LOCK-LA1T0570A71IM8RH
AC-SALTO-MORTISE-LOCK-LA1T0770A22IMSLH
AC-SALTO-MORTISE-LOCK-LA1T0770A22IMSLR
AC-SALTO-MORTISE-LOCK-LA1T0770A22IMSRH
AC-SALTO-MORTISE-LOCK-LA1T0770A22IMSRR
AC-SALTO-MORTISE-LOCK-LA1T0770A24IMSLH
AC-SALTO-MORTISE-LOCK-LA1T0770A24IMSLR
AC-SALTO-MORTISE-LOCK-LA1T0770A24IMSRH
AC-SALTO-MORTISE-LOCK-LA1T0770A24IMSRR
AC-SALTO-MORTISE-LOCK-LA1T1570A21IM8LH
AC-SALTO-MORTISE-LOCK-LA1T1570A21IM8RH
AC-SALTO-MORTISE-LOCK-LA1T1570A21PM8LH
AC-SALTO-MORTISE-LOCK-LA1T1570A21PM8RH
AC-SALTO-MORTISE-LOCK-LA1T1570A71IM8R
AC-SALTO-MORTISE-LOCK-LA1T3570A21IM8LH
AC-SALTO-MORTISE-LOCK-LA1T3570A21IM8RH
AC-SALTO-NEO-CAM-CYL-NJCL119M28BCBA
AC-SALTO-NEO-CAM-CYL-NJCL119M28BCBAR
AC-SALTO-NEO-CAM-CYL-NJCL119M28CPBA
AC-SALTO-NEO-CAM-CYL-NJCL119M28CPBAR
AC-SALTO-NEO-CAM-CYL-NJCL119M28CSBA
AC-SALTO-NEO-CAM-CYL-NJCL119M28CSBAR
AC-SALTO-NEO-CAM-LOCK-CYLINDER-NMCL119M40BCBA
AC-SALTO-NEO-CINLINDER-RIM-ANSI-NMB1100N00CSBN
AC-SALTO-NEO-CYLINDER-ANSI-NMB1100N00BCBN
AC-SALTO-NEO-CYLINDER-ANSI-NMB1100N00BCBNR
AC-SALTO-NEO-DEADBOLT-CYLINDER-ANSI-NMB3141N00CSBN
AC-SALTO-NEO-DEADBOLT-CYLINDER-ANSI-NMB3151N00CSBN
AC-SALTO-NEO-MORTISE-ANSI-NMM1132N00BCBN
AC-SALTO-NEO-MORTISE-ANSI-NMM1132N00BCBNR
AC-SALTO-NEO-MORTISE-ANSI-NMM1135N00CSBN
AC-SALTO-NEO-MORTISE-ANSI-NMM1135N00CSBNR
AC-SALTO-NEO-MORTISE-CYL-NBM1132N00NEBNR
AC-SALTO-NEO-MORTISE-CYL-NBM1135N00CSBNR
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00BCBN

AC-SALTO-NEO-MORTISE-CYL-NJM1132N00BCBNR
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00CPBN
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00CPBNR
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00CSBN
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00CSBNR
AC-SALTO-NEO-PADLOCK-G4-NMP4P60150CPB1
AC-SALTO-NEO-PADLOCK-G4-NMP4R60150CPB0
AC-SALTO-NEO-RIM-CYL-BLKRDR-NBB3151N00BCBN
AC-SALTO-NEO-RIM-CYL-BLKRDR-NBB3151N00BCBNR
AC-SALTO-NEO-SERVER-RACK-CYL-NJE9130N00NEBR
AC-SALTO-NEO-SERVER-RACK-CYL-NJE9130N00NEBRR
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00BCBN
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00BCBNR
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00CPBN
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00CPBNR
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00CSBN
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00CSBNR
AC-SALTO-NEOXX-PADLOCK-HID-ICLASS-NJP4R60150CPB0
AC-SALTO-OUTDOOR-KIT-XS4-ESCUTCHEON-SP220475-6
AC-SALTO-PORTABLE-PROGRAMMING-DEVICE-PPD800
AC-SALTO-PRO-ACCESS-STARTER-KIT-SPAONLMBMB
AC-SALTO-PROACCESS-SPACE-SOFTWARE-SPACE-OPT-0032
AC-SALTO-PROACCESS-SPACE-SOFTWARE-SPAONLINE
AC-SALTO-PROACCESS-SPACE-SOFTWARE-SPAPART
AC-SALTO-PROACCESS-SPACE-STARTER-KIT-SPAONLABAB
AC-SALTO-RFNET-BLACK-GATEWAYB2CUS
AC-SALTO-RFNET-WHITE-GATEWAYW2CUS
AC-SALTO-RIM-PB-PBF110033IM
AC-SALTO-RIM-PB-PBF110045IM
AC-SALTO-SAMKIT9
AC-SALTO-SAMKITH
AC-SALTO-SHACKLE-CHAIN-NEOXX-PADLOCK-SP226335
AC-SALTO-SHIP-OPTION-SPACE-OPT-0018
AC-SALTO-SP226850
AC-SALTO-SPACE-RING-SILVER-SP226077-S-10
AC-SALTO-SPACE-TRAINING-KIT-TR-SPACE-V1
AC-SALTO-SPACER-PLATE-SP226233.02-BM
AC-SALTO-STICKERS-SMARTCARD-PSD04K-20
AC-SALTO-STICKERS-SMARTCARD-PSM04K-20
AC-SALTO-THUMBTURN-SP01027-IM
AC-SALTO-UPDATER-KIT-UBOX42DBABTUS
AC-SALTO-UPDATER-KIT-UBOX42DBMBTUS
AC-SALTO-WALL-READER-DESFIRE-WHITE-WRDB0A4W
AC-SALTO-WALL-READER-ICLASS-BLACK-WRDJ0A4B
AC-SALTO-WALL-READER-ICLASS-WHITE-WRDJ0A4W
AC-SALTO-WALL-READER-MULLION-DESFIR-WHITE-WRDB0M4W
AC-SALTO-WALL-READER-MULLION-ICLASS-BLACK-WRDJ0M4B

AC-SALTO-WALL-READER-MULLION-ICLASS-WHITE-WRDJ0M4W
AC-SALTO-WALL-READER-PANEL-MOUNT-DESFIRE-WRDBOP40
AC-SALTO-WIRELESS-NODE-BLUENET-RFNODE3
AC-SALTO-WIRELESS-NODE-RFNET-RFNODE
AC-SALTO-WIRELESS-OPTION-BLUENET-SPACE-OPT-0033
AC-SALTO-WIRELESS-OPTION-RF-SPACE-OPT-0021
AC-SALTO-WIRELESS-REPEATER-BLUENET-REPEATER03US
AC-SALTO-XS4-ANSI-MINI-CJ250N60BCB3
AC-SALTO-XS4-ANSI-MINI-CJ250N60CPB3
AC-SALTO-XS4-ANSI-MINI-CJ250N60CSB3
AC-SALTO-XS4-ANSI-MINI-CM250G70CSB3
AC-SALTO-XS4-ANSI-MINI-CM250N60BCB3
AC-SALTO-XS4-ANSI-MINI-CM250N60CSB3
AC-SALTO-XS4-ANSI-MINI-CM250N70CSB3
AC-SALTO-XS4-ANSI-MINI-CM260G70CSB3
AC-SALTO-XS4-ANSI-MINI-CM260G70CSB4
AC-SALTO-XS4-ANSI-MINI-CM260N70CSB3
AC-SALTO-XS4-CABLE-SP01045-100
AC-SALTO-XS4-CREDENTIAL-UHF-WINDSHLD-TRPDR-PWU008B
AC-SALTO-XS4-ESCUTCHEON-KEYPAD-ANSI-AB650G00IM38WK
AC-SALTO-XS4-ONE-ESCUTCHEON-DEADLAT-EB756HDLIMB4MD5
AC-SALTO-XS4-OP-ESCUTCHEON-ANSI-AM660W00IMB48G
AC-SALTO-XS4-OP-ESCUTCHEON-BIOCOTE-AM656N00BCB38
AC-SALTO-XS4-OP-ESCUTCHEON-BIOCOTE-AM656N00BCB48
AC-SALTO-XS4-OP-ESCUTCHEON-BIOCOTE-AM658N61BCB38
AC-SALTO-XS4-OP-ESCUTCHEON-BIOCOTE-AM658N62BCB38
AC-SALTO-XS4-OP-ESCUTCHEON-DC-KIT-SP01798-C8-4
AC-SALTO-XS4-OP-HALF-ESCUTCH-ANSI-AM660A00IMBH8E5
AC-SALTO-XS4-OP-HALF-ESCUTCH-ANSI-AM660W00PMBH8E5
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM650A00BCWH8
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM650A00IMBH8
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM650G00IMBH8
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM650G00IMBP8
AC-SALTO-XS4-OP-HALF-ESCUTCHN-ANSI-AM650G00IMBH8E5
AC-SALTO-XS4-OP-HALF-ESCUTCHN-ANSI-AM650N00IMBH8E5
AC-SALTO-XS4-OP-HALF-ESCUTCHN-ANSI-AM660B00IMBH8E5
AC-SALTO-XS4-OP-HALF-ESCUTCHN-ANSI-AM660J00IMBH8
AC-SALTO-XS4-OP-HALFESCUTCHEONANSI-AM650W00DBBH8E5
AC-SALTO-XS4-OP-HALFESCUTCHEONANSI-AM650W00IMBH8E5
AC-SALTO-XS4-OP-HALFESCUTCHEONANSI-AM660W00IMBH8E5
AC-SALTO-XS4-OP-HALFESCUTHEON-ANSI-AM660N00IMBH8
AC-SALTO-XS4-OP-HALFESCUTHEON-ANSI-AM660N00IMBH8E5
AC-SALTO-XS4-OP-HALFESCUTHEON-ANSI-AM660N00IMBP8
AC-SALTO-XS4-OP-PANIC-BAR-BIOCOTE-AM650N00BCBH8
AC-SALTO-XS4-OP-PANIC-BAR-BIOCOTE-AM650N00BCBP8
AC-SALTO-XS4-OP-PANIC-BAR-KIT-CR-KPP17IM
AC-SALTO-XS4-OP-PANIC-BAR-KIT-DK-KPP55IM

AC-SALTO-XS4-OP-PANIC-BAR-KIT-DORMA-KPP19IM
AC-SALTO-XS4-OP-PANIC-BAR-KIT-SAR-KPP08IM
AC-SALTO-XS4-OP-PANIC-BAR-KIT-SAR-KPP39IM
AC-SALTO-XS4-OP-PANIC-BAR-KIT-VD-KPB03IM-U
AC-SALTO-XS4-OP-PANIC-BAR-KIT-VD-KPP03IM
AC-SALTO-XS4-OP-PANIC-BAR-KIT-VD-KPP04IM
AC-SALTO-XS4-OP-PANIC-BAR-KIT-VD-KPP37IM
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00BCB38E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB38E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB48E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650N00IMBH8
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM658A62IMB38E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM658A62IMB48E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660U00IMB38E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM666A00IMB48E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM668U62IMB48E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660N00IMB48E5G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB48
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB48G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMBH8E5
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650G00IMB38E5
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650G00IMB48
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650N00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650N00IMB38E5
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650W00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650W00IMBH8
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650W00NEB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650W00NEBH8
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM656A00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM656A00IMB48
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM656A00IMB48G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM656G00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM656N00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM656N00IMB38G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM656W00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM658N62DBB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM658N62IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM658N62IMB48
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660A00IMB38E5
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660A00IMB3SG
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660G00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660G00IMB48
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660J00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM666A00IMB48G
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM666G00IMB38
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM666N00BCB38

AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM666N00IMB38
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM666N00IMB38G
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM666N00IMB48
AC-SALTO-XS4-OP-WB-ESCUTCHEONANSI-AM658N62IMB38E5G
AC-SALTO-XS4-OP-WB-ESCUTCHEONANSI-AM660A00IMB48E5G
AC-SALTO-XS4-OP-WB-ESCUTCHEONANSI-AM668U61IMW38E5G
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM660N00IMB38E5
AC-SALTO-XS4-OP-WBESCUTCHEON-ANSI-AM650N00IMB38E5G
AC-SALTO-XS4-PB-KIT-CR-KPB17IM
AC-SALTO-XS4-PB-KIT-SG-KPB08IM
AC-SALTO-XS4-PB-KIT-SG-KPB08IMW
AC-SALTO-XS4-PB-KIT-VD-KPB03IM
AC-SALTO-XS4-PB-KIT-VD-KPB04IM
AC-SALTO-XS4-PB-KIT-VONDUPRIN-98-99-KPB03IMW
AC-SALTO-XS4-READER-UHF-LD-WRLUD24BUS
AC-SALTO-XS4-UHF-LD-CONNECTION-CABLE-10M-WRLUD-C10
AC-SALTO-XS4-UHF-LD-SIC-MODULE-CONVERTR-WRLUD-SIC1
AC-HID-EL-96000-SVM10
AC-HID-EL-96300-ADM10
AC-HID-EL-97000-EKIOSK
AC-HID-EL-98000-EADV10
AC-HID-EL-ACI-AVIG
AC-HID-EL-ACI-UPGRD
AC-HID-EL-AST-ID150
AC-HID-EL-AST-ID150A
AC-HID-EL-AST-UPDATEA
AC-HID-EL-DESKO-ICON
AC-HID-EL-DYMO-30856
AC-HID-EL-DYMO-30911
AC-HID-EL-DYMO-450T
AC-HID-EL-DYMO-550
AC-HID-EL-EADV-UPGRD
AC-HID-EL-K12-SVM
AC-HID-EL-SOS-K12
AC-HID-EL-SS-R2
AC-HID-EL-SSA-ACIS
AC-HID-EL-SSA-EADVS
AC-HID-EL-SSA-K12S
AC-HID-EL-SSA-SVMS
AC-HID-EL-SVM10-UPGRD
AC-HID-EL-TOP-1X5
AC-SW-ACM-DEMO-30D-6-P
AC-SW-LIC-16RCU-6-P
AC-SW-LIC-AF-6-P
AC-SW-LIC-BDGE-6-P
AC-SW-LIC-PART-6-P
AC-SW-LIC-REP-6-P

AC-SW-LIC-REST-6-P
AC-SW-LIC-WIRELESS-LOCK-6-P
UA-SW-LIC-1000DOORS
UA-SW-LIC-100DOORS
UA-SW-LIC-10DOORS
UA-SW-LIC-1DOORS
UA-SW-LIC-ALL-IN-ADDON
UA-SW-LIC-AVAILABILITY-ADDON
UA-SW-LIC-AWARENESS-ADDON
UA-SW-LIC-BASE-PACK
UA-SW-LIC-DATA-ADDON
UA-SW-LIC-INTEGRATIONS-ADDON
UA-SW-LIC-SERVICE-PLAN-1000-1Y
UA-SW-LIC-SERVICE-PLAN-1000-3Y
UA-SW-LIC-SERVICE-PLAN-1000-5Y
UA-SW-LIC-SERVICE-PLAN-2000-1Y
UA-SW-LIC-SERVICE-PLAN-2000-3Y
UA-SW-LIC-SERVICE-PLAN-2000-5Y
UA-SW-LIC-SERVICE-PLAN-250-1Y
UA-SW-LIC-SERVICE-PLAN-250-3Y
UA-SW-LIC-SERVICE-PLAN-250-5Y
UA-SW-LIC-SERVICE-PLAN-4000-1Y
UA-SW-LIC-SERVICE-PLAN-4000-3Y
UA-SW-LIC-SERVICE-PLAN-4000-5Y
UA-SW-LIC-UPGRADE-PLAN-1000-1Y
UA-SW-LIC-UPGRADE-PLAN-2000-1Y
UA-SW-LIC-UPGRADE-PLAN-250-1Y
UA-SW-LIC-WIRELESS-LOCK
AC-SW-LIC-LDAP-6-P
AC-SW-LIC-ORCL-6-P
AC-SW-LIC-SQL-6-P
AC-SW-LIC-XML-6-P
AC-SW-LIC-ACMEC-MIG-6-P
AC-SW-LIC-BOSCHINTR-10PANEL-6-P
AC-SW-LIC-BOSCHINTR-1PANEL-6-P
AC-SW-LIC-DMPINTR-10PANEL-6-P
AC-SW-LIC-DMPINTR-1PANEL-6-P
AC-SW-LIC-HID-VERTEX-ASM-6-P
AC-SW-LIC-VIRDI-BIO-6-P
AC-SW-LIC-EXACQ-6-P
AC-SW-LIC-MILEST-6-P
AC-SW-LIC-AVO-VER-16VS-6-P
AC-SW-LIC-AVO-VER-5VS-6-P
AC-APP-1024R-ENT-PLUS-6
AC-APP-16R-ENT-PLUS-6
AC-APP-2048R-ENT-PLUS-6
AC-APP-512R-ENT-PLUS-6

AC-APP-ENT-PLUS-WARR-EXTEND-1YR
AC-APP-ENT-PLUS-WARR-EXTEND-2YR
UA-APP-ENT-PLUS-7
UA-APP-ENT-PLUS-WARR-EXTEND-1YR
UA-APP-ENT-PLUS-WARR-EXTEND-2YR
AC-APP-ENT2-WARR-EXTEND-1YR
AC-APP-ENT2-WARR-EXTEND-2YR
UA-APP-ENT-7
UA-APP-ENT-WARR-EXTEND-1YR
UA-APP-ENT-WARR-EXTEND-2YR
AC-APP-PRO-WARR-EXTEND-1YR
AC-APP-PRO-WARR-EXTEND-2YR
UA-APP-PRO-7
UA-APP-PRO-WARR-EXTEND-1YR
UA-APP-PRO-WARR-EXTEND-2YR
AC-SW-1024R-VM-6-P
AC-SW-128R-VM-6-P
AC-SW-16R-VM-6-P
AC-SW-2048R-VM-6-P
AC-SW-256R-VM-6-P
AC-SW-32R-VM-6-P
AC-SW-512R-VM-6-P
AC-SW-64R-VM-6-P
UA-SW-LIC-APP-VIRTUAL-HYPERV
UA-SW-LIC-APP-VIRTUAL-VMWARE
AC-MER-A-RES-1K32
AC-MER-A-TC-MR50
AC-MER-A-TERM5-3
AC-MER-A-TERM5-4
AC-MER-A-TERM5-5
AC-MER-A-TERM5-6
AC-MER-CON-MR16IN
AC-MER-CON-MR16OUT
AC-MER-CON-MR50
AC-MER-CON-MR52-S3B
AC-MER-CONT-LP4502
AC-MER-CONT-MP1501
AC-MER-CONT-MP1502
AC-MER-CONT-MP2500
AC-MER-CONT-MP4502
AC-MER-M5-16DO-1
AC-MER-M5-20IN-1
AC-MER-M5-2K
AC-MER-M5-2K-BASE
AC-MER-M5-2SRP-1
AC-MER-M5-8RP-1
AC-MER-M5-IC-1

AC-MER-MUX8
AC-MER-RIM-MR62E
AC-STID-CARD-CCTW490
AC-ALL-SCH-FOB-9651
AC-ALL-SCH-FOB-9651T
AC-ING-CARD-APTIQ-XF9520
AC-ING-CARD-APTIQ-XF9551
AC-ING-FOB-APTIQ-XF7610
AC-SCH-CARD-8543
AC-SCH-CARD-8543M1
AC-SCH-CARD-MT-8943
AC-SCH-FOB-8643T
AC-SCH-FOB-MT-8843T
AC-FP-CARD-CONEKT-CSM-2P
AC-FP-CARD-CSC-2
AC-FP-CARD-CSM-2S
AC-FP-CARD-DC1-1
AC-FP-CARD-DC4-1
AC-FP-CARD-DE2
AC-FP-CARD-DM1-3
AC-FP-CARD-DM1-3S
AC-FP-CARD-DM4-3
AC-FP-CARD-DM4-3S
AC-FP-CARD-PSC-1-H
AC-FP-CARD-PSI-4-H
AC-FP-CARD-PSM-2P-H
AC-FP-CARD-PSM-2S-H
AC-FP-CONEKT-CMC-2-25
AC-FP-FOB-CSK-2
AC-FP-FOB-DK1-3
AC-FP-FOB-DK4-3
AC-FP-TAG-PDT-1-H
AC-FP-TAG-PSK-3-H
AC-FP-TRANS-LONG-RANGE-WRT-2+D2
AC-FP-TRANS-LONG-RANGE-WRT-2+S1
AC-FP-TRANS-LONG-RANGE-WRT-2+S4
AC-FP-TRANS-LONG-RANGE-WRT-2M
AC-FP-TRANS-LONG-RANGE-WRT-4+S4
AC-FP-TRANS-LONG-RANGE-WRT-4+SI
AC-FP-TRANS-WRT-2+H
AC-FP-TRANS-WRT-4+H
AC-HID-CARD-2122BGGMNN
AC-HID-CARD-3000PG1MN
AC-HID-CARD-3150RGGMNM
AC-HID-CARD-ADMIN-SEC9X-CRD-0-005J
AC-HID-CARD-DUOPROXII-CL
AC-HID-CARD-ICLASS-2000

AC-HID-CARD-ICLASS-2002
AC-HID-CARD-ICLASS-2004
AC-HID-CARD-ICLASS-2050
AC-HID-CARD-ICLASS-2080
AC-HID-CARD-ICLASS-2100
AC-HID-CARD-ICLASS-3000PGGMB
AC-HID-CARD-ICLASS-3000PGGMV
AC-HID-CARD-ICLASS-3050PGGMN
AC-HID-CARD-ICLASS-3350PMSMV
AC-HID-CARD-ICLASS-PROX-2120BG1MNN
AC-HID-CARD-ICLASS-PROX-2120BGGMNM
AC-HID-CARD-ICLASS-PROX-2120BGGMVM
AC-HID-CARD-ICLASS-PROX-3150RGGMNN
AC-HID-CARD-ICLASS-SE-3000
AC-HID-CARD-ICLASS-SE-3000-AVG
AC-HID-CARD-ICLASS-SE-3000-AVG-NL
AC-HID-CARD-ICLASS-SE-3002
AC-HID-CARD-ICLASS-SE-3004
AC-HID-CARD-ICLASS-SE-UHF-6014SGGANN
AC-HID-CARD-ICLASS-SEOS-5005PG1MN
AC-HID-CARD-ICLASS-SR-2080
AC-HID-CARD-ICLASS-UHF-600TGGAN
AC-HID-CARD-ISOPROXII-GRPH
AC-HID-CARD-MIFARE-DESFIRE-EV3-801FPGGAN
AC-HID-CARD-MOB-ADMIN-SEC9X-CRD-MADD
AC-HID-CARD-MOB-SEC9X-CRD-E-MKYD
AC-HID-CARD-PROXCARDII-CL
AC-HID-CARD-SEOS-5005PGGMN
AC-HID-CARD-SEOS-5005PGGSN
AC-HID-CARD-SEOS-5006PG1MN
AC-HID-CARD-SEOS-5006PGCMN-AVG
AC-HID-CARD-SEOS-5006PGGMN
AC-HID-CARD-SEOS-5006PGGMN-AVG
AC-HID-CARD-SEOS-5006PGGNN
AC-HID-CARD-SEOS-5006PGGSN
AC-HID-CARD-SEOS-5656PMSAV
AC-HID-CARD-SEOS-ICLASS-PROX-5105PGGMNN
AC-HID-CARD-SEOS-ICLASS-PROX-5105PGGNNN
AC-HID-CARD-SEOS-ICLASS-PROX-5105RG1MNM
AC-HID-CARD-SEOS-ICLASS-PROX-5105RG1MNN
AC-HID-CARD-SEOS-ICLASS-PROX-5105RG1NNM
AC-HID-CARD-SEOS-ICLASS-PROX-5105RGGMNM
AC-HID-CARD-SEOS-ICLASS-PROX-5105RGGMNN
AC-HID-CARD-SEOS-ICLASS-PROX-5105RGGNNS
AC-HID-CARD-SEOS-ICLASS-PROX-5105RGGSN
AC-HID-CARD-SEOS-ICLASS-PROX-5106PG1MNN
AC-HID-CARD-SEOS-ICLASS-PROX-5106PGGMNN

AC-HID-CARD-SEOS-ICLASS-PROX-5106PGGNNN
AC-HID-CARD-SEOS-ICLASS-PROX-5106RGGMNM
AC-HID-CARD-SEOS-ICLASS-PROX-5106RGGMNN
AC-HID-CARD-SEOS-ICLASS-PROX-5106RGGNNN
AC-HID-ELITE-FEE-MC-0036
AC-HID-FOB-3250PNNMN
AC-HID-FOB-ICLASS-3250PNNMN-AVG
AC-HID-FOB-PROXKEYIII-CL
AC-HID-FOB-SEOS-5266PNNA-AVG
AC-HID-MOB-MID-SUB-T100
AC-HID-MOB-MID-SUB-T100-ADD
AC-HID-MOB-MID-SUB-T100-ADD-1-MONTH
AC-HID-TAG-ICLASS-SE-3300
AC-HID-TAG-MICROPROX-ADH
AC-HID-TAG-PROXPASSII-VEH
AC-HID-CARD-DESFIRE-EV3-802FPGGAN
AC-HID-CARD-ICLASS-2000HPGGAV
AC-HID-CORP1K-MC-1000
AC-STID-CARD-NONPROGRAMED-CCTW670
AC-STID-KEYFOB-NONPROGRAMED-PCGW671
AC-STID-TAG-UHF-WINDSHIELD-ETA-W75B-574BE10
AC-LSP-16DR-MER
AC-LSP-16DR-MER-LCK
AC-LSP-2DR-MER
AC-LSP-2DR-MER-LCK
AC-LSP-4DR-MER
AC-LSP-4DR-MER-LCK
AC-LSP-8DR-MER
AC-LSP-8DR-MER-LCK
AC-LSP-B100
AC-LSP-C4
AC-LSP-C8
AC-LSP-CAMLOCKSET
AC-LSP-D8P
AC-LSP-E1M
AC-LSP-E2-BOXED
AC-LSP-E2-BS1
AC-LSP-E2M
AC-LSP-E4-3BS1
AC-LSP-E4M
AC-LSP-E4M1
AC-LSP-E4V
AC-LSP-E4V1
AC-LSP-E6M-BOXED
AC-LSP-E6M1-BOXED
AC-LSP-E8M-BOXED
AC-LSP-E8M2-BOXED

AC-LSP-EPLT-1M
AC-LSP-F8
AC-LSP-F8P
AC-LSP-FPO150
AC-LSP-FPO150-8DR-DV
AC-LSP-FPO150-8DR-SV
AC-LSP-FPO150-B1002D8PM8NL4E4M/T8-C
AC-LSP-FPO150-B100C82D8PE4M-T8-A
AC-LSP-FPO150-B100C8D8E4-4SL1
AC-LSP-FPO150-B100C8D8NL4E4M
AC-LSP-FPO150-B100C8P2D8PE4M-T8-A
AC-LSP-FPO150-B100D8M8NL4E4-4SL1
AC-LSP-FPO150-B100D8PM8NL4E4M
AC-LSP-FPO150-B100D8PM8NL4E6M
AC-LSP-FPO150-PS
AC-LSP-FPO150/150-16DR-DV
AC-LSP-FPO150/250-2D82M8NL4E6M1
AC-LSP-FPO150/250-2D8P2M8NL4E4M1
AC-LSP-FPO150/250-2D8P2M8NL4E6M1
AC-LSP-FPO150/250-2D8P2M8NL4E8M2
AC-LSP-FPO150/250-3D8P2M8NL4E4M1/T16-A
AC-LSP-FPO150/250-3D8P2M8NL4E4M1/T16-C
AC-LSP-FPO150/250-3D8P2M8NL4E8M2/P16-B
AC-LSP-FPO150-B100-2D8PM8NL4E4M1-P8-A
AC-LSP-FPO250
AC-LSP-FPO250-16DR-SV
AC-LSP-FPO250-2M8PNL4E4M
AC-LSP-FPO250-B100D8PM8NL4E6M
AC-LSP-FPO250-M8PNL4E4M-NU02
AC-LSP-FPO250/250-16DR-DV
AC-LSP-FPO250/250-3C85D8PE12M/T24-A
AC-LSP-FPO250/250-4M8PNLXE8M2-NU01
AC-LSP-FPO250/250-5M8NLXE8M2/P16-A
AC-LSP-FPO250/250-NLXE4M
AC-LSP-FPO250/250-NLXE8M2
AC-LSP-FPO75
AC-LSP-FPO75-2D8E2-5SL1
AC-LSP-FPO75-2E2M
AC-LSP-FPO75-4DR-SV
AC-LSP-FPO75-B100C4D8NL4E2M
AC-LSP-FPO75-B100C4E1-2SL1
AC-LSP-FPO75-B100C8D8E2-3SL1
AC-LSP-FPO75-B100M8NL4E2M
AC-LSP-FPO75-B100M8PNL4E2M-WP-FCS04
AC-LSP-FPO75-D8E1-2SL1
AC-LSP-FPO75-D8E2-4SL1
AC-LSP-FPO75-E1M

AC-LSP-FPO75-E2M
AC-LSP-FPO75/150-D8M8NL4E4M1
AC-LSP-FPO75/75-8DR-DV
AC-LSP-M8
AC-LSP-MSM25
AC-LSP-NL4
AC-LSP-NLX-BOXED
AC-LSP-OSE-16DR-MER
AC-LSP-OSE-16DR-MER-IO
AC-LSP-OSE-16DR-MER-LCK
AC-LSP-OSE-16DR-MER-LCK-IO
AC-LSP-PS-MCLASS-E5M
AC-LSP-RACK-MOUNT-MERC-RGM75-D8PNZ
AC-LSP-RACK-MOUNT-MERC-RGM75-D8PZ
AC-LSP-RACK-MOUNT-MERC-RGM75-M8PNZ
AC-LSP-RACK-MOUNT-MERC-RGM75B-C4PNZ
AC-LSP-RACK-MOUNT-MERC-RGM75B-C4PZ
AC-LSP-RACK-MOUNT-MERC-RGM75B-M8PNZ
AC-LSP-RACK-MOUNT-RGM75B-M8PNZ1
AC-LSP-RM-BAT-RBE
AC-LSP-SDU
AC-LSP-WALL-MOUNT-FPO150-B100C8D8E2M
AC-LSP-WALL-MOUNT-FPO75-B100C4D8NL2E2M
AC-LSP-WIRED-FPO150-B1002D8PM8NL4E6M/P8-A
AC-LSP-WIRED-FPO150-B100C82D8PE6M/P8-A
AC-LSP-WIRED-FPO150/250-2C83D8PE8M2/P16-A
AC-LSP-WIRED-FPO150/250-2C83D8PE8M2/P16-C
AC-LSP-WIRED-FPO150/250-3D8P2M8NL4E8M2/P16-A
AC-LSP-WIRED-FPO150/250-3D8P2M8NL4E8M2/P16-C
AC-RO-SMALL-ENC
AC-PRO-HM-1024
AC-PRO-HM-2048
AC-PRO-HM-256
AC-PRO-HM-512
AC-PRO-MIG-LDAP
AC-PRO-MIG-ORCL
AC-PRO-MIG-SQL
AC-PRO-MIGF-LDAP
AC-PRO-MIGF-ORCL
AC-PRO-MIGF-SQL
AC-PRO-SYNC-AD-AZURE
AC-PRO-SYNC-AD-GEN
AC-PRO-SYNC-CUSTOM
AC-PRO-SYNC-LDAP
AC-PRO-SYNC-ORCL
AC-PRO-SYNC-SQL
AC-STID-READER-ANT-SPECTRE-B

AC-STID-READER-ETA-W75B-574BE10P
AC-STID-READER-SLA-R51-A/U04-3I/1
AC-STID-READER-SLA-W53-A/U04-7OS/1
AC-STID-SPECTRE-READER-MOUNT-KIT-KFX-UHF-08
AC-STID-SPECTRE-READER-MOUNT-KIT-KFX-UHF-09
AC-STID-SPECTRE-READER-MOUNT-KIT-KFX-UHF-10
AC-ALL-READ-APTIQ-OSDP-KEYPD-MTK15-485
AC-ALL-READ-APTIQ-OSDP-MULL-MT11-485
AC-ALL-READ-APTIQ-OSDP-SNG-MT15-485
AC-ALL-SCH-WPR400-MT
AC-ALL-SCH-WRI400
AC-ING-READ-APTIQ-MINI-SM10
AC-ING-READ-APTIQ-MULL-MT11
AC-SCH-READER-MTB11
AC-SCH-READER-MTB15
AC-SCH-READER-MTKB15
AC-FP-READ-CSR-35L-OSDP
AC-FP-READ-CSR-35L-WG
AC-FP-READ-DELTA-62-OSDP-F05552-600SCN
AC-FP-READ-DELTA-62-OSDP-F05662-600
AC-FP-READ-DELTA3-SECTOR
AC-FP-READ-DELTA5-OSDP
AC-FP-READ-DELTA5-SECTOR
AC-FP-READ-DELTA5.3-SECTOR
AC-FP-READ-DELTA6.4-SECTOR
AC-FP-READ-GIBRALTER-BR-P-453-HA
AC-FP-READ-GIBRALTER-BR-P-455-HA
AC-FP-READ-GUARDIAN-VR-P-403-HA
AC-FP-READ-GUARDIAN-VR-P-405-HA
AC-FP-READ-GUARDIAN-VR-P-410-HA
AC-FP-READ-P-300-H
AC-FP-READ-P-300-H-A
AC-FP-READ-P-500-H
AC-FP-READ-P-500-H-A
AC-FP-READ-P-640-H
AC-FP-READ-P-640-H-A
AC-FP-READ-P-640-H-OSDP
AC-FP-READ-P-710-H
AC-FP-READ-P-710-H-A
AC-FP-READ-P-900-H
AC-FP-READ-P-900-H-A
AC-FP-READ-PROX-EURO-P-530-HA
AC-FP-READ-PROX-KEYPAD-P-620-HA
AC-FP-READ-WG-MCR-50-H
AC-FP-READER-OSDP-EM-64-H
AC-FP-READER-P-300-H-OSDP
AC-FP-READER-P-500-H-OSDP

AC-FP-READER-PCR-620L-OSDP
AC-FP-READER-PCR-620L-WIEGAND
AC-FP-READER-PCR-640L-OSDP
AC-FP-READER-PCR-640L-WIEGAND
AC-FP-READER-WIEGAND-EM-64-H
AC-FP-REC-LONG-RANGE-WRR-22
AC-FP-REC-WRR-44
AC-HID-GASKET-IP65GSKT-R10
AC-HID-GASKET-IP65GSKT-R15
AC-HID-GASKET-IP65GSKT-R40
AC-HID-GASKET-IP65GSKT-RK40
AC-HID-ICLASS-SE-R40-920NTPNEK000FA
AC-HID-MCLASS-SE-PROX-OSDP-900PTPTEK00387
AC-HID-MCLASS-SE-PROX-OSDP-910PTPNEK00387
AC-HID-MCLASS-SE-PROX-OSDP-910PTPTEK00387
AC-HID-MCLASS-SE-PROX-OSDP-921PTPNEK00385
AC-HID-PIVCLASS-40HNKS-03-0005LE
AC-HID-PIVCLASS-40KHNS-03-0005LE
AC-HID-READ-ICLASS-SE-MOB-OSDP-900NMPNEKEA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-900NMPNEKMA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-900NMPTEKEA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-900NMPTEKMA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-910NMPNEKEA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-910NMPNEKMA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-910NMPTEKEA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-910NMPTEKMA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-920NMPNEKEA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-920NMPNEKMA005
AC-HID-READ-ICLASS-SE-MOB-OSDP-920NMPTEKMA005
AC-HID-READ-ICLASS-SE-MOB-WG-900NBNNEKE0000
AC-HID-READ-ICLASS-SE-MOB-WG-900NBNTEK20000
AC-HID-READ-ICLASS-SE-MOB-WG-900NBNTEKE0000
AC-HID-READ-ICLASS-SE-MOB-WG-900NMNNEKEA001
AC-HID-READ-ICLASS-SE-MOB-WG-900NMNTEKEA001
AC-HID-READ-ICLASS-SE-MOB-WG-910NMNNEKEA001
AC-HID-READ-ICLASS-SE-MOB-WG-910NMNTEKEA001
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNNEK20000
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNNEKE0000
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNNEKES077
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNTEK20000
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNTEKE0000
AC-HID-READ-ICLASS-SE-MOB-WG-920NMNNEKEA001
AC-HID-READ-ICLASS-SE-MOB-WG-920NMNTEKEA001
AC-HID-READ-ICLASS-SE-MOB-WG-921NBNNEKE0000
AC-HID-READ-ICLASS-SE-R10
AC-HID-READ-ICLASS-SE-R10-AVG
AC-HID-READ-ICLASS-SE-R40

AC-HID-READ-ICLASS-SE-R40-WG-920NSNNEK20000
AC-HID-READ-ICLASS-SE-R90-WG-940NNNTEK2037P
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK00000
AC-HID-READ-ICLASS-SE-RK40
AC-HID-READ-ICLASS-SE-RK40-WG-921NSNNEK20000
AC-HID-READ-ICLASS-SE-RP40
AC-HID-READ-ICLASS-SE-RP40-AVG
AC-HID-READ-ICLASS-SE-RPK40
AC-HID-READ-MAXIPROX
AC-HID-READ-MCLASS-SE-INDALA-900LTNNEK00017
AC-HID-READ-MCLASS-SE-INDALA-910LTNNEK00017
AC-HID-READ-MCLASS-SE-INDALA-920LTNNEK00017
AC-HID-READ-MCLASS-SE-MOB-OSDP-900PMPNEKEA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-900PMPNEKMA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-900PMPTEKEA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-900PMPTEKMA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-910PMPNEKEA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-910PMPNEKMA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-910PMPTEKEA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-920PMPNEKEA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-920PMPNEKMA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-920PMPTEKEA007
AC-HID-READ-MCLASS-SE-MOB-OSDP-920PMPTEKMA007
AC-HID-READ-MCLASS-SE-MOB-WG-900PBNNEK20000
AC-HID-READ-MCLASS-SE-MOB-WG-900PBNTEK20000
AC-HID-READ-MCLASS-SE-MOB-WG-900PMNNEKEA003
AC-HID-READ-MCLASS-SE-MOB-WG-900PMNNEKMA003
AC-HID-READ-MCLASS-SE-MOB-WG-900PMNTEKEA003
AC-HID-READ-MCLASS-SE-MOB-WG-900PMNTEKMA003
AC-HID-READ-MCLASS-SE-MOB-WG-910PBNNEK20000
AC-HID-READ-MCLASS-SE-MOB-WG-910PMNNEKEA003
AC-HID-READ-MCLASS-SE-MOB-WG-910PMNNEKMA003
AC-HID-READ-MCLASS-SE-MOB-WG-910PMNTEKEA003
AC-HID-READ-MCLASS-SE-MOB-WG-910PMNTEKMA003
AC-HID-READ-MCLASS-SE-MOB-WG-920PBNNEK20000
AC-HID-READ-MCLASS-SE-MOB-WG-920PBNTEK20000
AC-HID-READ-MCLASS-SE-MOB-WG-920PMNNEKMA003
AC-HID-READ-MCLASS-SE-MOB-WG-920PMNTEKEA003
AC-HID-READ-MCLASS-SE-MOB-WG-920PMNTEKMA003
AC-HID-READ-MCLASS-SE-PROX-WG-910PTNTEK00000
AC-HID-READ-MCLASS-SE-PROX-WG-920PTNTEK00000
AC-HID-READ-MCLASS-SE-PROX-WG-921PTNTEK00000
AC-HID-READ-MCLASS-WIEG-900PTNNEKE0000
AC-HID-READ-MCLASS-WIEG-910PTNNEKE0000
AC-HID-READ-MCLASS-WIEG-920PTNNEKE0000
AC-HID-READ-MCLASS-WIEG-921PTNNEKE0000
AC-HID-READ-MINIPROX

AC-HID-READ-OMNIKEY-R54270101
AC-HID-READ-PROXPRO
AC-HID-READ-PROXPRO-KEYPD
AC-HID-READ-PROXPROII
AC-HID-READ-THINLINE
AC-HID-READ-U90-ICLASS-SE-RDRSEU908K00000
AC-HID-READ-U90-ICLASS-SE-RDRSEU909K00000
AC-HID-READER-SIGNO-20KNKS-00-000000
AC-HID-READER-SIGNO-20KNKS-00-000000-AVG
AC-HID-READER-SIGNO-20KNKS-01-000000
AC-HID-READER-SIGNO-20KNKS-01-00001H
AC-HID-READER-SIGNO-20KNKS-02-000000
AC-HID-READER-SIGNO-20KNKS-02-000000-AVG
AC-HID-READER-SIGNO-20KNKS-02-0002BL
AC-HID-READER-SIGNO-20KNKS-T0-000000
AC-HID-READER-SIGNO-20KNKS-T1-000000
AC-HID-READER-SIGNO-20KNKS-T2-000000
AC-HID-READER-SIGNO-20KNKS-T3-00FD21
AC-HID-READER-SIGNO-20KTKS-00-000000
AC-HID-READER-SIGNO-20KTKS-00-000000-AVG
AC-HID-READER-SIGNO-20KTKS-01-000000
AC-HID-READER-SIGNO-20KTKS-01-000000-AVG
AC-HID-READER-SIGNO-20KTKS-01-00001H
AC-HID-READER-SIGNO-20KTKS-02-000000
AC-HID-READER-SIGNO-20KTKS-02-000000-AVG
AC-HID-READER-SIGNO-20KTKS-02-0002BL
AC-HID-READER-SIGNO-20KTKS-T0-000000
AC-HID-READER-SIGNO-20KTKS-T1-000000
AC-HID-READER-SIGNO-20KTKS-T2-000000
AC-HID-READER-SIGNO-20NKS-00-000000
AC-HID-READER-SIGNO-20NKS-00-000000-AVG
AC-HID-READER-SIGNO-20NKS-01-000000
AC-HID-READER-SIGNO-20NKS-01-00001H
AC-HID-READER-SIGNO-20NKS-02-000000
AC-HID-READER-SIGNO-20NKS-02-000000-AVG
AC-HID-READER-SIGNO-20NKS-02-0002BL
AC-HID-READER-SIGNO-20NKS-T0-000000
AC-HID-READER-SIGNO-20NKS-T1-000000
AC-HID-READER-SIGNO-20NKS-T2-000000
AC-HID-READER-SIGNO-20NKS-T3-00FD21
AC-HID-READER-SIGNO-20TKS-00-000000
AC-HID-READER-SIGNO-20TKS-00-000000-AVG
AC-HID-READER-SIGNO-20TKS-01-000000
AC-HID-READER-SIGNO-20TKS-01-000000-AVG
AC-HID-READER-SIGNO-20TKS-01-00001H
AC-HID-READER-SIGNO-20TKS-01-00001H-AVG
AC-HID-READER-SIGNO-20TKS-02-000000

AC-HID-READER-SIGNO-20TKS-02-000000-AVG
AC-HID-READER-SIGNO-20TKS-02-0002BL
AC-HID-READER-SIGNO-20TKS-T0-000000
AC-HID-READER-SIGNO-20TKS-T1-000000
AC-HID-READER-SIGNO-20TKS-T2-000000
AC-HID-READER-SIGNO-20TKS-T3-00FD21
AC-HID-READER-SIGNO-40KNKS-00-000000
AC-HID-READER-SIGNO-40KNKS-00-000000-AVG
AC-HID-READER-SIGNO-40KNKS-01-000000
AC-HID-READER-SIGNO-40KNKS-01-00001H
AC-HID-READER-SIGNO-40KNKS-02-000000
AC-HID-READER-SIGNO-40KNKS-02-000000-AVG
AC-HID-READER-SIGNO-40KNKS-02-0002BL
AC-HID-READER-SIGNO-40KNKS-T0-000000
AC-HID-READER-SIGNO-40KNKS-T1-000000
AC-HID-READER-SIGNO-40KNKS-T2-000000
AC-HID-READER-SIGNO-40KTKS-00-000000
AC-HID-READER-SIGNO-40KTKS-00-000000-AVG
AC-HID-READER-SIGNO-40KTKS-01-000000
AC-HID-READER-SIGNO-40KTKS-01-000000-AVG
AC-HID-READER-SIGNO-40KTKS-01-00001H
AC-HID-READER-SIGNO-40KTKS-02-000000
AC-HID-READER-SIGNO-40KTKS-02-000000-AVG
AC-HID-READER-SIGNO-40KTKS-02-0002BL
AC-HID-READER-SIGNO-40KTKS-T0-000000
AC-HID-READER-SIGNO-40KTKS-T1-000000
AC-HID-READER-SIGNO-40KTKS-T2-000000
AC-HID-READER-SIGNO-40NKS-00-000000
AC-HID-READER-SIGNO-40NKS-00-000000-AVG
AC-HID-READER-SIGNO-40NKS-01-000000
AC-HID-READER-SIGNO-40NKS-01-00001H
AC-HID-READER-SIGNO-40NKS-02-000000
AC-HID-READER-SIGNO-40NKS-02-000000-AVG
AC-HID-READER-SIGNO-40NKS-02-0002BL
AC-HID-READER-SIGNO-40NKS-T0-000000
AC-HID-READER-SIGNO-40NKS-T1-000000
AC-HID-READER-SIGNO-40NKS-T2-000000
AC-HID-READER-SIGNO-40NKS-T3-00FD21
AC-HID-READER-SIGNO-40TKS-00-000000
AC-HID-READER-SIGNO-40TKS-00-000000-AVG
AC-HID-READER-SIGNO-40TKS-01-000000
AC-HID-READER-SIGNO-40TKS-01-000000-AVG
AC-HID-READER-SIGNO-40TKS-01-00001H
AC-HID-READER-SIGNO-40TKS-01-00001H-AVG
AC-HID-READER-SIGNO-40TKS-02-000000
AC-HID-READER-SIGNO-40TKS-02-000000-AVG
AC-HID-READER-SIGNO-40TKS-02-0002BL

AC-HID-READER-SIGNO-40TKS-T0-000000
 AC-HID-READER-SIGNO-40TKS-T1-000000
 AC-HID-READER-SIGNO-40TKS-T2-000000
 AC-HID-READER-SIGNO-40TKS-T3-00FD21
 AC-HID-SPACER-05-R10-6132AKB-M
 AC-HID-SPACER-05-R15-6132AKC-M
 AC-HID-SPACER-05-R40-6132AKT-M
 AC-HID-SPACER-05-RK40-6132AKU-M
 AC-HID-SPACER-10-R40-6132AKE-M
 AC-HID-SPACER-SIGNO-20-K-05
 AC-HID-SPACER-SIGNO-40-K-05
 AC-HID-UPGKIT-BLEOSDP-UPG-A-920
 AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT
 AC-STID-EM+HID-LF-MODULE-SE810
 AC-STID-ENROLL-READER-UHF-SWEDGE-W45
 AC-STID-ENROLL-READER-UHF-SWEDGE-W55
 AC-STID-ENROLL-READER-USB-ARCS-R35-H/BT1-5AB/1A
 AC-STID-ENROLL-READER-USB-ARCS-R35-H/BT1-5AQ/1A
 AC-STID-KIT-SECARD-BT-BIO
 AC-STID-LF-MT-MODULE-SE8M10
 AC-STID-QR-BARCODE-MODULE-SE910
 AC-STID-READER-ARC1S-R31-B/BT1-3I/1A
 AC-STID-READER-ARC1S-W33-B/BT1-7OS/1A
 AC-STID-READER-ARCS-R31-A/BT1-3I/1A
 AC-STID-READER-ARCS-R31-B/BT1-3I/1A
 AC-STID-READER-ARCS-R31-C/BT1-3I/1
 AC-STID-READER-ARCS-RX1-IM/BT2-3I/1A
 AC-STID-READER-ARCS-RX1-JM/BT2-3I/1A
 AC-STID-READER-ARCS-S31-E/BT1-3I/1A
 AC-STID-READER-ARCS-W33-A/BT1-7OS/1A
 AC-STID-READER-ARCS-W33-AQ/BT1-7OS/1A
 AC-STID-READER-ARCS-W33-B/BT1-7OS/1A
 AC-STID-READER-ARCS-W33-BQ/BT1-7OS/1A
 AC-STID-READER-ARCS-W33-C/BT1-7OS/1A
 AC-STID-READER-SE7-ARC-DE-02
 AC-STID-READER-SNA-W53-A/BT4-7OS/1
 AC-STID-SE610
 AC-STID-SPACER-PLA-ADAP-V2-ARC-NO
 AC-STID-SPACER-PLAQ-ARC1-NO-V2
 AC-STID-SPECTRE-CABLE-3M
 AC-VT-READ-BIO-RFID-AC2000IC
 AC-VT-READ-BIO-RFID-AC2000IC-EU
 AC-VT-READ-BIO-RFID-AC2000IC-NA
 AC-VT-READ-BIO-RFID-AC2000IC-UK
 AC-VT-READ-BIO-RFID-AC2000PROX
 AC-VT-READ-BIO-RFID-AC2000PROX-EU
 AC-VT-READ-BIO-RFID-AC2000PROX-NA

AC-VT-READ-BIO-RFID-AC2000PROX-UK
AC-VT-READ-BIO-RFID-AC2000SC
AC-VT-READ-BIO-RFID-AC2000SC-EU
AC-VT-READ-BIO-RFID-AC2000SC-NA
AC-VT-READ-BIO-RFID-AC2000SC-UK
AC-VT-READ-BIO-RFID-AC5000IC
AC-VT-READ-BIO-RFID-AC5000IC-EU
AC-VT-READ-BIO-RFID-AC5000IC-NA
AC-VT-READ-BIO-RFID-AC5000IC-UK
AC-VT-READ-BIO-RFID-AC5000PROX
AC-VT-READ-BIO-RFID-AC5000PROX-EU
AC-VT-READ-BIO-RFID-AC5000PROX-NA
AC-VT-READ-BIO-RFID-AC5000PROX-UK
AC-VT-READ-BIO-RFID-AC5000SC-BLK
AC-VT-READ-BIO-RFID-AC5000SC-BLK-EU
AC-VT-READ-BIO-RFID-AC5000SC-BLK-NA
AC-VT-READ-BIO-RFID-AC5000SC-BLK-UK
AC-VT-READ-BIO-USB-FOH02
AC-VT-READ-BIO-USB-FOH02-SC
AC-AA-SAR-10-3186-32D
AC-SCH-AD-23760275
AC-AA-APA-10-PC
AC-AA-HUB-EXT-10-ANT
AC-MER-APD-10-USB
AC-ALL-SCH-AD400-ANT400-REM-CEILING
AC-ALL-SCH-AD400-ANT400-REM-HALL
AC-ALL-SCH-AD400-ANT400-REM-I/O+6DB
AC-ALL-SCH-AD400-MGB+MCA5
AC-ALL-SCH-COM400L
AC-ALL-SCH-COM400P-626
AC-ALL-SCH-COM400P-643E
AC-ALL-SCH-ENGAGE-GWE
AC-ALL-SCH-PIB300-2D
AC-ALL-SCH-PIM400-1501-LC
AC-ALL-SCH-PIM400-485-RSI
AC-ALL-SCH-PIM400-TD2
AC-ALL-SCH-RLBD
AC-ALL-SCH-WPR400-MTK
AC-SCH-BATTERY-8B-626
AC-SCH-COM300L-643E
AC-SCH-COM400L-626
AC-SCH-READ-MODULE-SI-626
AC-SCH-READ-MODULE-SIK-626
AC-SCH-TK400
AC-SCH-47282796-SUS-A-KIT
AC-SCH-COM300L-626
AC-SCH-RETROFIT-KIT-47278749

Name
AC-AA-88-5010-000
Aperio RS485 Hub Gen 5 - NA Version
AC-AA-SAR-79-5000-32D
LifeSafety Power Custom
SALTO NEO Cam - RIM - Mortise - Server Rack Cylinder
SALTO SP Custom Line Item
SALTO XS4 ANSI MINI Lock
ALLEGION AD-400-993M-70-MT-RHO626JRHR4B134
AC-SCH-AD-400-CY-40-MT-RHO-626-B-LH4B1324710025134
AC-SCH-AD-400-CY-40-MT-RHO-626-B-RH4B1324710025134
AC-SCH-AD-400-CY-40-MT-RHO-626-BRHR4B1324710025134
AC-SCH-AD-400-CY-40-SI-RHO-626-B-LH4B1324710025134
AC-SCH-AD-400-CY-40-SI-RHO-626-B-RH4B1324710025134
WL AD400-CY-70MTRHO612BRH4B1324710025134
ALLEGION AD-400-CY-70-MTRHO626JLHR4B1324710025134
ALLEGION AD-400-CY-70-MTRHO626JRHR4B1324710025134
ALLEGION AD-400-MS-70-MT-RHO626JLH4B0966310072134
AC-SCH-AD-400-MS-70-MT-RHO626BLH4B0966310072134
AC-SCH-AD-400-MS-70-MT-RHO626BRH4B0966310072134
AC-SCH-AD-400-MS-70-MTRHO626BLHR4B0966310072134
AC-SCH-AD-400-MS-70-MTRHO626BRHR4B0966310072134
AC-SCH-AD400-CY70MTRHO626BRH4B1324710025134
AC-SCH-AD400CY70MTRHO626BDLHR4B1324710025134
Allegion Schlage Wireless Lock AD400MS70SiRHO626BLHR4B0966310072134
AC-SCH-CONTROL-FE410F-CUSTOM
Allegion Schlage Wireless Lock NDEBSIID-RHO-626-13-247-47267101
HID SIGNO PIV RDR 20HNKS-03-0004XR
HID SIGNO PIV RDR 20HTKS-03-0004XR
HID SIGNO PIV RDR 20KHTKS-03-0004XR
HID SIGNO PIV RDR 40HNKS-03-0004XR
HID SIGNO PIV RDR 40HNKS-03-00059X
HID SIGNO PIV RDR 40HTKS-03-0004XR
HID SIGNO PIV RDR 40HTKS-03-00059X
HID SIGNO PIV RDR 40KHNS-03-0004XR
HID SIGNO PIV RDR 40KHNS-03-00059X
HID SIGNO PIV RDR 40KHTKS-03-0004XR
HID SIGNO PIV RDR 40KHTKS-03-00059X
HID 91000-MS
HID 91000BBNNN
HID 920NHRNEK0001T
HID 920PHRNEK00004
HID 920PHRNEK00005
HID 921NHPNEK000UG
HID 921NHPNEK0019D
HID 921NHPNEK0032R
HID 921NHPTEK000UG

HID 921NHPTEK0033E
HID 921NHRNEK0004M
HID 921NHRNEK0013W
HID 921PHPNEK000R2
HID 921PHPNEK000UE
HID 921PHPNEK0032N
HID 921PHPNEK0033G
HID 921PHPNEK0033H
HID 921PHPTEK0033J
HID 921PHRNEK0002D
HID 921PHRNEK0002G
HID 921PHRNEK0005P
HID 921PHRNEK0006F
HID 921PHRNEK0032W
HID 921PHRTEK0002D
HID 921PHRTEK0002G
HID 921PHRTEK0032W
HID 923NPPNEK0000L
HID 923PPPNEK0033T
HID 923PPPTEK000P4
HID 924NPRNEK00504
HID 924NPRTEK00504
HID 928NFNTEK000TE
HID E91000-MS
HID E920PHPTEK000P2
HID EA-LICENSE2
HID PVC-CM
HID PVC-CM-MS
HID PVC-D/S
HID PVC-D/S-MS
HID PVC-FXRDR-MS
HID PVCP-D/S-18-00
HID PVCP-D/S-MS
SALTO SP220418.38-IM
SALTO SP220495-14-IM
SALTO SP220495-18-IM
SALTO AEB0IMBA3A8
SALTO AEB0IPBA3A8
SALTO AEB1IMBA3A8
SALTO AEB1IPBA3A8
SALTO AFB7PMB4A8
SALTO HANDLE R1SJRIM080
SALTO R3SJRIM081
SALTO R3SWRPM081
SALTO LA1T1770A24IMSRH
SALTO LOCKS LA1T1770F24IMSRH
SALTO LA1T1770A24PMSLH

SALTO LA1T1770F74PMSRH
SALTO AEB0PMBA3A8
SALTO LOCKS AFB2IMB4A8M
SALTO AFB2PMB3A8
SALTO SP226009
SALTO GATEWAYB3CUS
SALTO GATEWAYW3CUS
AC-SALTO-CLUTCH-MECHANISM-SP00946-W67AKO
SALTO CU42E0TUS
SALTO CU42E0GUS
SALTO CU42E0US
SALTO CU4200TUS
SALTO CU4200GUS
SALTO CU4200US
SALTO COPLE95IMCA
SALTO COPLE110IMCA
SALTO WBM01KNL-5
SALTO WBM01KNM-5
SALTO WBM01KNS-5
SALTO CREDENTIAL PCM04KB-50
SALTO PCH002C
SALTO PCM01KC
SALTO PCH004-50
SALTO PCD04KB-50
SALTO PCM01KB-50
SALTO PCM04KBH-50
SALTO PFD04KB-10
SALTO PFD04KN-10
SALTO PFM04KB-10
SALTO PFD04KBSVNKS-5
SALTO PFD04KGSVNKS-5
SALTO PFD04KRSVNKS-5
SALTO PFD04KSSVNKS-5
SALTO PFD04KWSVNKS-5
SALTO 1848
SALTO LC1KC60IM
SALTO LC1KC70IM
SALTO LD51C70CS
SALTO LD51C60CS
SALTO NBB3141N00CSBN
SALTO RFDTCTS18W01
SALTO Accessories RFDTCTW18W01
SALTO SPACE-OPT-0035
SALTO EPS100
SALTO EC904B0US
SALTO ECB04B0US
SALTO ECJ04B0US

SALTO CU4EB8US
SALTO SP220764
SALTO SP225542
SALTO LB050A30
SALTO LB050M30
SALTO LJ050A30
SALTO LJ050M30
SALTO ACCESSORIES THUMBTURN SPO1047-325
SALTO SPACE-OPT-0016-1
SALTO WRMB004B
SALTO LA1T0570A21IM8LH
SALTO LA1T0570A21IM8RH
SALTO LOCKS LA1T0570A71IM8RH
SALTO LA1T0770A22IMSLH
SALTO LA1T0770A22IMSLR
SALTO LA1T0770A22IMSRH
SALTO LA1T0770A22IMSRR
SALTO LA1T0770A24IMSLH
SALTO LA1T0770A24IMSLR
SALTO LA1T0770A24IMSRH
SALTO LA1T0770A24IMSRR
SALTO LA1T1570A21IM8LH
SALTO LA1T1570A21IM8RH
SALTO LA1T1570A21PM8LH
SALTO LA1T1570A21PM8RH
SALTO LA1T1570A71IM8R
SALTO LA1T3570A21IM8LH
SALTO LA1T3570A21IM8RH
SALTO NJCL119M28BCBA
SALTO NJCL119M28BCBAR
SALTO NJCL119M28CPBA
SALTO NJCL119M28CPBAR
SALTO NJCL119M28CSBA
SALTO NJCL119M28CSBAR
AC-SALTO-NEO-CAM-LOCK-CYLINDER-NMCL119M40BCBA
SALTO NMB1100N00CSBN
AC-SALTO-NEO-CYLINDER-ANSI-NMB1100N00BCBN
AC-SALTO-NEO-CYLINDER-ANSI-NMB1100N00BCBNR
SALTO NMB3141N00CSBN
SALTO LOCKS NMB3151N00CSBN
AC-SALTO-NEO-MORTISE-ANSI-NMM1132N00BCBN
AC-SALTO-NEO-MORTISE-ANSI-NMM1132N00BCBNR
AC-SALTO-NEO-MORTISE-ANSI-NMM1135N00CSBN
AC-SALTO-NEO-MORTISE-ANSI-NMM1135N00CSBNR
SALTO NEO NBM1132N00NEBNR
SALTO NBM1135N00CSBNR
SALTO NJM1132N00BCBN

SALTO NJM1132N00BCBNR
SALTO NJM1132N00CPBN
SALTO NJM1132N00CPBNR
SALTO NJM1132N00CSBN
SALTO NJM1132N00CSBNR
SALTO LOCKS NMP4P60150CPB1
SALTO LOCKS NMP4R60150CPB0
SALTO NBB3151N00BCBN
SALTO NBB3151N00BCBNR
SALTO NJE9130N00NEBR
SALTO NJE9130N00NEBRR
SALTO NJB1100N00BCBN
SALTO NJB1100N00BCBNR
SALTO NJB1100N00CPBN
SALTO NJB1100N00CPBNR
SALTO NJB1100N00CSBN
SALTO NJB1100N00CSBNR
SALTO NJP4R60150CPB0
SALTO SP220475-6
SALTO PPD800
SALTO SPAONLMBMB
SALTO SPACE-OPT-0032
SALTO SPAONLINE
SALTO SPAPART
SALTO SPAONLABAB
SALTO GATEWAYB2CUS
SALTO GATEWAYW2CUS
SALTO PBF110033IM
SALTO LOCKS PBF110045IM
SALTO SAMKIT9
SALTO SAMKITH
SALTO SP226335
SALTO SPACE-OPT-0018
SALTO SP226850
SALTO SP226077-S-10
SALTO TR-SPACE-V1
SALTO SP226233.02-BM
SALTO Stickers PSD04K-20
SALTO PSM04K-20
SALTO ACCESSORIES PIN SP01027-IM
Salto UBOX42DBABTUS
Salto UBOX42DBMBTUS
SALTO WRDB0A4W
SALTO WRDJ0A4B
SALTO WRDJ0A4W
SALTO WRDB0M4W
SALTO WRDJ0M4B

SALTO WRDJ0M4W
SALTO WRDB0P40
SALTO RFNODE3
SALTO RFNODE
SALTO SPACE-OPT-0033
SALTO SPACE-OPT-0021
SALTO REPEATER03US
SALTO CJ250N60BCB3
SALTO CJ250N60CPB3
SALTO CJ250N60CSB3
SALTO LOCKS CM250G70CSB3
SALTO LOCKS CM250N60BCB3
SALTO CM250N60CSB3
SALTO LOCKS CM250N70CSB3
SALTO LOCKS CM260G70CSB3
SALTO LOCKS CM260G70CSB4
SALTO LOCKS CM260N70CSB3
SALTO SP01045-100
SALTO CREDENTIAL PWU008B
SALTO AB650G00IM38WK
SALTO EB756HDLIMB4MD5
SALTO LOCKS AM660W00IMB48G
SALTO AM656N00BCB38
SALTO AM656N00BCB48
SALTO AM658N61BCB38
SALTO AM658N62BCB38
SALTO SP01798-C8-4
SALTO AM660A00IMBH8E5
SALTO AM660W00PMBH8E5
SALTO AM650A00BCWH8
SALTO LOCKS AM650A00IMBH8
SALTO AM650G00IMBH8
SALTO AM650G00IMBP8
SALTO AM650G00IMBH8E5
SALTO AM650N00IMBH8E5
SALTO AM660B00IMBH8E5
SALTO AM660J00IMBH8
SALTO LOCKS AM650W00DBBH8E5
SALTO LOCKS AM650W00IMBH8E5
SALTO LOCKS AM660W00IMBH8E5
SALTO LOCKS AM660N00IMBH8
SALTO AM660N00IMBH8E5
SALTO LOCKS AM660N00IMBP8
SALTO AM650N00BCBH8
SALTO AM650N00BCBP8
SALTO KPP17IM
SALTO KPP55IM

SALTO KPP19IM
SALTO KPP08IM
SALTO ACCESSORIES KPP39IM
SALTO KPB03IM-U
SALTO KPP03IM
SALTO KPP04IM
SALTO KPP37IM
SALTO LOCKS AM650A00BCB38E5G
SALTO LOCKS AM650A00IMB38E5G
SALTO LOCKS AM650A00IMB48E5G
SALTO LOCKS AM650N00IMBH8
SALTO LOCKS AM658A62IMB38E5G
SALTO LOCKS AM658A62IMB48E5G
SALTO LOCKS AM660U00IMB38E5G
SALTO LOCKS AM666A00IMB48E5G
SALTO LOCKS AM668U62IMB48E5G
SALTO AM660N00IMB48E5G
SALTO AM650A00IMB38
SALTO LOCKS AM650A00IMB48
SALTO AM650A00IMB48G
SALTO LOCKS AM650A00IMBH8E5
SALTO AM650G00IMB38E5
AC-SALTO-XS4-OP-WB-ESCUICHEON-ANSI-AM650G00IMB48
SALTO AM650N00IMB38
SALTO AM650N00IMB38E5
SALTO AM650W00IMB38
SALTO LOCKS AM650W00IMBH8
SALTO AM650W00NEB38
SALTO AM650W00NEBH8
SALTO AM656A00IMB38
SALTO AM656A00IMB48
SALTO AM656A00IMB48G
SALTO LOCKS AM656G00IMB38
SALTO AM656N00IMB38
SALTO AM656N00IMB38G
SALTO AM656W00IMB38
SALTO AM658N62DBB38
SALTO AM658N62IMB38
SALTO LOCKS AM658N62IMB48
SALTO AM660A00IMB38E5
SALTO AM660A00IMB3SG
SALTO AM660G00IMB38
SALTO LOCKS AM660G00IMB48
SALTO AM660J00IMB38
SALTO LOCKS AM666A00IMB48G
SALTO AM666G00IMB38
SALTO AM666N00BCB38

SALTO Locks AM666N00IMB38
SALTO Locks AM666N00IMB38G
SALTO Locks AM666N00IMB48
SALTO AM658N62IMB38E5G
SALTO LOCKS AM660A00IMB48E5G
SALTO LOCKS AM668U61IMW38E5G
SALTO AM660N00IMB38E5
SALTO AM650N00IMB38E5G
SALTO KPB17IM
SALTO KPB08IM
SALTO KPB08IMW
SALTO KPB03IM
SALTO KPB04IM
SALTO KPB03IMW
SALTO READER WRLUD24BUS
SALTO CABLE WRLUD-C10
SALTO MODULE WRLUD-SIC1
HID EL-96000-SVM10
HID EL-96300-ADM10
HID EL-97000-EKIOSK
HID EL-98000-EADV10
HID EL-ACI-AVIGILON
HID EL-ACI-UPGRD
HID EL-AST-ID150
HID EL-AST-ID150A
HID EL-AST-UPDATEA
AC-HID-EL-DESKO-ICON
HID EL-DYMO-30856
HID EL-DYMO-30911
HID EL-DYMO-450T
HID EL-DYMO-550
HID EL-EADV-UPGRD
HID EL-K12-SVM
HID EL-SOS-K12
AC-HID-EL-SS-R2
HID EL-SSA-ACIS
HID EL-SSA-EADVS
HID EL-SSA-K12S
HID EL-SSA-SVMS
HID EL-SVM10-UPGRD
HID EL-TOP-1X5
Access Control Manager 6 30 Day Demo License
Access Control Manager 6 Sixteen Doors Expansion Software Licenses
Access Control Manager 6 Auto Failover License (per appliance)
Access Control Manager 6 Badging Software Licenses
Access Control Manager 6 Partitioning License for additional partitions
Access Control Manager 6 Replication License (per appliance)

Access Control Manager 6 REST Connectivity Software License
Access Control Manager 6 Wireless Lock Connectivity Software License
UA7 1000 Door License
UA7 100 Door License
UA7 10 Door License
UA7 1 Door License
UA7 All-in Add-on
UA7 Availability and Network Add-on
UA7 Situational Awareness Add-on
UA7 Base Package License (includes 20 doors)
UA7 Data and Templates Add-on
UA7 Integrations Add-on
UA7 Service Plan for up to 1000 doors; 1 Year
UA7 Service Plan for up to 1000 doors; 3 Years
UA7 Service Plan for up to 1000 doors; 5 Years
UA7 Service Plan for up to 2000 doors; 1 Year
UA7 Service Plan for up to 2000 doors; 3 Years
UA7 Service Plan for up to 2000 doors; 5 Years
UA7 Service Plan for up to 250 doors; 1 Year
UA7 Service Plan for up to 250 doors; 3 Years
UA7 Service Plan for up to 250 doors; 5 Years
UA7 Service Plan for up to 4000 doors; 1 Year
UA7 Service Plan for up to 4000 doors; 3 Years
UA7 Service Plan for up to 4000 doors; 5 Years
ACM6 to UA7 Upgrade Package for up to 1000 doors (include 1 Year Service Plan)
ACM6 to UA7 Upgrade Package for up to 2000 doors (include 1 Year Service Plan)
ACM6 to UA7 Upgrade Package for up to 250 doors (include 1 Year Service Plan)
UA7 Wireless Lock License
Access Control Manager 6 LDAP Directory Connectivity Software License
Access Control Manager 6 Oracle Server Connectivity Software License
Access Control Manager 6 Microsoft SQL Server Connectivity Software License
Access Control Manager 6 XML Events Connectivity Software License
Access Control Manager 6 License for the migration of ACM Embedded Controller.
Access Control Manager 6 Bosch Integration Software Licenses
Access Control Manager 6 Bosch Integration Software Licenses
Access Control Manager 6 DMP Integration Software Licenses (ten panel)
Access Control Manager 6 DMP Integration Software Licenses (one panel)
Access Control Manager 6 NON OEM HID VertX EVO Assimilation License
Access Control Manager 6 ViRDI Integration Software Licenses
Access Control Manager 6 License for Video Integration for Exacq
Access Control Manager 6 License for Video Integration for Milestone
Access Control Manager 6 (ACM) Verify license for 16 virtual stations
Access Control Manager 6 (ACM) Verify license for 5 virtual stations
Access Control Manager Enterprise Plus 6 – Ent Plus Appliance for 1024 Readers
Access Control Manager Enterprise Plus 6 – Ent Plus Appliance for 16 Readers
Access Control Manager Enterprise Plus 6 – Ent Plus Appliance for 2048 Readers
Access Control Manager Enterprise Plus 6 – Ent Plus Appliance for 512 Readers

1 Year Extended Warranty for Access Control Manager Enterprise Plus Appliance
2 Year Extended Warranty for Access Control Manager Enterprise Plus Appliance
UA7 Enterprise Plus Appliance
1 Year Extended Warranty for UA Enterprise Plus Appliance
2 Year Extended Warranty for UA Enterprise Plus Appliance
1 Year Extended Warranty for Access Control Manager Enterprise Appliance
2 Year Extended Warranty for Access Control Manager Enterprise Appliance
UA7 Enterprise Appliance
1 Year Extended Warranty for UA Enterprise Appliance
2 Year Extended Warranty for UA Enterprise Appliance
1 Year Extended Warranty for Access Control Manager Professional Appliance
2 Year Extended Warranty for Access Control Manager Professional Appliance
UA7 Professional Appliance
1 Year Extended Warranty for UA Professional Appliance
2 Year Extended Warranty for UA Professional Appliance
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 1024 Readers
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 128 Readers
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 16 Readers
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 2048 Readers
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 256 Readers
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 32 Readers
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 512 Readers
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 64 Readers
UA7 Virtual Hyper-V Appliance License
UA7 Virtual VMware Appliance License
AXIAL LEADED 1K1%1/4W RESISTORS; 32-pack (Mercury Part #: RES-1K32)
CABLE FOR MR-50 TAMPER (Mercury Part #: A-TC-MR50)
Replace 3-Position Terminal Blocks; 10-pack(Mercury Part Number: A-TERM5-3)
Replace 4-Position Terminal Blocks; 10-pack (Mercury Part #: A-TERM5-4)
Replace 5-Position Terminal Blocks; 10-pack (Mercury Part #: A-TERM5-5)
Replace 6-Position Terminal Blocks; 10-pack(Mercury Part #: A-TERM5-6)
16 Zone Input Monitor Module with 2 relays (Mercury Part #: MR16in-S3)
16 Relay Output Control Module (Mercury Part #: MR16out-S3)
Series 3 Single Reader Interface Module (Mercury Part #: MR50-S3)
Series 3B Two-Reader Interface Module (Mercury Part #: MR52-S3B)
Intelligent Controller (Mercury Part #: LP4502)
CONTROLLER MERCURY MP1501
CONTROLLER MERCURY MP1502
CONTROLLER MERCURY MP2500
CONTROLLER MERCURY MP4502
Mercury M5 Bridge 16 DO
Mercury M5 Bridge 20 IN
Mercury M5 M2000 with with M5 IC
Mercury M5 M2000 only
Mercury M5 Bridge 2SRP
Mercury M5 Bridge 8RP
Mercury M5 Bridge IC

RS-232/485 to 8 RS-485 Channel Mux (Mercury Part #: MUX8)
Reader Interface Module (Mercury Part #: MR62e)
STid Card CCTW490
Allegion 9651
Allegion 9651T
Allegion 9520
Allegion 9551
Allegion 7610
Schlage 8543
Schlage 8543M1
Schlage 8943
Schlage 8643T
Schlage 8843T
Farpointe Data CSM-2P
Farpointe Data CSC-2
Farpointe Data CSM-2S
Farpointe Data DC1-1
Farpointe Data DC4-1
Farpointe Data DE2
Farpointe Data DM1-3
Farpointe Data DM1-3S
Farpointe Data DM4-3
Farpointe Data DM4-3S
Farpointe Data PSC-1-H
Farpointe Data PSI-4-H
Farpointe Data PSM-2P-H
Farpointe Data PSM-2S-H
Farpointe Data CMC-2-25
Farpointe Data CSK-2
Farpointe Data DK1-3
Farpointe Data DK4-3
Farpointe Data PDT-1-H
Farpointe Data PSK-3-H
Farpointe Data WRT-2+D2
Farpointe Data WRT-2+S1
Farpointe Data WRT-2+S4
Farpointe Data WRT-2M
Farpointe Data WRT-4+S4
Farpointe Data WRT-4+SI
Farpointe Data WRT-2+H
Farpointe Data WRT-4+H
HID 2122BGGMNN
HID 3000PG1MN
HID 3150RGGMNM
HID SEC9X-CRD-0-005J
HID 1336LGGMN
HID 2000PGGMN

HID 2002PGGMN
HID 2004PGGMN
HID 2050PNNMN
HID 2080PMSMV
HID 2100PG1MN
HID 3000PGGMB
HID 3000PGGMV
HID 3050PGGMN
HID 3350PMSMV
HID 2120BG1MNN
HID 2120BGGMNM
HID 2120BGGMVM
HID 3150RGGMNN
HID 3000PGGMN
HID 3000PGGMN AVIGILON FORMAT & LOGO
HID 3000PGGMN AVIGILON FORMAT
HID 3002PGGMN
HID 3004PGGMN
HID 6014SGGANN
HID 5005PG1MN
HID 2080HPMSMV
HID 600TGGAN
HID 1386LGGMN
HID 801FPGGAN
HID ADMIN-SEC9X-CRD-MADD
HID SEC9X-CRD-E-MKYD
HID 1326LMSMV
HID 5005PGGMN
HID 5005PGGSN
HID 5006PG1MN
HID-CARD-SEOS-5006PGCMN Avigilon Logo
HID 5006PGGMN
HID-CARD-SEOS-5006PGGMN AVO Format No Logo
HID 5006PGGNN
HID 5006PGGSN
HID 5656PMSAV
HID 5105PGGMNN
HID 5105PGGNNN
HID 5105RG1MNM
HID 5105RG1MNN
HID 5105RG1NNM
HID 5105RGGMNM
HID 5105RGGMNN
HID 5105RGGNNS
HID 5105RGGSN
HID 5106PG1MNN
HID 5106PGGMNN

HID 5106PGGNNN
HID 5106RGGMNM
HID 5106RGGMNN
HID 5106RGGNNN
HID MC-0036
HID 3250PNNMN
HID 3250PNNMN AVIGILON FORMAT
HID 1346LNSMN
HID-FOB-SEOS-5266PNNA Avigilon Logo
HID MID-SUB-T100
HID MID-SUB-T100-ADD
AC-HID-MOB-MID-SUB-T100-ADD-1-MONTH
HID 3300PKSMN
HID 1391LGSMN
HID 1351LBSMN
HID 802FPGGAN
HID 2000HPGGAV
HID MC-1000
STid CCTW670
STid PCGW671
STid ETA-W75B-574BE10
Lifesafety Power Sixteen Door Mercury Single Voltage Integrated Power System
Lifesafety Power Sixteen Door Mercury Dual Voltage Integrated Power System
Lifesafety Power Two Door Mercury Single Voltage Integrated Power System
Lifesafety Power Two Door Mercury Dual Voltage Integrated Power System
Lifesafety Power Four Door Mercury Single Voltage Integrated Power System
Lifesafety Power Four Door Mercury Dual Voltage Integrated Power System
Lifesafety Power Eight Door Mercury Single Voltage Integrated Power System
Lifesafety Power Eight Door Mercury Dual Voltage Integrated Power System
LifeSafety Power B100
LifeSafety Power C4
LifeSafety Power C8
LifeSafety Power Camlock_Set
LifeSafety Power D8P
LifeSafety Power E1M
LifeSafety Power E2-BOXED
LifeSafety Power E2-BS1
LifeSafety Power E2M
LifeSafety Power E4-3BS1
LifeSafety Power E4M
LifeSafety Power E4M1
LifeSafety Power E4V
LifeSafety Power E4V1
FLEXPOWER E6M MCLASS™ Power Enclosure
FLEXPOWER E6M1 MCLASS™ Power Enclosure
LifeSafety Power FLEXPOWER E8M MCLASS™ Power Enclosure
LifeSafety Power FLEXPOWER E8M2 16 Door Mercury Security

LifeSafety Power EPLT-1M
 LifeSafety Power F8
 LifeSafety Power F8P
 LifeSafety Power FPO150-2D8E4M1
 LifeSafety Power FPO150-B100C8D8E2
 LifeSafety Power FPO150-C8D8E2
 LifeSafety Power FPO150-B1002D8PM8NL4E4M/T8-C
 LifeSafetyPower FPO150B100C82D8PE4M-T8-A
 LifeSafety Power FPO150-B100C8D8E4-4SL1
 LifeSafetyPower FPO150-B100C8D8NL4E4M
 LifeSafety Power AC-LSP-FPO150-B100C8P2D8PE4M-T8-A
 LifeSafety Power FPO150-B100D8M8NL4E4-4SL1
 LifeSafety Power FPO150-B100D8PM8NL4E4M
 LifeSafety Power FPO150-B100D8PM8NL4E6M
 LifeSafety Power FPO150
 LifeSafety Power FPO150/150-2C82D8E4
 LifeSafety Power Mercury Unified Unified Power Systems
 LifeSafety Power FPO150-250-2D8P2M8NL4E4M1
 LifeSafety Power FPO150-250-2D8P2M8NL4E6M1
 LifeSafety Power FPO150-250-2D8P2M8NL4E8M2
 LifeSafety Power FPO150/250-3D8P2M8NL4E4M1/T16-A
 LifeSafety Power FPO150/250-3D8P2M8NL4E4M1/T16-C
 LifeSafety Power FPO150/250-3D8P2M8NL4E8M2/P16-B
 LifeSafetyPower FPO50-2D8PM8NL4E4M1/P8-A
 LifeSafety Power FPO250
 LifeSafety Power FPO250-2C82D8E4
 LifeSafety Power FPO250-2M8PNL4E4M
 LifeSafetyPower FPO250-B100D8PM8NL4E6M
 LifeSafety Power MCLASS™ UNIFIED POWER SYSTEM
 LifeSafety Power FPO250/250-2C82D8E4
 LifeSafety Power FPO250/250-3C85D8PE12M/T24-A
 LifeSafety Power MCLASS™ WIRED UNIFIED POWER SYSTEM
 LIFESAFETY POWER FPO250/250-5M8NLXE8M2/P16-A
 LifeSafety Power FPO250/250-NLXE4M
 LifeSafety Power 500W Dual Voltage Mercury Unified Power System
 LifeSafety Power FPO75
 LifeSafety Power FPO75-2D8E2-5SL1
 LifeSafety Power FPO75-2E2BP2
 LifeSafety Power FPO75-C4E1
 LIFESAFETY POWER FPO75-B100C4D8NL4E2M
 LifeSafety Power B100C4E1-2SL1
 LifeSafety Power FPO75-B100C8D8E2-3SL1
 LifeSafety Power FPO75-B100M8NL4E2M
 AC-LSP-FPO75-B100M8PNL4E2M-WP-FCS04
 LifeSafety Power FPO75-D8E1-2SL1
 LifeSafety Power FPO75-D8E2-4SL1
 LifeSafety Power FPO75-E1BP1

LifeSafety Power FPO75-E2BP2
LifeSafety Power Mercury Unified Unified Power Systems
LifeSafety Power FPO75/75-C8D8E2
LifeSafety Power M8
LifeSafety Power MSM25
LifeSafety Power NL4
LifeSafety Power NETLINK® NLX
LifeSafety Power 16 Door Mercury Over Sized Enclosure
LifeSafety Power 16 Door 12 or 24 VDC Mercury Over Sized Enclosure
LifeSafety Power 16 Door Mercury Over Sized Enclosure
LifeSafety Power 16 Door Dual Voltage Mercury Over Sized Enclosure
LifeSafety Power E5M
LifeSafety Power RGM75-D8PNZ
LifeSafety Power RGM75-D8PZ
LifeSafety Power RGM75-M8PNZ
LifeSafety Power RGM75B-C4PNZ
LifeSafety Power RGM75B-C4PZ
LifeSafety Power RGM75B-M8PNZ
LifeSafety Power RGM75B-M8PNZ1
Lifesafety Power RBE rackmount battery enclosure
LifeSafety Power SDU
LifeSafety Power FPO150-B100C8D8E2M
LifeSafety Power FPO75-B100C4D8NL2E2M
LifeSafety Power Eight Door Mercury Panduit ProWire Unified Power wall mount
LifeSafety Power Eight Door Mercury Panduit ProWire Unified Power wall mount
LifeSafety Power Sixteen Door Mercury Panduit ProWire Unified Power wall mount
LifeSafety Power Sixteen Door Mercury Panduit ProWire Unified Power wall mount
LifeSafety Power Sixteen Door Mercury Panduit ProWire Unified Power wall mount
LifeSafety Power Sixteen Door Mercury Panduit ProWire Unified Power wall mount
Small enclosure for 1 x Mercury LP1501 or 1 x Mercury MR62e
ACM Professional Services - HW1024 Migration - Contact ACM SE prior to Purchase
ACM Professional Services - HW2048 Migration - Contact ACM SE prior to Purchase
ACM Professional Services - HW256 Migration - Contact ACM SE prior to Purchase
ACM Professional Services - HW512 Migration - Contact ACM SE prior to Purchase
ACM Professional Services - LDAP Migration - Contact ACM SE prior to Purchase
ACM Professional Services - ORCL Migration - Contact ACM SE prior to Purchase
ACM Professional Services - SQL Migration - Contact ACM SE prior to Purchase
ACM Professional Services - LDAPF Migration - Contact ACM SE prior to Purchase
ACM Professional Services - ORCLF Migration - Contact ACM SE prior to Purchase
ACM Professional Services - SQLF Migration - Contact ACM SE prior to Purchase
ACM Professional Services - AZURE AD SYNC - Contact ACM SE prior to Purchase
ACM Professional Services - GENERIC SYNC - Contact ACM SE prior to Purchase
ACM Professional Services Hourly- CUSTOM SYNC - Contact ACM SE prior to Purchase
ACM Professional Services - LDAP SYNC - Contact ACM SE prior to Purchase
ACM Professional Services - ORACL SYNC - Contact ACM SE prior to Purchase
ACM Professional Services - SQL SYNC - Contact ACM SE prior to Purchase
STid Reader ANT-SPECTRE-B

STid Reader ETA-W75B-574BE10P
STid Reader SLA-R51-A/U04-3I/1
STid READER SLA-W53-A/U04-7OS/1
STid READER KFX-UHF-08
STid READER KFX-UHF-09
STid READER KFX-UHF-10
Allegion MTK15-485
Allegion MT11-485
Allegion MT15-485
Allegion WPR400-MT
Allegion WRI400
Allegion SM10
Allegion MT11
Allegion MTB11
Allegion MTB15
Allegion MTKB15
Farpointe Data CSR-35L-OSDP
Farpointe Data CSR-35L-WG
Farpointe Data DELTA6.2 OSDP MULLION-MOUNT CONTACTLESS SMARTCARD READER w/KEY
Farpointe Data DELTA 6.2
Farpointe Data DELTA3-SECTOR
Farpointe Data DELTA5-OSDP
Farpointe Data DELTA5-SECTOR
Farpointe Data DELTA5.3-SECTOR
Farpointe Data DELTA6.4-SECTOR
Farpointe Data P-453-HA
Farpointe Data P-455-HA
Farpointe Data P-403-HA
Farpointe Data P-405-HA
Farpointe Data P-410-HA
Farpointe Data P-300-H
Farpointe Data P-300-H-A
Farpointe Data P-500-H
Farpointe Data P-500-H-A
Farpointe Data P-640-H
Farpointe Data P-640-H-A
Farpointe Data P-640-H-OSDP
Farpointe Data P-710-H
Farpointe Data P-710-H-A
Farpointe Data P-900-H
Farpointe Data P-900-H-A
Farpointe Data P-530-HA
Farpointe Data P-620-HA
Farpointe Data MCR-50-H
Farpointe Data EM-64-H OSDP
Farpointe Data P-300-H OSDP
Farpointe Data P-500-H-OSDP

Farpointe Data PCR-620L-OSDP
Farpointe Data PCR-620L-WG
Farpointe Data PCR-640L-OSDP
Farpointe Data PCR-640L-WG
Farpointe Data EM-64-H WIEGAND
Farpointe Data WRR-22
Farpointe Data WRR-44
HID IP65GSKT-R10
HID IP65GSKT-R15
HID IP65GSKT-R40
HID IP65GSKT-RK40
HID 920NTPNEK000FA
HID 900PTPTEK00387
HID 910PTPNEK00387
HID 910PTPTEK00387
HID 921PTPNEK00385
HID 40HNKS-03-0005LE
HID 40KHNS-03-0005LE
HID 900NMPNEKEA005
HID 900NMPNEKMA005
HID 900NMPTEKEA005
HID 900NMPTEKMA005
HID 910NMPNEKEA005
HID 910NMPNEKMA005
HID 910NMPTEKEA005
HID 910NMPTEKMA005
HID 920NMPNEKEA005
HID 920NMPNEKMA005
HID 920NMPTEKMA005
HID 900NBNNEKE0000
HID 900NBNTEK20000
HID 900NBNTEKE0000
HID 900NMNNEKEA001
HID 900NMNTEKEA001
HID 910NMNNEKEA001
HID 910NMNTEKEA001
HID 920NBNNEK20000
HID 920NBNNEKE0000
HID 920NBNNEKES077
HID 920NBNTEK20000
HID 920NBNTEKE0000
HID 920NMNNEKEA001
HID 920NMNTEKEA001
HID 921NBNNEKE0000
HID 900NTNNEK00000
HID 900NTNNEK00000 Avigilon Logo
HID 920NTNNEK00000

HID 920NSNNEK20000
HID 940NNNTEK2037P
HID 940NTNTEK00000
HID 921NTNNEK00000
HID 921NSNNEK20000
HID 920PTNNEK00000
HID 920PTNNEK00000 Avigilon Logo
HID Part 921PTNNEK00000
HID MaxiProx Long Range Proximity Reader (HID # 5375AGN00)
HID 900LTNNEK00017
HID 910LTNNEK00017
HID 920LTNNEK00017
HID 900PMPNEKEA007
HID 900PMPNEKMA007
HID 900PMPTEKEA007
HID 900PMPTEKMA007
HID 910PMPNEKEA007
HID 910PMPNEKMA007
HID 910PMPTEKEA007
HID 920PMPNEKEA007
HID 920PMPNEKMA007
HID 920PMPTEKEA007
HID 920PMPTEKMA007
HID 900PBNNEK20000
HID 900PBNTEK20000
HID 900PMNNEKEA003
HID 900PMNNEKMA003
HID 900PMNTEKEA003
HID 900PMNTEKMA003
HID 910PBNNEK20000
HID 910PMNNEKEA003
HID 910PMNNEKMA003
HID 910PMNTEKEA003
HID 910PMNTEKMA003
HID 920PBNNEK20000
HID 920PBNTEK20000
HID 920PMNNEKMA003
HID 920PMNTEKEA003
HID 920PMNTEKMA003
HID 910PTNTEK00000
HID 920PTNTEK00000
HID 921PTNTEK00000
HID 900PTNNEKE0000
HID 910PTNNEKE0000
HID 920PTNNEKE0000
HID 921PTNNEKE0000
HID MiniProx Proximity Reader (HID # 5365EKP00)

HID R54270001
HID ProxPro Proximity Reader (HID # 5355AGN00)
HID ProxPro Proximity Reader with Keypad (HID # 5355AGK00)
HID ProxPro II Proximity Reader (HID # 5455BKN00)
HID ThinLine II Switch Plate Proximity Reader (HID # 5395CK100)
HID RDRSEU908K00000
HID RDRSEU909K00000
HID 20KNKS-00-000000
HID 20KNKS-00-000000 Avigilon Logo
HID 20KNKS-01-000000
HID 20KNKS-01-00001H
HID 20KNKS-02-000000
HID 20KNKS-02-000000 Avigilon Logo
HID 20KNKS-02-0002BL
HID 20KNKS-T0-000000
HID 20KNKS-T1-000000
HID 20KNKS-T2-000000
HID 20KNKS-T3-00FD21
HID 20KTKS-00-000000
HID 20KTKS-00-000000 Avigilon Logo
HID 20KTKS-01-000000
HID 20KTKS-01-000000 Avigilon Logo
HID 20KTKS-01-00001H
HID 20KTKS-02-000000
HID 20KTKS-02-000000 Avigilon Logo
HID 20KTKS-02-0002BL
HID 20KTKS-T0-000000
HID 20KTKS-T1-000000
HID 20KTKS-T2-000000
HID 20NKS-00-000000
HID 20NKS-00-000000 Avigilon Logo
HID 20NKS-01-000000
HID 20NKS-01-00001H
HID 20NKS-02-000000
HID 20NKS-02-000000 Avigilon Logo
HID 20NKS-02-0002BL
HID 20NKS-T0-000000
HID 20NKS-T1-000000
HID 20NKS-T2-000000
HID 20NKS-T3-00FD21
HID 20TKS-00-000000
HID 20TKS-00-000000 Avigilon Logo
HID 20TKS-01-000000
HID 20TKS-01-000000 Avigilon Logo
HID 20TKS-01-00001H
HID 20TKS-01-00001H AVIGILON LOGO
HID 20TKS-02-000000

HID 20TKS-02-000000 Avigilon Logo
HID 20TKS-02-0002BL
HID 20TKS-T0-000000
HID 20TKS-T1-000000
HID 20TKS-T2-000000
HID 20TKS-T3-00FD21
HID 40KNKS-00-000000
HID 40KNKS-00-000000 Avigilon Logo
HID 40KNKS-01-000000
HID 40KNKS-01-00001H
HID 40KNKS-02-000000
HID 40KNKS-02-000000 Avigilon Logo
HID 40KNKS-02-0002BL
HID 40KNKS-T0-000000
HID 40KNKS-T1-000000
HID 40KNKS-T2-000000
HID 40KTKS-00-000000
HID 40KTKS-00-000000 Avigilon Logo
HID 40KTKS-01-000000
HID 40KTKS-01-000000 Avigilon Logo
HID 40KTKS-01-00001H
HID 40KTKS-02-000000
HID 40KTKS-02-000000 Avigilon Logo
HID 40KTKS-02-0002BL
HID 40KTKS-T0-000000
HID 40KTKS-T1-000000
HID 40KTKS-T2-000000
HID 40NKS-00-000000
HID 40NKS-00-000000 Avigilon Logo
HID 40NKS-01-000000
HID 40NKS-01-00001H
HID 40NKS-02-000000
HID 40NKS-02-000000 Avigilon Logo
HID 40NKS-02-0002BL
HID 40NKS-T0-000000
HID 40NKS-T1-000000
HID 40NKS-T2-000000
HID 40NKS-T3-00FD21
HID 40TKS-00-000000
HID 40TKS-00-000000 Avigilon Logo
HID 40TKS-01-000000
HID 40TKS-01-000000 Avigilon Logo
HID 40TKS-01-00001H
HID 40TKS-01-00001H AVIGILON LOGO
HID 40TKS-02-000000
HID 40TKS-02-000000 Avigilon Logo
HID 40TKS-02-0002BL

HID 40TKS-T0-000000
HID 40TKS-T1-000000
HID 40TKS-T2-000000
HID 40TKS-T3-00FD21
HID 6132AKB-M
HID 6132AKC-M
HID 6132AKT-M
HID 6132AKU-M
HID 6132AKE-M
HID 20-K-05
HID 40-K-05
HID BLEOSDP-UPG-A-920
STid KIT-SECARD-BT
STid SE810
STid SWEDGE-W45
STid SWEDGE-W55
STid ARCS-R35-H/BT1-5AB/1A
STid ARCS-R35-H/BT1-5AQ/1A
AC-STID-KIT-SECARD-BT-BIO
STid SE8M10
STid SE910
STid ARC1S-R31-B/BT1-3i/1A
STid ARC1S-W33-B/BT1-7OS/1A
STid ARCS-R31-A/BT1-3I/1A
STid ARCS-R31-B/BT1-3I/1A
AC-STID-READER-ARCS-R31-C/BT1-3I/1
STid ARCS-RX1-IM/BT2-3I/1A
STid ARCS-RX1-JM/BT2-3I/1A
AC-STID-READER-ARCS-S31-E/BT1-3I/1A
STid ARCS-W33-A/BT1-7OS/1A
STid ARCS-W33-AQ/BT1-7OS/1A
STid ARCS-W33-B/BT1-7OS/1A
STid ARCS-W33-BQ/BT1-7OS/1A
STid ARCS-W33-C/BT1-7OS/1A
AC-STID-READER-SE7-ARC-DE-02
STid SNA-W53-A/BT4-7OS/1
AC-STID-SE610
STid PLA-ADAP-V2-ARC-NO
STid PLAQ-ARC1-NO-V2
AC-STID-SPECTRE-CABLE-3M
ViRDI AC2000HID iClass
ViRDI AC2000HID iClass
ViRDI AC2000HID iClass
ViRDI AC2000HID iClass
ViRDI AC2000Prox
ViRDI AC2000Prox
ViRDI AC2000Prox

ViRDI AC2000Prox
ViRDI AC2000SC
ViRDI AC2000SC
ViRDI AC2000SC
ViRDI AC2000SC
ViRDI AC5000plusHID iClass
ViRDI AC5000plusHID iClass
ViRDI AC5000plusHID iClass
ViRDI AC5000plusHID iClass
ViRDI AC5000PlusProx
ViRDI AC5000PlusProx
ViRDI AC5000PlusProx
ViRDI AC5000PlusProx
ViRDI AC5000Plus SA
ViRDI AC5000Plus SA
ViRDI AC5000Plus SA
ViRDI AC5000Plus SA
ViRDI FOH02
ViRDI FOH02-SC
ASSA ABLOY 10-3186-32D
Allegion 23760275
ASSA ABLOY Aperio Programming Kit APA-10-PC
ASSA ABLOY Aperio Hub Accessory; EXT-10-ANT Aperio External Antenna
ASSA ABLOY APD-10-USB
Allegion ANT400-REM-CEILING
Allegion ANT400-REM-HALL
Allegion ANT400-REM-I/O+6DB
Allegion MGB+MCA5
Allegion COM400L
Allegion COM400P-626
Allegion COM400P-643E
Allegion GWE-ENGAGE
Allegion PIB300-2D
Allegion PIM400-1501-LC
Allegion PIM400-485-RSI
Allegion PIM400-TD2
Allegion RLBD
Allegion WPR400-MTK
Allegion 8B-626
Allegion COM300L-643E
Allegion COM400L-626
Allegion SI-626
Allegion SIK-626
Allegion TK400
Schlage USB and 2-pin Android cable for SUS
Schlage COM300L
Schlage 47278749

Description (for prices starting on January 02 2025)

Aperio RS485 Hub Gen 5 - NA Version - Requires ACM version 6.54 or newer and Mercury FW v.2.x - Cannot share

LifeSafety Power Custom

SALTO NEO Cam - RIM - Mortise - Server Rack Cylinder

SALTO SP Custom Line Item

SALTO XS4 ANSI MINI Lock

Allegion (Schlage) | AD-400 networked wireless | 993M Exit Mortise Lock | 70 - Classroom - Storeroom Functiona

AD Series Wireless Lock

Allegion (Schlage) | AD-400 networked wireless | CY - Cylindrical Lock | 70 - Classroom - Storeroom Functionality

Allegion (Schlage) | AD-400 networked wireless | CY - Cylindrical Lock | 70 - Classroom - Storeroom Functionality

Allegion (Schlage) | AD-400 networked wireless | MS - Mortise Lock | 70 - Classroom - Storeroom Functionality |

AC-SALTO-SHIP-OPTION-SPACE-OPT-0018 (Do not use)

AElement Fusion reader and electronics - AFM2PMB3A8

Signo PIV 20; Pigtal; Prox Enabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 20; Terminal; Prox Enabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 20K; Keypad; Terminal; Prox Enabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 40; Pigtal; Prox Enabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 40; Pigtal; Prox Disabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 40; Terminal; Prox Enabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 40; Terminal; Prox Disabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 40K; Keypad; Pigtal; Prox Enabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 40K; Keypad; Pigtal; Prox Disabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 40K; Keypad; Terminal; Prox Enabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

Signo PIV 40K; Keypad; Terminal; Prox Disabled; HDX; 200Bit FASC-N with UUID 128Bit fallback

PAM Firmware Standard Maintenance & Support; STD M&S 8X5 M-F CST (Requires pivCLASS Supplemental Orderi

PAM; PIVCLASS (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLAS

RDR; R40-H; PIVCLASS; SE E; LF OFF; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN; BZ

RDR; RP40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN; B

RDR; RP40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN; B

RDR; RK40-H; PIVCLASS; SE E; LF OFF; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; PIG; BLK; STD-1; OSDP V2; OPEN COLL

RDR; RK40-H; PIVCLASS; SE E; LF OFF; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; PIG; BLK; STD-1; LED RED; FLSH GRN; F

RDR; RK40-H; PIVCLASS; SE E; LF OFF; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; PIG; BLK; STD-1; LED RED; FLSH GRN; F

RDR; RK40-H; PIVCLASS; SE E; LF OFF; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; TERM; BLK; STD-1; OSDP V2; OPEN CC

RDR; RK40-H; PIVCLASS; SE E; LF OFF; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; TERM; BLK; STD-1; LED RED; FLSH GRN
RDR; RK40-H; PIVCLASS; SE E; LF OFF; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN; E
RDR; RK40-H; PIVCLASS; SE E; LF OFF; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN; E
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; PIG; BLK; STD-1 ; LED RED; FLSH GRN
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; PIG; BLK; STD-1; OSDP V2; OPEN COL
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; PIG; BLK; STD-1; LED RED; FLSH GRN;
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; PIG; BLK; STD-1; OSDP V1; OPEN COL
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; PIG; BLK; STD-1; OSDP V1; OPEN COL
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485HDX; TERM; BLK; STD-1; LED RED; FLSH GR
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN;
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN;
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN;
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN;
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GRN;
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; PIG; BLK; STD-1; LED RED; FLSH GR
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; TERM; BLK; STD-1; LED RED; FLSH GR
RDR; RPK40-H; PIVCLASS; SE E; LF STD; HF STD/SIO/SEOS/FIPS/CAK; 485FDX; TERM; BLK; STD-1; LED RED; FLSH GR
RDR; RKCL40-P; PIVCLASS; SE E; CONT LCD; RF SUPPR; 485HDX; PIG; BLK; STD-1; A/V OFF; OSDP V2; OPT TAMP; OI
RDR; RPKCL40-P; PIVCLASS; SE E; CONT LCD; LF STD; HF STD/SIO/SEOS/FIPS/CAK/PKI; 485HDX; PIG; BLK; STD-1; LE
RDR; RPKCL40-P; PIVCLASS; SE E; CONT LCD; LF STD; HF STD/SIO/SEOS/FIPS/CAK/PKI; 485HDX; TERM; BLK; STD-1;
RDR; RKCLB40-P; PIVCLASS; SE E; CONT LCD BIO; LF OFF; HF STD/SIO/SEOS/FIPS/CAK/PKI; 485FDX; PIG; BLK; STD-1
RDR; RKCLB40-P; PIVCLASS; SE E; CONT LCD BIO; LF OFF; HF STD/SIO/SEOS/FIPS/CAK/PKI; 485FDX; TERM; BLK; STL
RDR/ENROLLER; RKL40; ICLASS; SE E; HF STD BIO/SEOS BIO; LCD/BIO; WIEG; TERM; BLK; STD-1; LED RED; FLSH GI
EMBEDDED AUTHENTICATION CONTROLLER; STD M&S 8X5 M-F CST (Requires pivCLASS Supplemental Ordering In
PIVCLASS BUNDLE; EMBEDDED AUTHENTICATION MODULE & TWO RP40-H TERMINAL READERS; FIRST YEAR EA M
TWO (2) EMBEDDED AUTHENTICATION LICENSES (Requires pivCLASS Supplemental Ordering Information form wit
PIVCLASS CERTIFICATE MANAGER; 1 LICENSE/PACS; DOWNLOAD; CODEBENCH SUPPLIER (Requires pivCLASS Supp
CERTIFICATE MANAGER; STD M&S 8X5 M-F CST; CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Orderin
PIVCLASS VALIDATION WORKSTATION & DOCUMENTATION; DOWNLOAD; CODEBENCH SUPPLIER (Requires pivCLA
VALIDATION WORKSTATION STD M&S 8X5 M-F CST; CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ord
READER SERVICES; STD M&S 8X5 M-F CST; CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Infor
PIVCLASS REGISTRATION ENGINE; AVIGILON ACM; DOWNLOAD (Requires pivCLASS Supplemental Ordering Inform
REGISTRATION ENGINE; STD M&S 8X5 M-F CST; CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering
SALTO Mortise cylinder collar. B=3/8" (9.5mm) collar; Satin stainless steel (US32D) (Available only in the USA and
Adapter Ring; 1/4" key override depth spacer; satin stainless (Available only in the USA and Canada)
Adapter Ring; 1/8" key override depth spacer; satin stainless (Available only in the USA and Canada)
AEElement elec|Black Rdr|BLE|Mifare|DESFire|SVN; Standard|Anthracite BB|satin stainless trim (Available only in
AEElement elec|Black Rdr|BLE|Mifare|DESFire|SVN; Standard|Anthracite BB|polished ss trim (Available only in th
AEElement elec|Black Rdr|BLE|Mifare|DESFire|SVN; Elec Privacy|Anthracite BB|satin stainless trim (Available only
AEElement elec|Black Rdr|BLE|Mifare|DESFire|SVN; Elec Privacy|Anthracite BB|polished ss trim (Available only in
SALTO AEElement Fusion electronics. Includes split spindles that must be used with the AEElement handle set (Morti
SALTO J handle for AEElement handle set. Round rose. To be fitted with the split spindle provided with the AElemer
SALTO J handle for AEElement handle set. Round rose. To be fitted with the split spindle provided with the AElemer
SALTO W handle for AEElement handle set. Round rose. To be fitted with the split spindle provided with the AElemer
Mortise Lock|AEElement|ANSI; Door+Egress detectors|RH|stainless steel (Available only in the USA and Canada)
SALTO AEElement Fusion mortise lock with dead bolt and panic function. Stainless steel (Available only in the USA a
SALTO Mortise Lock|Deadbolt|AEElement|ANSI | Privacy+Door+Egress detectors|LH|satin brass (Available only in

Mortise Lock|AElement|ANSI; Door+Egress detectors|RH|satin brass (Available only in the USA and Canada)
 SALTO AElement electronics with ANSI mechanical privacy. Includes split spindles that must be used with the AElement
 SALTO AElement Fusion electronics. Includes split spindles that must be used with the AElement handle set (Morti
 AElement Fusion reader and electronics / Satin Brass front plate / needs AElement mortise and handles (not inc
 Assembly Tool|Neox Padlock; (Available only in the USA and Canada)
 Wireless Gateway|BLUEnet node|black|12VDC xfmr; Ethernet|supports upto 6 additional wired nodes (Available
 Wireless Gateway|BLUEnet node|white|12VDC xfmr; Ethernet|supports upto 6 additional wired nodes (Available
 Clutch mechanism. (Available only in the USA and Canada)
 Control Unit|XS4 2.0|two rdr|6 in|4 out|ethernet; expandable via RS485|12VDC xfmr|encl|clear cover (Available
 Control Unit|XS4 2.0|two rdr|6 in|4 out|ethernet; expandable via RS485|12VDC xfmr|encl|Grey cover (Available
 Control Unit|XS4 2.0|two rdr|6 in|4 out|ethernet; expandable via RS485|12VDC xfmr|No enclosure (Available or
 Control Unit|XS4 2.0|two rdr|6 in|4 out|RS485 aux; offline or exp of CU42Ex|12V xfmr|encl|Clear cover (Availab
 Control Unit|XS4 2.0|two rdr|6 in|4 out|RS485 aux; offline or exp of CU42Ex|12V xfmr|encl|Grey cover (Availabl
 Control Unit|XS4 2.0|two rdr|6 in|4 out|RS485 aux; offline or exp of CU42Ex|12VDC xfmr|No enclosure (Availabl
 SALTO Cover Plate Pr - ANSI - Wide - Cyl cartridge compatible. (Available only in the USA and Canada)
 Cover Plate Pr|ANSI wide|cyl cartridge compatible; 13-53/64" H X 4-21/64" W|satin stainless (Available only in th
 SALTO proximity silicone Bracelets; MIFARE; 01K | 1KBytes; Black; Large; Pack of 5 bracelets (Available only in the
 SALTO proximity silicone Bracelets; MIFARE; 01K | 1KBytes; Black; Medium; Pack of 5 bracelets (Available only in t
 SALTO proximity silicone Bracelets; MIFARE; 01K | 1KBytes; Black; Small; Pack of 5 bracelets (Available only in the
 SALTO Credential|CR80 card|dual technology; Mifare 4KB with magstripe|pack of 50 (Available only in the USA ar
 Credential|Construction Card|HID iClass; testing and management prior to initialization (Available only in the USA
 Credential|Construction Card|Mifare; testing and management prior to initialization (Available only in the USA an
 Credential|CR80 card|printable white|HID iClass; 32Kbs|sammed for use with Salto standard codes; pack of 50 (A
 Credential|CR80 card|printable white|Mifare 4KB; pack of 50 (Available only in the USA and Canada)
 Credential|CR80 card|printable white|Mifare 1KB|pack of 50 (Available only in the USA and Canada)
 SALTO Credential|CR80 card|dual technology; Mifare 4KB with magstripe|pack of 50 (Available only in the USA ar
 Credential|FOB|blue with white center Salto logo; DESFire EV2 4KB|pack of 10 (Available only in the USA and Can
 Credential|FOB|black with white center Salto logo; DESFire EV2 4KB|pack of 10 (Available only in the USA and Car
 Credential|FOB|blue with white center Salto logo; Mifare 4KB|pack of 10 (Available only in the USA and Canada)
 SVNKS | SALTO KS + SVN compatible Tags - Blue - Pack of 5 (Available only in the USA and Canada)
 SVNKS | SALTO KS + SVN compatible Tags - Green - Pack of 5 (Available only in the USA and Canada)
 SVNKS | SALTO KS + SVN compatible Tags - Red - Pack of 5 (Available only in the USA and Canada)
 SVNKS | SALTO KS + SVN compatible Tags - Silver - Pack of 5 (Available only in the USA and Canada)
 SVNKS | SALTO KS + SVN compatible Tags - White - Pack of 5 (Available only in the USA and Canada)
 Alignment Kit|Cylindrical Cartridge; use with Ax6xx and LCxK cartridge combination (Available only in the USA and
 SALTO cylindrical latch grade 1. ANSI A156.2 grade1. model K. squared front plate. latch by lever either side. Auxili
 Cylindrical Cartridge Lock|ANSI|Grade 2; 2-3/4" backset(stnd comm)|satin stainless (Available only in the USA and
 Deadbolt; single cylinder for use with GEO heavy duty deadbolt cylinder; 2 3/4" backset; standard operation; satin
 Deadbolt|less single cyl|2 3/8" backset|requires eCylinder|satin stainless (Available only in the USA and Canada)
 SALTO NEO Heavy duty deadbolt electronic double cylinder. To be used in combination with SALTO deadbolt LD41
 RFDCT | Door detector with plug connection for the SALTO wireles escutcheon; S | For steel doors; 18 | For wide
 SALTO RFDCT Door detector with plug connection for the SALTO wireless escutcheon - for Wood doors.- for wide
 SALTO SPACE-OPT-0035 This feature permits you to enable the elevators communication module to mange syster
 Emergency Power Supply|PPD connection cord; battery harness|requires 4 AA batteries (Available only in the USA/
 SALTO NCoder - Proximity card encoder Mifare/DESFire. USB and Ethernet connections. DHCP addressing. Desktop|
 Encoder|BLE|DESFire|Mifare|ethernet; USB|can be used as desktop reader (Available only in the USA and Canad
 Encoder|BLE|HID iClass|ethernet; USB|can be used as desktop reader (Available only in the USA and Canada)

Expansion Unit|XS4 2.0|4 in|8 out|RS485 auxillary; exp of CU42xx|12VDC xfmr|No enclosure (Available only in the SALTO Geo installation tool (NOT NEO) (Available only in the USA and Canada)
 SALTO Neo installation tool (Available only in the USA and Canada)
 Locker Lock|XS4|BLE|DESFire|Mifare|battery incl; 20-30mm door|sandwich mount|BioCote|anthracite rdr (Avail
 Locker Lock|XS4|BLE|DESFire|Mifare|battery incl; 20-30mm door|sandwich mount|BioCote|white rdr rdr (Avail
 Locker Lock|XS4|BLE|HID iClass|SEOS|battery incl; 20-30mm door|sandwich mount|BioCote|anthracite rdr (Ava
 Locker Lock|XS4|BLE|HID iClass|SEOS|battery incl; 20-30mm door|sandwich mount|BioCote|white rdr rdr (Avail
 Replacement Part: Single thumbturn knob for locks.(Available only in the USA and Canada)
 SALTO ProAccess SPACE; SPACE Mobile Users License (0016-1); included for first 12 months from software registrati
 SALTO Modular XS Wall Reader Proximity BLE DESFire/Mifare. Includes concealed fixing covers. Excludes fixing ba
 Mortise Lock|ANSI|Grade 1|32mm faceplate; Door detector|LH(field rev)|satin stainless (Available only in the US
 Mortise Lock|ANSI|Grade 1|32mm faceplate; Door detector|RH(field rev)|satin stainless (Available only in the US
 SALTO ANSI mortise lock with latch. Auxiliar latch (anticard) deadlocks the latch. (Available only in the USA and Ca
 Mortise Lock|AEElement|ANSI; Door+Egress detectors|LH|satin stainless (Available only in the USA and Canada)
 Mortise Lock|AEElement|ANSI; Door+Egress detectors|LHR|satin stainless (Available only in the USA and Canada)
 Mortise Lock|AEElement|ANSI; Door+Egress detectors|RH|satin stainless (Available only in the USA and Canada)
 Mortise Lock|AEElement|ANSI; Door+Egress detectors|RHR|satin stainless (Available only in the USA and Canada)
 Mortise Lock|AEElement|ANSI; Privacy+Door+Egress detectors|LH|satin stainless (Available only in the USA and Ca
 Mortise Lock|AEElement|ANSI; Privacy+Door+Egress detectors|LHR|satin stainless (Available only in the USA and C
 Mortise Lock|AEElement|ANSI; Privacy+Door+Egress detectors|RH|satin stainless (Available only in the USA and C
 Mortise Lock|AEElement|ANSI; Privacy+Door+Egress detectors|RHR|satin stainless (Available only in the USA and C
 Mortise Lock|Deadbolt|ANSI|Grade 1|32mm faceplate - Door detector|LH (field rev)|satin stainless (Available or
 Mortise Lock|Deadbolt|ANSI|Grade 1|32mm faceplate - Door detector|RH(field rev)|satin stainless (Available on
 ANSI Mortise with latch and deadbolt / Grade 1 / 32mm front plate / satin brass Left Handing
 ANSI Mortise with latch and deadbolt / Grade 1 / 32mm front plate / satin brass Right Handing
 SALTO Mortise Lock Deadbolt ANSI Grade 1 27mm faceplate; Door detector RH(field rev) satin stainless (Available
 SALTO Mortise Lock - ANSI with latch and automatic deadbolt. with panic function|Auto-DB|ANSI|Grade 1|32mm
 SALTO Mortise Lock - ANSI with latch and automatic deadbolt. with panic function|Auto-DB|ANSI|Grade 1|32mm
 NEO Cam Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP55|BioCote (Available only in the USA and Canada)
 NEO Cam Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP66|BioCote (Available only in the USA and Canada)
 NEO Cam Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP55|polished chrome (Available only in the USA and Canada)
 NEO Cam Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP66|polished chrome (Available only in the USA and Canada)
 NEO Cam Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP55|satin chrome (Available only in the USA and Canada)
 NEO Cam Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP66|satin chrome (Available only in the USA and Canada)
 SALTO NEO Cam lock electronic cylinder. Cylinder body: 19mm. Technology: Mifare; Bluetooth LE + HSE. (Available
 SALTO NEO RIM USA profile electronic cylinder. Exterior cylinder; one knob; no thumbturn. Technology: Mifare; Bl
 SALTO NEO RIM USA profile electronic cylinder. Exterior cylinder; one knob; no thumbturn. Technology: Mifare; Bl
 SALTO NEO RIM USA profile electronic cylinder. Exterior cylinder; one knob; no thumbturn. Technology: Mifare; Bl
 SALTO NEO Heavy duty deadbolt electronic double cylinder. To be used in combination with SALTO deadbolt LD41
 SALTO NEO Heavy duty deadbolt electronic cylinder. To be used in combination with SALTO deadbolt LD51 or LD7
 SALTO NEO Mortise profile electronic cylinder Exterior cylinder; one knob; no thumbturn. Technology: Mifare; Blu
 SALTO NEO Mortise profile electronic cylinder Exterior cylinder; one knob; no thumbturn. Technology: Mifare; Blu
 SALTO NEO Mortise profile electronic cylinder Exterior cylinder; one knob; no thumbturn. Technology: Mifare; Blu
 SALTO NEO Mortise profile electronic cylinder Exterior cylinder; one knob; no thumbturn. Technology: Mifare; Blu
 SALTO NEO Mortise profile electronic cylinder Exterior cylinder; one knob; no thumbturn. (Can be initialized in SAL
 SALTO NEO Mortise profile electronic cylinder Exterior cylinder; one knob; no thumbturn - BLE DESFire MIFARE: St
 NEO Mortise Cylinder|HID iClass|SEOS|SVN; Black Rdr|1-1/4" body length|IP55|BioCote (Available only in the US

NEO Mortise Cylinder|HID iClass|SEOS|SVN; Black Rdr|1-1/4" body length|IP66|BioCote (Available only in the US
 NEO Mortise Cylinder|HID iClass|SEOS|SVN; Black Rdr|1-1/4" body length|IP55|polished chrome (Available only
 NEO Mortise Cylinder|HID iClass|SEOS|SVN; Black Rdr|1-1/4" body length|IP66|polished chrome (Available only
 NEO Mortise Cylinder|HID iClass|SEOS|SVN; Black Rdr|1-1/4" body length|IP55|satin chrome (Available only in tl
 NEO Mortise Cylinder|HID iClass|SEOS|SVN; Black Rdr|1-1/4" body length|IP66|satin chrome (Available only in tl
 Salto G4 NEOXX Padlock - permanent 50mm Shackle; 11 MM diameter; polished chrome; black; with chain. (Avail
 SALTO Neoxx Padlock G4 (Available only in the USA and Canada)
 SALTO NEO Rim Cylinder|BLE|Mifare|DESFire|SVN - Black Rdr|Salto DB not incl|IP55|BioCote (Available only in tl
 SALTO NEO Rim Cylinder|BLE|Mifare|DESFire|SVN - Black Rdr|Salto DB not incl|IP66|BioCote (Available only in tl
 NEO Server Rack Cyl|HID iClass|SEOS|SVN; Black Rdr|40mm long|satin black (Available only in the USA and Canac
 NEO Server Rack Cyl|HID iClass|SEOS|SVN; Black Rdr|40mm long|satin black (Available only in the USA and Canac
 NEO US Rim Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP55|BioCote (Available only in the USA and Canada)
 NEO US Rim Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP66|BioCote (Available only in the USA and Canada)
 NEO US Rim Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP55|polished chrome (Available only in the USA and Canac
 NEO US Rim Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP66|polished chrome (Available only in the USA and Canac
 NEO US Rim Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP55|satin chrome (Available only in the USA and Canada)
 NEO US Rim Cylinder|HID iClass|SEOS|SVN; Black Rdr|IP66|satin chrome (Available only in the USA and Canada)
 Neoxx Padlock|HID iClass|SEOS|BLE|SVN|Black; Non-removable shackle 11mm dia-60mm len|IP66 (Available onl
 Outdoor Kit; pair of gaskets for weather exposed; XS4 escutcheons; pack of 6 sets (Available only in the USA and C
 Portable Programming Device|NFC|USB connection; 3 pin harness connector|req 3 AAA batteries; incl (Available
 SPAONLINE. Starter kit includes choice of ProAccess Space Software; PCM04K-50 (contactless Mifare smart card; 4
 SALTO ProAccess SPACE software SPACE-OPT-0032; SALTO event-alarms & communication module. Enables event
 SALTO ProAccess SPACE; ProAccess SPACE Software |Online|SVN|RF|Lockdown; Event Stream|Automatic Key As
 SALTO ProAccess SPACE software Partitional package that includes: - All the features included in the SALTO ProAcc
 SALTO Starter Kit - ProAccess SPACE Software - Online; standard readers; ANSI; black readers (Available only in the
 Wireless Gateway|RFnet node|black|12VDC xfmr; Ethernet|supports upto 6 additional wired nodes (Available on
 Wireless Gateway|RFnet node|white|12VDC xfmr; Ethernet|supports upto 6 additional wired nodes (Available or
 Rim Panic Bar Device|33" length - Use w/KPB03|satin stainless (Available only in the USA and Canada)
 SALTO RIM Panic Bar Device. Stainless steel finish. Latchdeadlocking system. Max 1220mm wing width. Strike plat
 Salto Authorization Module(SAM)|DESFire|EndUser; requires EC9xx|application subject to approval; SAM Softwar
 Salto Authorization Module(SAM)|HID iClass|EndUser; requires ECHxx|application subject to approval; SAM Softw
 Shackle Chain|collar attached|300mm length; For use with Neoxx Padlock; Padlock Not Included (Available only ir
 SALTO ProAccess SPACE; SPACE SHIP Interface Option (0018) (Available only in the USA and Canada)
 SALTO Outdoor kit for exterior doors. (Available only in the USA and Canada)
 SALTO Cover for space ring. Silver (Available only in the USA and Canada)
 Salto SPACE Training Kit (one user) (Available only in the USA and Canada)
 Spacer Plate for door thickness 1-1/4" - 1-3/8" (30-35mm) (Available only in the USA and Canada)
 SALTO Contactless smart stickers.(Available only in the USA and Canada)
 Credential|smart sticker|1" round|white PVC | Pack of 20 stickers | Mifare 4KB|pack of 20 (Available only in the I
 Replacement Part: 25 Pack. Internal pin for lockset. (Available only in the USA and Canada)
 The UBOX4000 offers a compact solution updatr kit based on a SALTO Controller and a Wall Reader that permits
 The UBOX4000 offers a compact solution updatr kit based on a SALTO Controller and a Wall Reader that permits
 Wall Reader|ANSI|XS4 2.0|BLE|DESFire|Mifare|White; series CU42xx controller req|IP66 (Available only in the U
 Wall Reader|ANSI|XS4 2.0|BLE|HID iClass|Black; series CU42xx controller req|IP66 (Available only in the USA and
 Wall Reader|ANSI|XS4 2.0|BLE|HID iClass|White; series CU42xx controller req|IP66 (Available only in the USA an
 Wall Reader|Mullion|XS4 2.0|BLE|DESFire|Mifare; White|series CU42xx controller req|IP66 (Available only in the
 Wall Reader|Mullion|XS4 2.0|BLE|HID iClass; Black|series CU42xx controller req|IP66 (Available only in the USA &

Wall Reader| Mullion|XS4 2.0|BLE|HID iClass; White|series CU42xx controller req|IP66 (Available only in the USA
 Wall Reader|Panel Mount|XS4 2.0|BLE|DESFire|Mifare; Incl stickers|series CU42xx controller req|IP66
 Wireless Node|BLUEnet|white; Wired|requires GATEWAYxx for operation (Available only in the USA and Canada)
 Wireless Node|RFnet|white; Wired|requires GATEWAYxx for operation (Available only in the USA and Canada)
 SALTO ProAccess SPACE; SPACE BLUEnet Wireless Connection Option (0033); 1ea per Lockset (online) (Available o
 SALTO ProAccess SPACE; SPACE Wireless Option (0021)|enables RF (Available only in the USA and Canada)
 Wireless Repeater|BLUEnet|white; Wired|requires GATEWAYx3 or RFNODE3 for operation (Available only in the
 XS4 ANSI Mini|BLE|HID iClass|Black Rdr; Entrance|N lever|2-3/8" backset|BioCote (Available only in the USA and
 XS4 ANSI Mini|BLE|HID iClass|Black Rdr; Entrance|N lever|2-3/8" backset|polished chrome (Available only in the
 XS4 ANSI Mini|BLE|HID iClass|Black Rdr; Entrance|N lever|2-3/8" backset|satin chrome (Available only in the US/
 SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch; 2 handles; any type. Entrance Lock. Mifare D
 SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch; 2 handles; any type. Entrance Lock. Mifare D
 SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch; 2 handles; any type. Entrance Lock. MIFARE I
 SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch; 2 handles; any type. Entrance Lock. Mifare D
 SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch; 2 handles; any type. Entrance Lock with key
 SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch; 2 handles; any type. Entrance Lock with key
 SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch; 2 handles; any type. Entrance Lock with key
 XS4 Original connection circuit cable. For XS4 Originalwith door thickness up to 100mm (Available only in the USA
 SALTO Windshield transponder ISO-Format UHF 8 bytes for SALTO WRLUD readers. White neutral. UHF UID printe
 SALTO XS4 Electronic Escutcheon Ax650; with keypad For ANSI mortise locks; 2 handles; any type. BLE DESFire Tec
 SALTO XS4 ONE Electronic Escutcheon Ex756; 2 Handles; any type. Electronic "do not disturb" system. BLE Mifare
 SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder
 SALTO XS4 Original + Escutcheon|BLE|Mifare|DESFire|HSE|SVN | Privacy Button|ANSI N lever|BioCote | BlueNet
 SALTO XS4 Original + Escutcheon|BLE|Mifare|DESFire|HSE|SVN | Privacy Button|ANSI N lever|BioCote | BlueNet
 SALTO XS4 Original + Escutcheon|BLE|Mifare|DESFire|HSE|SVN |eadbolt|ANSI N lever|BioCote | BlueNet Capabl
 SALTO XS4 Original + Escutcheon|BLE|Mifare|DESFire|HSE|SVN |eadbolt|ANSI N lever|BioCote | BlueNet Capabl
 SALTO XS4 Original + Escutcheon |Door Thickness Change Kit (Available only in the USA and Canada)
 SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar; 1 handle; any type; built in mechanical cylinder with au
 SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar; 1 handle; any type; built in mechanical cylinder with au
 SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type. Technology: Mifare + Bluetooth LE
 SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type. Technology: Mifare + Bluetooth LE
 SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type. Technology: Mifare + Bluetooth LE
 SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type for concealed rod panic bars. Techn
 SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type. Technology: Mifare + Bluetooth LE
 SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type. Technology: Mifare + Bluetooth LE
 SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar; 1 handle; any type; built in mechanical cylinder with au
 SALTO XS4 Original+ Half escutcheon ANSI - Electronic Half Escutcheon Ax660 for panic bar; 1 handle; any type; bu
 SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; W handle type. Technology: Mifare + Bluetooth LE + H
 SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; W handle type. Technology: Mifare + Bluetooth LE + H
 SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar; 1 handle; any type; built in mechanical cylinder with au
 SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar; 1 handle; any type; built in mechanical cylinder with au
 XS4 Original+ Half escutcheon|BLE|Mifare|DESFire|HSE|Black Rdr|KO|Entrance|ANSI|N lever|satin ss; SALTO XS
 SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar; 1 handle; any type; built in mechanical cylinder with au
 SALTO XS4 Original + Panic Bar Trim|BLE|Mifare|DESFire|HSE|SVN | RIM compatible|ANSI N lever|BioCote | Blu
 SALTO XS4 Original + Panic Bar Trim|BLE|Mifare|DESFire|HSE|SVN | Con rod compatibl|ANSI N lever|BioCote | E
 SALTO XS4 Original + PB Kit| Corbin Russwin ED2500 & Yale 7100 | SVN|satin stainless (Available only in the USA &
 SALTO XS4 Original + PB Kit | Dorma Kabba | SVN|satin stainless (Available only in the USA and Canada)

SALTO XS4 Panic Bar Kit for versions of DORMA. (Available only in the USA and Canada)
SALTO XS4 Original + PB Kit | SARGENT 8888 | SVN |satin stainless (Available only in the USA and Canada)
SALTO XS4 Panic Bar Kit for versions of SARGENT 8800 prior to 2002 (Available only in the USA and Canada)
Kit panic bars - UNIVERSAL - KPB | Kit panic bars | SALTO XS4 Panic Bar Kit for versions of VON DUPRIN | Satin stai
SALTO XS4 Original + PB Kit | Salto PBF110 | Von Duprin series 98 & 99 | SVN |satin stainless (Available only in the U
SALTO XS4 Original + PB Kit | Von Duprin series 98/9927 & 98/9957 | SVN |satin stainless (Available only in the USA
SALTO XS4 Panic Bar Kit for versions of VON DUPRIN. (Available only in the USA and Canada)
SALTO XS4 Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handles; any type. Technology: Mifare + Blueto
SALTO XS4 Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handles; any type. Technology: Mifare + Blueto
SALTO XS4 Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handles; any type. Technology: Mifare + Blueto
SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type. Technology: Mifare + Bluetooth LE
SALTO XS4 Electronic Escutcheon Ax658; For ANSI mortise locks; 2 handles; any type; inside thumbturn 90°; with c
SALTO XS4 Electronic Escutcheon Ax658; For ANSI mortise locks; 2 handles; any type; inside thumbturn 90°; with c
SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder r
SALTO XS4 Electronic Escutcheon Ax666; For ANSI mortise locks; 2 handles; any type; electronic "do not disturb" s
SALTO XS4 Electronic Escutcheon Ax668; For ANSI mortise locks; 2 handles; any type; inside thumbturn 90°; with c
SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder r
XS4 Original+ Wide Body Escutcheon - ANSI | BLE | Mifare | DESFire | HSE | Black Rdr | Entrance | ANSI | A lever | satin ss (
SALTO XS4 Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handles; any type. Technology: Mifare + Blueto
SALTO XS4 Original+ Wide Body Escutcheon - ANSI - Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handl
SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type. Technology: Mifare + Bluetooth LE
SALTO XS4 Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handles; any type. Technology: Mifare + Blueto
SALTO XS4 Electronic Escutcheon AM650; For ANSI mortise locks; G Handle. Technology: Mifare + Bluetooth LE + B
SALTO XS4 Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handles; any type. Technology: Mifare + Blueto
SALTO XS4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | Entrance | ANSI | N lever | satin ss; XS4 Original+ Wide Boc
XS4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | Entrance | ANSI | W lever | satin ss (Available only in the USA and
SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar; 1 handle; any type. Technology: Mifare + Bluetooth LE
XS4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | Entrance | ANSI | W lever | blk chromium (Available only in the US
XS4 Original+ | Half Escutcheon for Panic Bar | BLE | Mifare | DESFire | HSE | Black Rdr | Entrance | ANSI | W lever | blk chrc
XS4 Original + 656 provacy button ANSI Mifare DesFire HSE Bluetooth A handle satin Stainless Black Reader Inter
XS4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | Privacy Button | ANSI | A lever | satin ss (Available only in the USA
SALTO XS4 Electronic Escutcheon Ax656; For ANSI mortise locks; 2 Handles; any type; Electronic "do not disturb" s
SALTO XS4 Electronic Escutcheon Ax656; For ANSI mortise locks; 2 Handles; any type; Electronic "do not disturb" s
SALTO XS4 original+ Wide Body Electronic Escutcheon; For ANSI mortise locks; 2 Handles; any type; Electronic "do
SALTO XS4 Electronic Escutcheon Ax656; For ANSI mortise locks; 2 Handles; any type; Electronic "do not disturb" s
XS4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | Privacy Button | ANSI | W lever | satin ss (Available only in the US
SALTO XS4 original+ Wide Body Electronic Escutcheon; For ANSI mortise locks; 2 handles; any type; inside thumbt
XS4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | Deadbolt | ANSI | N lever | satin ss (Available only in the USA and
SALTO XS4 Electronic Escutcheon Ax658; For ANSI mortise locks; 2 handles; any type; inside thumbturn 90°; with c
SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder r
SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder r
SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder r
SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder r
SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder r
SALTO XS4 Electronic Escutcheon Ax666; For ANSI mortise locks; 2 handles; any type; electronic "do not disturb" s
SALTO XS4 Electronic Escutcheon Ax666; For ANSI mortise locks; 2 handles; any type; electronic "do not disturb" s
SALTO XS4 Electronic Escutcheon Ax666; For ANSI mortise locks; 2 handles; any type; electronic "do not disturb" s

SALTO XS4 Electronic Escutcheon Ax666; For ANSI mortise locks; 2 handles; any type; electronic "do not disturb" s

SALTO XS4 Electronic Escutcheon Ax666; For ANSI mortise locks; 2 handles; any type; electronic "do not disturb" s

SALTO XS4 Electronic Escutcheon Ax666; For ANSI mortise locks; 2 handles; any type; electronic "do not disturb" s

SALTO XS4 Original+ Wide Body Escutcheon - ANSI - Electronic Escutcheon Ax658; For ANSI mortise locks; 2 handles

SALTO XS4 Electronic Escutcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder

SALTO XS4 Electronic Escutcheon Ax668; For ANSI mortise locks; 2 handles; any type; inside thumbturn 90°; with c

XS4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | KO | Entrance | ANSI | N lever | satin ss; SALTO XS4 Electronic Escu

SALTO XS4 Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handles; any type. Technology: Mifare + Blueto

XS4 PB Kit | Corbin Russwin ED2500 & Yale 7100 - SVN | satin stainless (Available only in the USA and Canada)

XS4 PB Kit | SARGENT 8888 - SVN | satin stainless (Available only in the USA and Canada)

XS4 PB Kit | SARGENT 8888 - SVN | RFnet | satin stainless (Available only in the USA and Canada)

XS4 PB Kit | Salto PBF110 | Von Duprin series 98 & 99 - SVN | satin stainless (Available only in the USA and Canada)

XS4 PB Kit | Von Duprin series 98/9927 & 98/9957 - SVN | satin stainless (Available only in the USA and Canada)

SALTO KPBO3XX.. Adapter Kit for Von Duprin 98/99 Panic Bar Single Point (Available only in the USA and Canada)

SALTO XS4 UHF Long Distance Reader. Up to 7 meters distance reading. To be used with CU42E0 controller. Needs

SALTO XS4 UHF Long Distance Reader 10 meters connection cable - 10m length Connection cable - 10m with 4 pin c

SALTO XS4 UHF long Distance Reader SIC module LD Reader - CU42E0 Wiegand signal converter device. (Available

SVM™ (main application) per workstation; includes Free Administrator™ (HID Part Number: EL-96000-SVM10)

Administrator™ (additional licenses) per workstation (HID Part Number: EL-96300-ADM10)

EasyLobby® eKiosk™ Self Registration Software makes it fast and easy for visitors to register themselves upon arri

eAdvance™ (web pre-registration) per web server (HID Part Number: EL-98000-EADV10)

Access Control Integration - Access Control Manager from EasyLobby - Must also purchase Avigilon Rest License (A

Access control integration upgrade to latest version (HID Part Number: EL-ACI-UPGRD)

AssureTec ID-150 (reads driver's license; data and photo capture) (COO: South Korea) (HID # EL-AST-ID150)

AssureTec ID-150A (reads/authenticates driver's license; data and photo capture) (COO: South Korea) (HID # EL-A

AssureTec PRO software library updates for 1 year (data and authentication) (HID # EL-AST-UPDATEA)

The HID EasyLobby DESCO ICON Scanner's class leading scan technology; developed by DESKO; provides high-reso

DYMO 30856 non-adhesive badges (250) (HID Part Number: EL-DYMO-30856)

DYMO 30911 adhesive self-expiring badges (250) (HID Part Number: EL-DYMO-30911)

Dymo 450 Turbo Thermal Printer (B&W) (HID Part Number: EL-DYMO-450T)

DYMO LABELWRITER 550 B&W PRINTER (HID Part Number: EL-DYMO-550)

eAdvance software upgrade to latest version (HID Part Number: EL-EADV-UPGRD)

1 copy of SVM software; includes Free Administrator™ software (admin/reporting) Special bundle package for K-1

Sex offender screening service per year per system Special bundle package for K-12 schools only (HID # EL-SOS-K1

ACUANT SNAPSHELL R2 DRIVER'S LICENSE SCANNER (COO: Israel) (HID # EL-SS-R2)

A/C INTEGRATION ANNUAL MAINTENANCE PER COPY (INCLUDES UPGRADES AND UPDATES)

EADVANCE ANNUAL MAINTENANCE PER COPY (INCLUDES UPGRADES AND UPDATES) (HID Part Number: EL-SSA-EA

K12 ANNUAL SOFTWARE MAINTENANCE PLAN (FOR FREE UPDATES AND UPGRADES) = PER YEAR PER SYSTEM

SVM ANNUAL MAINTENANCE PER COPY (INCLUDES ALL UPDATES AND UPGRADES) (HID Part Number: EL-SSA-SVM

SVM software upgrade to SVM10 (HID Part Number: EL-SVM10-UPGRD)

Topaz SignatureGem LCD 1x5 SigPad (signature block only) (HID Part Number: EL-TOP-1X5)

Access Control Manager 6 License 30 Day Demonstration: includes licensing for Badging; Exacq; Milestone; one B

Additional 16 Doors Expansion Software Licenses for Avigilon Access Control Manager Professional; Enterprise; En

Access Control Manager 6 Hot Standby - Auto Failover Software License (per Appliance) includes AC-SW-LIC-REP-6

Badging Software Licenses for Avigilon Access Control Manager Professional; Enterprise; Enterprise Plus & Virtual

Access Control Manager 6 Partitioning License for additional partitions (per appliance)

Access Control Manager 6 Multi-Appliance Replication Software License (per appliance)

Access Control Manager 6 REST Connectivity Software License (per appliance)
Access Control Manager 6 Wireless Lock Connectivity Software License for each wireless locks not purchased from
UA7 1000 Door License
UA7 100 Door License
UA7 10 Door License
UA7 1 Door License
Includes the Availability & Network; Situational Awareness; Data & Templates; and Integrations Add-on
UA7 Availability and Network Add-on
UA7 Situational Awareness Add-on
UA7 Base Package License (includes 20 doors)
UA7 Data and Templates Add-on
UA7 Integrations Add-on
UA7 Service Plan for up to 1000 doors; 1 Year
UA7 Service Plan for up to 1000 doors; 3 Years
UA7 Service Plan for up to 1000 doors; 5 Years
UA7 Service Plan for up to 2000 doors; 1 Year
UA7 Service Plan for up to 2000 doors; 3 Years
UA7 Service Plan for up to 2000 doors; 5 Years
UA7 Service Plan for up to 250 doors; 1 Year
UA7 Service Plan for up to 250 doors; 3 Years
UA7 Service Plan for up to 250 doors; 5 Years
UA7 Service Plan for up to 4000 doors; 1 Year
UA7 Service Plan for up to 4000 doors; 3 Years
UA7 Service Plan for up to 4000 doors; 5 Years
ACM6 to UA7 Upgrade Package for up to 1000 doors (include 1 Year Service Plan)
ACM6 to UA7 Upgrade Package for up to 2000 doors (include 1 Year Service Plan)
ACM6 to UA7 Upgrade Package for up to 250 doors (include 1 Year Service Plan)
UA7 Wireless Lock License
Access Control Manager 6 LDAP Directory Connectivity Software License (required for integration with Microsoft /
Access Control Manager 6 Oracle Server Connectivity Software License (from Oracle DB 9i forward)(per appliance)
Access Control Manager 6 Microsoft SQL Server Connectivity Software License (from Microsoft SQL 2000 forward)
Access Control Manager 6 XML Events Connectivity Software License (per appliance)
Access Control Manager 6 License for the migration and conversion of a single ACM Embedded Controller into an
Bosch Intrusion (10 Panel) Integration Software Licenses for Avigilon Access Control Manager 6 Professional; Ente
Bosch Intrusion (1 Panel) Integration Software Licenses for Avigilon Access Control Manager 6 Professional; Ente
Access Control Manager 6 for 10 panel license for DMP intrusion panel integration. Panels supported: XR150 & XR
Access Control Manager 6 per panel license (one panel) for DMP intrusion panel integration. Panels supported: XR
Access Control Manager 6 NON OEM (Non Avigilon Ordered) HID VertX EVO V1000 or HID VertX EVO V2000 Assim
ViRDI BE Manager Integration Software Licenses for Avigilon Access Control Manager 6 Professional; Enterprise; E
Access Control Manager 6 License for Video Integration for Exacq (per appliance)
Access Control Manager 6 License for Video Integration for Milestone (per appliance)
Access Control Manager 6 (ACM) Verify license for 16 virtual stations (per appliance)
Access Control Manager 6 (ACM) Verify license for 5 virtual stations (per appliance)
Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 1024 Readers - includes: | physical
Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 16 Readers - includes: | physical a
Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 2048 Readers - includes: | physical
Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 512 Readers - includes: | physical

1 Year Extended Warranty for Access Control Manager Enterprise Plus Appliance
2 Year Extended Warranty for Access Control Manager Enterprise Plus Appliance
UA7 Enterprise Plus Appliance
1 Year Extended Warranty for UA Enterprise Plus Appliance
2 Year Extended Warranty for UA Enterprise Plus Appliance
1 Year Extended Warranty for Access Control Manager Enterprise Appliance
2 Year Extended Warranty for Access Control Manager Enterprise Appliance
UA7 Enterprise Appliance
1 Year Extended Warranty for UA Enterprise Appliance
2 Year Extended Warranty for UA Enterprise Appliance
1 Year Extended Warranty for Access Control Manager Professional Appliance
2 Year Extended Warranty for Access Control Manager Professional Appliance
UA7 Professional Appliance
1 Year Extended Warranty for UA Professional Appliance
2 Year Extended Warranty for UA Professional Appliance
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 1024 Readers - includes: embedded 64 bit Linux O
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 128 Readers - includes: embedded 64 bit Linux OS
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 16 Readers - includes: embedded 64 bit Linux OS &
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 2048 Readers - includes: embedded 64 bit Linux O
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 256 Readers - includes: embedded 64 bit Linux OS
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 32 Readers - includes: embedded 64 bit Linux OS &
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 512 Readers - includes: embedded 64 bit Linux OS
Access Control Manager Virtual 6 - Web-Based PACS Virtual for 64 Readers - includes: embedded 64 bit Linux OS &
UA7 Virtual Hyper-V Appliance License
UA7 Virtual VMware Appliance License
AXIAL LEADED 1K1%1/4W RESISTORS; 32-pack(Mercury Part Number: RES-1K32)
CABLE FOR MR-50 TAMPER (Mercury Part Number: A-TC-MR50)
Replace 3-Position Terminal Blocks; 10-pack(Mercury Part Number: A-TERM5-3)
Replace 4-Position Terminal Blocks; 10-pack(Mercury Part Number: A-TERM5-4)
Replace 5-Position Terminal Blocks; 10-pack(Mercury Part Number: A-TERM5-5)
Replace 6-Position Terminal Blocks; 10-pack(Mercury Part Number: A-TERM5-6)
16 Zone Input Monitor Module with 2 relays (Mercury Part Number: MR16in-S3)
16 Relay Output Control Module (Mercury Part Number: MR16out-S3)
Series 3 Single Reader Interface Module: mag or wiegand; 2 inputs; 2 relays (Mercury Part Number: MR50-S3)
HID® Mercury™ MR52-S3B Controller Serial I/O Dual Card Reader Interface; 2-Reader Interface Module - (2 reader
Intelligent Controller; Linux Based with 2 doors; 8 inputs and 4 outputs; expandable up to 64 doors. (Mercury Part
MERCURY MP1501 INTELLIGENT CONTROLLER WITH POE+ (1 DOOR; 2 READERS; 2 INPUTS; 2 OUTPUTS)
MERCURY MP1502 INTELLIGENT CONTROLLER (2 DOORS; 4 READERS; 8 INPUTS; 4 OUTPUTS)
MERCURY MP2500 INTELLIGENT CONTROLLER (NO ON-BOARD IO)
MERCURY MP4502 INTELLIGENT CONTROLLER WITH EXTENDED APPLICATIONS (2 DOORS; 4 READERS; 8 INPUTS; 4
Mercury M5 Bridge 16 DO; 16 Digital Output Control Module-(16 digital arrays) (1 board)(Mercury Part Number: I
Mercury M5 Bridge 20 IN; 20 Zone Input Monitor Module (1 board)(Mercury Part Number: M5-20IN-1)
Mercury M5 Bridge M2000 with with M5 IC; Multi-device interface panel for replacement of the Casi M2000 read
Mercury M5 Bridge M2000 only; Multi-device interface panel for replacement of the Casi M2000 reader controlle
Mercury M5 Bridge 2SRP; Supervised Reader Interface Module-(2 Rdr; 4 Inputs; 6 Outputs) (1 board)(Mercury Pai
Mercury M5 Bridge 8RP; Supervised Reader Interface Module-(8 Supervised Rdr Connections) (1 board)(Mercury
Mercury M5 Bridge IC; Intelligent Controller; 32MB RAM; Ethernet; Dual RS485 ports (1 board)(Mercury Part Nun

RS-232/485 to 8 RS-485 Channel Mux (Mercury Part Number: MUX8)
 Reader Interface Module with 2 doors; 4 inputs and 4 outputs; PoE+ Support. (Mercury Part #: MR62e)
 UHF GEN2 programmable - Impinj Monza 4QT chip (ETSI & FCC); Frequency: 13.56 MHz; Color: White - Customizable
 Schlage 13.56 MHz smart credential; keyfob; MIFARE Classic; 1K byte/8Kbit; minimum order quantity: 50 (Allegion
 Schlage 13.56 MHz smart credential; thin keyfob; MIFARE Classic; 1K byte/8Kbit; minimum order quantity: 50 (Allegion
 MIFARE Smart Card 2.5 k bit ISO Glossy White (Allegion Part Number: XF9520)
 MIFARE Contactless Smart Card 1k byte/8k bit ISO Glossy White (Allegion Part Number: XF9551)
 Proximity Keyfob; minimum order quantity: 50 (Allegion Part Number: XF7610)
 Schlage 13.56 MHz Smart credential ISO glossy white 4K byte/32k bit card (minimum order 100)
 Schlage MIFARE DESFire EV3 4K byte/32K bit with Magnetic Stripe ISO Glossy White (minimum order 100)
 Schlage Multi-technology credential; 125 kHz + 13.56 MHz; Proximity and Schlage MIFARE DESFire EV3 4K byte/32
 Schlage 13.56 MHz Smart credential Thin keyfob 4K byte/32k bit card (minimum order 100)
 Schlage Multi-technology credential; 125 kHz + 13.56 MHz; Proximity and Schlage MIFARE DESFire EV3 4K byte/32
 CONEKT™ High-security ISO-style composite card
 High-security clamshell-style card; MIFARE® DESFire® EV2
 CONEKT™ Credential High-security ISO-style composite card with HiCo (27500e) magnetic stripe
 DC1-1 Delta Clamshell Contactless Smartcard - ISO14443-compliant; clamshell-style contactless smartcard card with
 DC4-1 Delta Clamshell Contactless Smartcard - ISO14443-compliant; clamshell-style contactless smartcard card with
 DE2 MIFARE® DESFire® EV1 SMARTCARD; Frequency: 13.56 MHz; Read Range: Up to 2.5 inches (64 mm) (Farpointe
 DM1-3 Delta ISO Contactless Smartcard - ISO14443-compliant; contactless smartcard card with a 1K-byte memory
 DM1-3S Delta ISO Contactless Smartcard - ISO14443-compliant; contactless smartcard card with a 1K-byte memory
 DM4-3 Delta ISO Contactless Smartcard - ISO14443-compliant; contactless smartcard card with a 4K-byte memory
 DM4-3S Delta ISO Contactless Smartcard - ISO14443-compliant; contactless smartcard card with a 4K-byte memory
 PSC-1 Standard Light Proximity Card - Clamshell style proximity card backed by a lifetime warranty (Minimum order
 PSI-4 Image Technology Proximity Card - Thicker-format (0.046 inches (1.17 mm)) proximity card appropriate for c
 PSM-2P Multi Technology Proximity Card - ISO-style multi technology proximity card appropriate for dye sublimat
 PSM-2S Multi Technology Proximity Card - ISO-style multi technology style proximity card appropriate for dye sub
 CONEKT Credentials; 2.4-GHz Mobile supporting BLE-enabled smartphones; 25 Pack with QR Code
 High-security key fob-style tag; MIFARE® DESFire® EV2
 DK1-3 Delta Keyfob Contactless Smartcard Credential - ISO14443-compliant key tag-style contactless smartcard cr
 DK4-3 Delta Keyfob Contactless Smartcard Credential - ISO14443-compliant key tag-style contactless smartcard cr
 Model PDT-1 Proximity Disc Tag - Has an adhesive on one side that allows for the prox-enabling of a variety of nor
 PSK-3 Proximity Key Ring Tag - Small proximity tag designed to be carried on a key ring; includes a re-enforcing bra
 WRT-2+ Ranger Two Button Long Range Transmitter - 2-button clicker-type access credential; featuring both long
 Ranger® 433-MHz Long-Range Transmitters; 2-button; with 1K insert. (Farpointe Data Part Number: WRT-2+S1)
 Ranger® 433-MHz Long-Range Transmitters; 2-button; with 4K insert. (Farpointe Data Part Number: WRT-2+S4)
 Ranger® 433-MHz Long-Range Transmitters; Mini 2-button; no proximity insert. (Farpointe Data Part Number: WR
 WRT-2+ Ranger Two Button Long Range Transmitter - 2-button clicker-type access credential; featuring both long
 Ranger® 433-MHz Long-Range Transmitters; 4-button; with 1K insert. (Farpointe Data Part Number: WRT-4+S1)
 WRT-2+ Ranger Two Button Long Range Transmitter - 2-button clicker-type access credential; featuring both long
 WRT-4+ Ranger Four-Button Long Range Transmitter - 4-button clicker-type access credential; featuring both long
 COMPOSITE ICLASS/PROX; 16K/16; PROG; F-GLOSS; F-GLOSS; MATCHING ICLASS#; NO SLOT; NO PROX#
 ICLASS 2K/2 SE; PROG; F-GLOSS; B-GLOSS W/MAG; MATCH; NO SLOT; Minimum Order 100 (HID Part Number: 30I
 COMPOSITE ICLASS PROX SE 2K/2; PROG ICLASS/PROX; F-GLOSS; B-GLOSS; MATCH ICLASS#; NO SLOT; MATCH PR
 Configuration card used to adjust CSN output settings from 32 bit MSB to 56 bit LSB on iCLASS Standard; SE and SE
 DuoProx II Graphics Quality PVC; Proximity Access Card; w/ Magnetic Stripe; Minimum Order 100 (HID Part Numb
 iCLASS Contactless Smart Card; 2k bit with 2 application areas; Minimum Order 100 (HID Part Number: 2000PGGN

iCLASS Contactless Smart Card; 16k bit with 16 application areas; Minimum Order 100 (HID Part Number: 2002PGI
iCLASS Contactless Smart Card; 32k bit with 16k/16 + 16k/1 application areas; Minimum Order 100 (HID Part Num
iCLASS Key II Contactless Smart Key Fob 2k bit with 2 application areas; Minimum Order 100 (HID Part Number: 2C
iCLASS Clamshell Contactless Smart Card; 2k bit with 2 application areas; Minimum Order 100 (HID Part Number: 2
COMPOSITE ICLASS; 2K/2; PROG; F-GLOSS; F-GLOSS W/ MAG; MATCHING#; Minimum Order 100; (HID Part Numbr
HID ICLASS 2K/2; PROG; SE; F-GLOSS; B-GLOSS W/ BOTH VERT. & HORZ. SLOT INDICATORS; MATCH #; NO SLOT Mi
ICLASS 2K/2 SE; PROG; F-GLOSS; B-GLOSS; MATCH; VERT SLOT; Minimum Order 100 (HID Part Number: 3000PGGM
ICLASS 2K/2 SE; COMPOSITE; PROG; F-GLOSS; B-GLOSS; MATCHING; NO SLOT; Minimum Order 100 (HID Part Num
iCLASS SE Clamshell Card; 2k bits with 2 application areas; plain white vineyl with matte finish; HID logo on back; v
iCLASS + Prox Contactless Smart Card; 2k bits with 2 application areas; plain white with gloss finish on front; plain
iCLASS + Prox Contactless Smart Card; 2k bits with 2 application areas; plain white with gloss finish; no slot punch
COMPOSITE ICLASS PROX 2K/2; PROGRAMMED; F-GLOSS; B-GLOSS; MATCHING; VERT SLOT; MATCH 125K #
COMPOSITE ICLASS PROX SE 2K/2; PROG ICLASS/PROX; F-GLOSS; B-GLOSS; MATCH ICLASS#; NO SLOT; NO PROX #
iCLASS SE Contactless Smart Card; 2k bit with 2 application areas; Minimum Order 100 (HID Part Number: 3000PG
iCLASS SE Contactless Smart Card; 2k bit with 2 application areas; Avigilon Format; Avigilon logo on back; Order qu
iCLASS SE Contactless Smart Card; 2k bit with 2 application areas; Avigilon Format; Without Avigilon logo; Order qu
iCLASS SE Contactless Smart Card; 16k bit with 16 application areas; Minimum Order 100 (HID Part Number: 3002I
iCLASS SE Contactless Smart Card; 32k bit with 16k/16 + 16k/1 application areas; Minimum Order 100 (HID Part Ni
ISO CARD COMPOSITE UHF/ICLASS 32K; PROG; WHITE; UHF LASER MATCHING; 860-960 MHz Application areas 16
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 16K; PROG; F-GLOSS; B-GLOSS W/MAG; MATCHING #; NO S
iCLASS SR (note: SR instead of SE is correct for this card) Clamshell Contactless Smart Card; 2k bit with 2 applicatio
ISO CARD COMPOSITE UHF; PROG; WHITE; LASER MATCHING; 860-960 MHz; Minimum Order 100 (HID Part Numb
ISOProx II Graphics Quality PVC; Proximity Access Card; Minimum Order 100 (HID Part Number: 1386LGGMN)
HID MIFARE® DESFire® EV3 Card - Compatibility Profile
Configuration card which enables the use of the Mobile Configuration App used to adjust Bluetooth range settings
Configuration Card used to personalize and convert a Mobile-Ready reader to a Mobile-Enabled reader. (HID Part
ProxCard II Proximity Access Card (Clam Shell); Minimum Order 100 (HID Part Number: 1326LMSMV)
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 16 KB MEMORY; PROG.; F-GLOSS; B-GLOSS; MATCH. ICLASS
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 16 KB MEMORY; PROG.; F-GLOSS; B-GLOSS; SEQ. #. ICLASS #
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8K; SEOS OS LOADED; PROG.; F-GLOSS; B-GLOSS; W/MAG; M
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8K; PROG; F-GLOSS; B-AVIGILON; MATCHING #; NO SLOT; CI
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8 KB MEMORY; PROG.; F-GLOSS; B-GLOSS; MATCH. ICLASS #
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8K; PROG; F-GLOSS; B-GLOSS; MATCHING #; NO SLOT; CUST
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8 KB MEMORY; PROG.; F-GLOSS; B-GLOSS; NO ICLASS #; NO
COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8 KB MEMORY; PROG.; F-GLOSS; B-GLOSS; SEQ. ICLASS #; NI
SEOS CLAMSHELL 8K CARD; PROG. SEOS; F-MATT; B-HID LOGO; LASER MATCH SEOS#; Minimum Order 100 (HID P
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS; MATCH. ICLASS #; NO SLOT; NO PROX #; M
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS; NO ICLASS #; NO SLOT; NO PROX #; Minim
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS W/MAG; MATCH. ICLASS #; NO SLOT; MATC
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS W/MAG; MATCH. ICLASS #; NO SLOT; MATC
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS W/MAG; MATCH. ICLASS #; NO SLOT; MATC
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS/PROX F-GLOSS; B-GLOSS W/MAG; NO ICLASS #; NO SLOT; MAT
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS; MATCH. ICLASS #; NO SLOT; MATCH. PROX
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS; MATCH. ICLASS #; NO SLOT; NO PROX #; M
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS; NO ICLASS #; NO SLOT; SEQ. PROX #; Minir
COMPOSITE ICLASS SEOS PROX 16K; PROG. ICLASS; F-GLOSS; B-GLOSS; SEQ. ICLASS #; NO SLOT; NO PROX #; Minir
COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K; PROG. ICLASS ; F - GLOSS; B - GLOSS W/MAG; MA
COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K; PROG. ICLASS;NON PROGRAM PROX; F-GLOSS; B-

COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K; PROG. ICLASS;NON PROGRAM PROX; F-GLOSS; B-GLOSS; MATCH ICLASS #; Minimum Order 100 (HID Part Number: MC-0036)

COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K; PROG. ICLASS/PROX; F-GLOSS; B-GLOSS; MATCH ICLASS #; Minimum Order 100 (HID Part Number: MC-0036)

COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K; PROG. ICLASS/PROX; F-GLOSS; B-GLOSS; MATCH ICLASS #; Minimum Order 100 (HID Part Number: MC-0036)

COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K; ICLASS SIO PROGRAMMED; PROX HID FORMAT; F-GLOSS; B-GLOSS; MATCH ICLASS #; Minimum Order 100 (HID Part Number: MC-0036)

Service fee; per card; Elite Card Maintenance Fee (HID Part Number: MC-0036)

ICLASS SE KEYFOB 2K/2; PROG ICLASS; BLACK W/BLUE HID; MATCH ICLASS #; Minimum Order 100 (HID Part Number: MC-0036)

ICLASS SE KEYFOB 2K/2; PROG ICLASS; BLACK W/BLUE HID; MATCH ICLASS #; Available with Avigilon format; Stock ProxKey III Proximity Access Keyfob; Minimum Order 100 (HID Part Number: 1346LNSMN)

SEOS KEY FOB 8K; PROG SEOS; F-BLACK W/HID ARTWORK; B-BLACK; LASER MATCH SEOS #; (AVIGILON FORMAT - ICLASS SIO PROGRAMMED); Minimum Order 100 (HID Part Number: 1346LNSMN)

HID Origo Mobile Identities - User licenses - initial and renewal. Number of user licenses (maximum number of licenses per card is 100). Add-on order cost is per month. Number of user licenses (maximum number of licenses per card is 100). Add-on order cost is per month.

ADDON USER LICENSE HID ORIGO; MOBILE IDENTITIES

iCLASS SE Tag; Contactless Smart Tag ; 2k bit with 2 application areas; Black with HID Standard Artwork; Sequential MICROPROX TAG; PROG; GRAY; MATCH #; Minimum Order 100 (HID Part Number: 1391LGSMN)

ProxPass II Long Range Active Proximity Access Tag for Vehicle Access; Minimum Order 10 (HID Part Number: 1351LNSMN)

COMPOSITE HID DESFIRE EV3 8K; RANDOM UID; PROG SIO HIGH SECURITY; F-GLOSS; B-GLOSS; LASER MATCH #; N ICLASS 2K/2; SR; PROG ICLASS; F-GLOSS; B-GLOSS; MATCH LASER ICLASS #; VERT SLOT

Service fee per card for Corporate 1000 card format. (HID Part Number: MC-1000)

NON PROGRAMED 13.56 MHz NXP MIFARE® DESFire® EV2 2K chip - DESFire EV2 2K ISO Card (MOQ 200) - NO LOGO

NON PROGRAMED 13.56 MHz NXP MIFARE® DESFire® EV2 2K chip - DESFire EV2 2K Keyfob (MOQ 100) - NO LOGO

NON PROGRAMMED UHF GEN2 Self-destructing programable adhesive windshield tag (MOQ 100) Requires AC-STII

Sixteen Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with Seven AC-MER-CONT-2DR

Sixteen Door Mercury Dual Voltage Integrated Power System supporting one AC-MER-CONT-2DR with seven AC-MER-CONT-2DR

Two Door Mercury Single Voltage Integrated Power System supporting two AC-MER-CONT-1DR or one AC-MER-CONT-2DR

Two Door Mercury Dual Voltage Integrated Power System supporting two AC-MER-CONT-1DR or one AC-MER-CONT-2DR

Four Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with one AC-MER-CONT-2DR

Four Door Mercury Dual Voltage Integrated Power System supporting one AC-MER-CONT-2DR with one AC-MER-CONT-2DR

Eight Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with three AC-MER-CONT-2DR

Eight Door Mercury Dual Voltage Integrated Power System supporting one AC-MER-CONT-2DR with three AC-MER-CONT-2DR

The B100 Secondary Voltage Module provides a means to easily and economically add an additional voltage to an enclosure.

The C4 (4 Door) Lock Control Module adds four (4) fused outputs to a FPO power supply for “buffered” lock control.

The C8 (8 Door) Lock Control Module lock adds eight (8) fused outputs to a FPO power supply for “buffered” lock control.

Replacement Camlock and key (set of three) for LifeSafety Power enclosures; keyed alike (Lifesafety Power # Camlock)

The D8P (8 Out) Power Distribution Module provides 8 auxiliary power outputs; each one individually protected by a fuse.

Backplate; Standoffs & E1M size cabinet kit: Size: 12" x 14" x 4.5"; Weight: 9 lb. (LifeSafety Power Part Number: E1M)

LifeSafety Power E series enclosures are engineered to house FlexPower® power management boards in multiple configurations.

Locking battery enclosure with one 4" battery shelf. 20x16x4.5 enclosure with pre-installed lock set and tamper switch.

Backplate; Standoffs & E2M size cabinet kit: Size: 16" x 20" x 4.5"; Weight: 13 lb. (LifeSafety Power Part Number: E2M)

Locking battery enclosure with three 4" battery shelf. 24x20x4.5 enclosure with pre-installed lock set and tamper switch.

8 Door Mercury enclosure with removable backplate Battery space for 12V or 24V; 8Ah batteries is available with 16 Door Mercury enclosure with door mount & removable backplate. Battery space for 12V or 24V; 8Ah batteries

8 Door HID VertX enclosure with removable backplate *** Accomodates single voltage only *** Battery space for 12V or 24V

8 - 16 Door HID VertX enclosure with door mount & removable backplate *** Accomodates single or dual voltage

MCLASS multi-purpose enclosures offer maximum flexibility; functionality and savings to access system designers.

MCLASS multi-purpose enclosures offer maximum flexibility; functionality and savings to access system designers.

MCLASS multi-purpose enclosures offer maximum flexibility; functionality and savings to access system designers.

LifeSafety Power FLEXPPOWER E8M2 16 Door Mercury Security® MCLASS multi-purpose enclosures offer maximum

LifeSafety Power - FLEXPOWER EPLT-1M - Mercury Expansion Plate for MCLASS- Mercury/LSP board addition.

The F8 module provides 8 protected outputs; each output programmable to enable voltage on activation of the fire alarm. The F8P module provides 8 protected outputs; each output programmable to enable voltage on activation of the fire alarm.

The F150W-12/24VDC PS; Backplate; Standoffs; & E4M size cabinet kit: The FlexPower AC-LSP-FPO150 (FPO150-2D8E4M) is a 8 Door Access/Dual Voltage 150W PS/C ;12VDC@4A and 24VDC@4A System Features: One battery set supports a maximum of 8 Door Access/Single Voltage 150W PS/C ; 12VDC@12A or 24VDC@6A System Features: 80Ah charge capability; r LifeSafety Power; Mercury 8DR; ProWire; Tie Wrap Cable Management; Networked; 170W dual voltage; 120/230VAC Power supply board 150W; 12A/12V or 6A/24V | 12V secondary voltage power module. Adjustable 5-18V output @ 4A max

LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0; CU42E0 Power supply board 150W; 12A/12V or 6A/24V | AC Fault System Fault form C contacts may be triggered by low/no battery; 8 LifeSafety Power AC-LSP-FPO150-B100C8P2D8PE4M-T8-A ; Mercury ProWire Power Systems; 150W Dual Voltage; LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0; CU42E0 Power supply board 150W; 12A/12V or 6A/24V | Secondary voltage power supply; 5-18V adjustable @ 4A max; class 1 Power supply board 150W; 4A/12V or 4A/24V | Secondary voltage power supply; 5-18V adjustable @ 4A max; class 1

The FPO150 150W Power Supply Board is a high efficiency; off-line switchmode power supply-battery charger design for 16 Door Access/Dual Voltage 300W PS/C; 12VDC@12A and 24VDC@6A System Features: 80Ah charge capability; LifeSafety Power Mercury Unified Unified Power Systems; 400W Dual Voltage; 120 VAC; 16 Managed / 16 Auxiliary Power supply board 150W; 12A/12V or 6A/24V | Power supply board 250W; 20A/12V or 10A/24V | 16 auxiliary D Power supply board 150W; 12A/12V or 6A/24V | Power supply board 250W; 20A/12V or 10A/24V | 16 auxiliary D Power supply board 150W; 12A/12V or 6A/24V | Power supply board 250W; 20A/12V or 10A/24V | 16 auxiliary D LifeSafety Power; Mercury 16DR; ProWire; Tie Wrap Cable Management; Networked; 452W dual voltage; 120/230VAC LifeSafety Power; Mercury 16DR; ProWire; Tie Wrap Cable Management; Networked; 452W dual voltage; 120/230VAC LifeSafety Power ProWire 16 Door Panduit Unified Power wall mount dual voltage access power system; precision 150W power supply; 12A/12V or 6A/24V | 12V secondary voltage power module. Adjustable 5-18V output @ 4A max

The FPO250 250W Power Supply Board is a high efficiency; off-line switchmode power supply-battery charger design for 16 Door Access/Single Voltage 250W PS/C; 12VDC@20A or 24VDC@10A System Features: 80Ah charge capability LifeSafety Power Mercury Unified Power Systems; 250W Single Voltage; 120 VAC; for 8 Doors 250W power supply; 20A/12V or 10A/24V 12V secondary voltage power module. Adjustable 5-18V output @ 4A max

LifeSafety Power Mercury Unified Unified Power Systems; 250W NETWORKED / 12/24VDC / 8 Doors; 8 Managed / 16 Door Access/Dual Voltage 500W PS/C; 12VDC@20A and 24VDC@10A System Features: 80Ah charge capability LifeSafety Power; Mercury 24DR; ProWire; Tie Wrap Cable Management; Networked; 564W dual voltage; 120/230VAC LifeSafety Power MCLASS™ WIRED UNIFIED POWER SYSTEM; NETWORKED 500W / 12 & 24VDC / 16 Doors; 32 Max LifeSafety Power FPO250/250-5M8NLXE8M2/P16-A Mercury ProWire Power System; 500W Dual Voltage; 120VAC LifeSafety Power - Mercury Unified Power Systems - 500W Dual Voltage; 120 VAC

Mercury Unified Power System combine FlexPower modules alongside preview access control hardware in one compact form factor. The FPO75 75W Power Supply Board is a high efficiency; off-line switchmode power supply-battery charger design for LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0; CU42E0 One (1) 75W-12/24VDC PS; Backplate; Standoffs; & two (2) E2M size cabinets kit: The FlexPower FPO75-2E2M is a 4 Door Access/Single Voltage 75W PS/C; 12VDC@4A or 24VDC@2A System Features: 40Ah charge capability; micro 75W power supply; 6A/12V or 3A/24V | 12V secondary voltage power module. Adjustable 5-18V output @ 4A max

LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0; CU42E0 LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0; CU42E0 Power supply board 75W; 6A/12V or 3A/24V | Secondary voltage power supply; 5-18V adjustable @ 4A max; class 1

Mercury ProWire Power System combine FlexPower modules along preview access control hardware in one compact form factor. LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0; CU42E0 LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0; CU42E0 75W-12/24VDC PS; Backplate; Standoffs; & E1 size cabinet kit: The FlexPower FPO75-E1M is an offline switchmode

75W-12/24VDC PS; Backplate; Standoffs & E2 size cabinet kit: The FlexPower FPO75-E2M is an offline switchmode LifeSafety Power Mercury Unified Unified Power Systems; 225W Dual Voltage; 120 VAC; 8 Managed / 8 Auxiliary (8 Door Access/Dual Voltage 150W PS/C ; 12VDC@6A and 24VDC@3A System Features: 40Ah charge capability; m The M8 smart power controller communicates with the NL4 network module and provides eight (8) monitored an LifeSafety Power MSM-Enterprise; Multi-Site Power Manager for Access Installations; Server Application / Web Br The NL4 Network Communication Module communicates and controls power status over a local or wide area netw LifeSafety Power NETLINK™ NLX module is part of LifeSafety Power's Flex-Power® modular power management sy 16 Door Mercury Over Sized Enclosure (OSE) with door mount & removable backplate. Enclosure holds a total of 1 16 Door 12 or 24 VDC Mercury Over Sized Enclosure (OSE) with door mount & removable backplate. 150W power 16 Door Mercury Over Sized Enclosure (OSE) with removable backplate. Enclosure holds a total of 8 mercury pane 16 Door Dual Voltage Mercury Over Sized Enclosure (OSE) with removable backplate. 150W power supply for syst E5 enclosure size 8.5W x 11H x 3D with Mercury/LNL hole mount pattern Fits up to Mercury 1501 or Mr51e Contr 75W 12V/6A or 24V/3A UL listed 4DR Mercury rack mount; networked; 12/24V 8 class 2 power limited outputs fu 75W 12V/6A or 24V/3A UL listed 4DR Mercury rack mount; 12/24V 8 class 2 power limited outputs fused at 2.5A/ 75W 12V/6A or 24V/3A UL listed 4DR Mercury rack mount; networked 12/24V 8 managed class 2 power limited o 75W 12V/2A and 24V/2A UL listed Dual Voltage 12 & 24VDC 12 & 24VDC: 4DR Mercury rack mount; 4 class 2 pow 75W 12V/2A and 24V/2A UL listed Dual Voltage 12 & 24VDC 12 & 24VDC: 4DR Mercury rack mount; 4 class 2 pow 75W 12V/2A and 24V/2A UL listed Dual Voltage 12 & 24VDC 12 & 24VDC: 4DR Mercury rack mount; 8 class 2 pow 75W power supply; 6A/12V or 3A/24V;12V secondary voltage power module. Adjustable 5-18V output @ 4A max; RBE rackmount battery enclosure for 7-8Ah batteries; Standard 2U EIA; 19" rack mount chassis(LifeSafety Power | LifeSafety Power OneDrop™ SDU (Single Drop USB) adapter allows a single IP connection to be used in Mercury ; Power supply board 150W; 12A/12V or 6A/24V | Secondary voltage power supply; 5-18V adjustable @ 4A max; cl Power supply board 75W; 6A/12V or 3A/24V | Secondary voltage power supply; 5-18V adjustable @ 4A max; clas Eight Door Mercury Panduit ProWire Unified Power wall mount | Power supply board 150W; 4A/24V | Secondary Eight Door Mercury Panduit ProWire Unified Power wall mount | Power supply board 150W; 4A/24V | Secondary Sixteen Door Mercury Panduit ProWire Unified Power wall mount | Power supply board 150W; 12A/12V | Power Sixteen Door Mercury Panduit ProWire Unified Power wall mount | Power supply board 150W; 12A/12V | Power Sixteen Door Mercury Panduit ProWire Unified Power wall mount | Power supply board 150W; 12A/12V | Power Sixteen Door Mercury Panduit ProWire Unified Power wall mount | Power supply board 150W; 12A/12V | Power 6.5W x 6.5W x 3D small size enclosure suitable for 1 x Mercury LP1501 or 1 x Mercury MR62e ; IP67 rated; Includ One-time migration of field hardware data from a Mercury Security Hardware-based system of up to 1024 card re One-time migration of field hardware data from a Mercury Security Hardware-based system of up to 2048 card re One-time migration of field hardware data from a Mercury Security Hardware-based system of up to 256 card rea One-time migration of field hardware data from a Mercury Security Hardware-based system of up to 512 card rea One-time migration of Identity data from a single LDAP-based data source into Avigilon ACM. Migrated data will ir One-time migration of Identity data from a single Oracle data source into Avigilon ACM. Migrated data will include One-time migration of Identity data from a single SQL data source into Avigilon ACM. Migrated data will include d One-time migration and filtering of Identity data from a single LDAP-based data source into Avigilon ACM. Migrate One-time migration and filtering of Identity data from a single Oracle data source into Avigilon ACM. Migrated dat One-time migration and filtering of Identity data from a single SQL data source into Avigilon ACM. Migrated data v On-going one-way inbound synchronization of Identity data from a single AzureAD data source into Avigilon ACM. I On-going one-way inbound synchronization of Identity data from a single Generic AD data source into Avigilon ACM Hourly Rate to configure on-going one-way inbound synchronization of Identity data from a single Custom Third-P On-going one-way inbound synchronization of Identity data from a single LDAP data source into Avigilon ACM. Imp On-going one-way inbound synchronization of Identity data from a single Oracle data source into Avigilon ACM. Im On-going one-way inbound synchronization of Identity data from a single SQL data source into Avigilon ACM. Impor UHF antenna for SPECTRE scalable readers (no cable included) - Circular Polarization - Upper Band 902-928 MHz -

UHF GEN2 Self-destroying programmed customized adhesive label - Secure & encrypted EPC mode - 100 x 30 mm
 SLA - SPECTRE UHF Long Range & Scalable reader with 1 integrated antenna - Upper Band 902-928 MHz - EPC1 GE
 SLA - SPECTRE Access UHF scalable reader - USA Upper Band 902 to 928MHz - RS485 - OSDP - USB Cable & ULTRYS
 UHF SPECTRE & SPECTRE nano reader orientable wall mounting kit (Stid hardware sold separately)
 UHF SPECTRE & SPECTRE nano reader orientable pole mounting kit (Stid hardware sold separately)
 UHF SPECTRE & SPECTRE nano reader orientable wall + pole mounting kit (Stid hardware sold separately)
 Schlage (formerly aptiQ™) Multi-Technology Keypad - Single Gang Reader - OSDP (Allegion Part Number: MTK15-4
 Schlage (formerly aptiQ™) Multi-Technology – Mullion Reader - OSDP (Allegion Part Number: MT11-485)
 Schlage (formerly aptiQ™) Multi-Technology - Single Gang Reader - OSDP (Allegion Part Number: MT15-485)
 Wireless Portable Reader (with Multi-Technology Reader Module) Handheld; battery-operated unit with Multi-Tec
 Outdoor Wireless Reader Interface Compatible with Wiegand or Magnetic Stripe Interface. Includes Weatherproof
 Schlage (formerly aptiQ™) 13.56 MHz Smart - Mini Mullion Reader (Allegion Part Number: SM10)
 Schlage (formerly aptiQ™) Multi-Technology – Mullion Reader (Allegion Part Number: MT11)
 Mobile Enabled Multi-Technology Reader – Mullion Mount - Dimensions: 5.91" x 1.72" x 0.81". Power required: 5-
 Mobile Enabled Multi-Technology Reader – Wall Mount - Dimensions: 5.1" x 3.25" x 0.76". Power required: 5-24 V
 Mobile Enabled Multi-Technology Reader – Wall Mount with Keypad - Dimensions: 5.1" x 3.25" x 0.76". Power rec
 CONEKT OSDP; Long Range; Mullien and Single-gang Mount; Mobile-Ready Contactless Smartcard Readers (2.4-GHz
 CONEKT Wiegand; Long Range; Mullien and Single-gang Mount; Mobile-Ready Contactless Smartcard Readers (2.4
 Delta6.2 OSDP Contactless Smartcard Reader and Keypad - The model Delta6.2 is designed to be mounted directly
 Delta 6.2 OSDP Contactless Smartcard Reader and Keypad - The model Delta 6.2 is designed to be mounted direct
 Delta3 Contactless Smartcard Reader - With a compact design the model Delta3 may be mounted to metal door o
 Delta5 OSDP Contactless Smartcard Reader - With a thin profile the model Delta5 may be mounted to a standard l
 Delta5 Contactless Smartcard Reader - With a thin profile the model Delta5 may be mounted to a standard North
 Delta5.3 Contactless Smartcard Reader - With distinctive contemporary styling the model Delta5.3 lends itself to r
 Delta6.4 Contactless Smartcard Reader and Keypad - The model Delta6.4 is designed to be mounted directly to a s
 Gibraltar Proximity Reader; Bullet-resistant reader designed to be mounted to mullion; door or window frames.(F
 Gibraltar Proximity Reader; Bullet-resistant reader designed to mount to standard North American single-gang wa
 Guardian Proximity Reader; Vandal-resistant reader designed to mount to a metal door and window frame.(Farpo
 Guardian Proximity Reader; Vandal-resistant reader designed to mount to a standard North American single-gang
 Guardian Proximity Reader; Vandal-resistant reader designed to mount to a standard North American double-gan
 P-300 Cascade Proximity Reader - Designed to be mounted to metal door and window frames (Stock Item) (Farpoi
 Mullion mount reader; supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (Farpointe Data
 P-500 Alps Proximity Reader - Designed to be mounted to a standard North American single-gang wall switch box
 Single-gang mount reader; supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (Farpointe I
 P-640 Patagonia Proximity Reader and Keypad - Designed to be mounted directly to standard North American size
 Keypad + reader; single-gang mount; supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (f
 P-640 Patagonia Proximity Reader and Keypad - Designed to be mounted directly to standard North American size
 P-710 Andes Proximity Reader - Intended for applications calling for heightened levels of convenience; such as par
 Parking; single-gang mount reader; supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (Fa
 P-900 Proximity Reader - A high performance design; it is classified as a long range reader; and is capable of delive
 Single-gang/double-gang; standard parking bollard mount reader; supports Farpointe + certain HID® and AWID® 1
 EuroMount Proximity Reader; designed to be mounted to a standard European-sized (60 mm) wall switch box. (N
 Mullion Mount Keypad reader + proximity; designed to be mounted to window or door frames(Farpointe Data Pai
 MCR-50 Proximity Reader - Supports Farpointe + certain Indala® ASP Advantage Series Proximity formats + certain
 EM-64-H OSDP Enabled; Secure Communication Protocol; (125kHz HID & Pyramid Proximity Technologies Support
 P-300-H Cascade Proximity Reader; OSDP Enabled; Secure Communication Protocol (125kHz HID Proximity Techno
 P-500-H Alps Proximity Reader; OSDP Enabled; Secure Communication Protocol (125kHz HID Proximity Technolog

Long-range mullion mount mobile and proximity credential reader and keypad
 Long-range mullion mount mobile and proximity credential reader and keypad
 Long-range single-gang wall switch box mount mobile and proximity credential reader and keypad
 Long-range single-gang wall switch box mount mobile and proximity credential reader and keypad
 EM-64-H Diamondback Proximity Reader and Keypad ; Ship Kit
 Long-Range Receiver; designed to output Transmitter data from buttons 1 and 2 over two separate Wiegand outp
 WRR-44 Ranger Receiver - Long range radio-type receiver; features a Transmitter receive range of up to 200-feet (
 GASKET PACK; IP65; R10 SIZE; ICLASS SE; PACK OF 10 GASKETS (HID Part Number: IP65GSKT-R10)
 GASKET PACK; IP65; R15 SIZE; ICLASS SE; PACK OF 10 GASKETS (HID Part Number: IP65GSKT-R15)
 GASKET PACK; IP65; R40 SIZE; ICLASS SE; PACK OF 10 GASKETS (HID Part Number: IP65GSKT-R40)
 GASKET PACK; IP65; RK40 SIZE; ICLASS SE; PACK OF 10 GASKETS (HID Part Number: IP65GSKT-RK40)
 RDR; R40; ICLASS; SE E; LF OFF; HF STD/SIO/SEOS; 485HDX; PIG; BLK; STD-1; A/V OFF; OSDP V2; OPT TAMP; OPEN
 RDR; RP10; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS; 485HDX; TERM; BLK; STD-1; A/V OFF; OSDP V1; OPN COL
 RDR; RP15; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS; 485HDX; PIG; BLK; STD-1; A/V OFF; OSDP V1; OPN COL; C
 RDR; RP15; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS; 485HDX; TERM; BLK; STD-1; A/V OFF; OSDP V1; OPN COL
 RDR; RPK40; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS; 485HDX; PIG; BLK; STD-1; A/V OFF; OSDP V1; OPN COL;
 SIGNO 40 PIV;BLK/SLVR;PIG;CRD PFL CSTM;FIPS75BIT;BLE:OFF;OSDP;V1;CSN SUPR;EM:32-B;LED:OFF;FLSH:OFF;NC
 SIGNO 40K PIV;BLK/SLVR;PIG;CRD PFL CSTM;FIPS75BIT;BLE:OFF;OSDP;V1;CSN SUPR;EACH;ASCII;NOPAR;LEN:13;FC
 R10 Mini-mullion reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Standard; I
 RDR; R10; ICLASS; SE E; LF OFF; HF STD/SIO/SEOS/MA; OSDP; PIG; BLK; A/V OFF; OPT TAMP; OPEN COLL; CSN 32-B
 R10 Mini-mullion reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Standard; I
 RDR; R10; ICLASS; SE E; LF OFF; HF STD/SIO/SEOS/MA; OSDP; TERM; BLK; A/V OFF; OPT TAMP; OPEN COLL; CSN 32
 R15 Mullion reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Standard; MIFA
 RDR; R15; ICLASS; SE E; LF OFF; HF STD/SIO/SEOS/MA; OSDP; PIG; BLK; A/V OFF; OPT TAMP; OPEN COLL; CSN 32-B
 R15 Mullion reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Standard; MIFA
 RDR; R15; ICLASS; SE E; LF OFF; HF STD/SIO/SEOS/MA; OSDP; TERM; BLK; A/V OFF; OPT TAMP; OPEN COLL; CSN 32
 R40 Standard wall switch reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Sta
 RDR; R40; ICLASS; SE E; LF OFF; HF STD/SIO/SEOS/MA; OSDP; PIG; BLK; A/V OFF; OPT TAMP; OPEN COLL; CSN 32-B
 RDR; R40; ICLASS; SE E; LF OFF; HF STD/SIO/SEOS/MA; OSDP; TERM; BLK; A/V OFF; OPT TAMP; OPEN COLL; CSN 32
 R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and N
 R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Terminal Strip
 R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and N
 R10 Mini-mullion reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Standar
 R10 Mini-mullion reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Standar
 R15 Mullion reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Standard; M
 R15 Mullion reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR; Standard; M
 R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Pigtail
 R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Eli
 R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Eli
 R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Termir
 R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Eli
 R40 Standard wall switch reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR;
 R40 Standard wall switch reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos; SE; SR;
 RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Blue
 R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire
 R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire
 R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE I

RDR; R40; ICLASS; SE E; LF OFF; HF SEOS; WIEG; PIG; BLK; STD-2; LED RED; FLSH GRN; BZR ON; VAR BIT OUTPUT PE
R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos; SE; SR; MIFARE Classic (SIO); MIFA
R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos; SE; SR; Standard; MIFARE Classic (S
RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; iCLASS Seos; SE; SR; Standard; MIFARE Cl
RDR; RK40; ICLASS; SE E; LF OFF; HF SEOS; WIEG; PIG; BLK; STD-2; LED RED; FLSH GRN; BZR ON; VAR BIT OUTPUT P
RP40 Standard wall switch reader; Wiegand; HID Prox; AWID and EM4102 (32 bits); iCLASS Seos; SE; SR; Standard;
RP40 Standard wall switch reader; Wiegand; HID Prox; AWID and EM4102 (32 bits); iCLASS Seos; SE; SR; Standard;
RPK40 Standard wall switch reader with keypad input; Wiegand; HID Prox; AWID and EM4102 (32 bits); iCLASS Sec
MaxiProx Long Range Proximity Reader (HID # 5375AGN00)
RDR; RP10; MULTICLASS; SE E; LF CST; HF STD/SIO/SEOS; SE INDALA MODULE; WIEG; PIG; BLK; STD-1; LED RED; FL
RDR; RP15; MULTICLASS; SE E; LF CST; HF STD/SIO/SEOS; SE INDALA MODULE; WIEG; PIG; BLK; STD-1; LED RED; FL
RDR; RP40; MULTICLASS; SE E; LF CST; HF STD/SIO/SEOS; SE INDALA MODULE; WIEG; PIG; BLK; STD-1; LED RED; FL
R10 Mini-mullion reader; OSDP; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iC
RDR; RP10; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; 485HDX; A/V OFF; OSDP V1; PIG; BLK; OPT TAMP; O
R10 Mini-mullion reader; OSDP; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iC
RDR; RP10; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; OSDP; TERM; BLK; LED RED; FLSH GRN; BZR ON; OPT
R15 Mullion reader; OSDP; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS
RDR; RP15; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; OSDP; PIG; BLK; A/V OFF; OPT TAMP; OPEN COLL; C
R15 Mullion reader; OSDP; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS
R40 Standard wall switch reader; OSDP; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth S
RDR; RP40; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; OSDP; PIG; BLK; A/V OFF; OSDP V1; OPT TAMP; OPE
R40 Standard wall switch reader; OSDP; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth S
RDR; RP40; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; OSDP; TERM; BLK; A/V OFF; OSDP V1; OPT TAMP; O
RDR; RP10; MULTICLASS; SE E; LF FSK ONLY; HF SEOS; WIEG; PIG; BLK; STD-2; LED RED; FLSH GRN; BZR ON; VAR BI
RDR; RP10; MULTICLASS; SE E; LF FSK ONLY; HF SEOS; WIEG; TERM; BLK; STD-2; LED RED; FLSH GRN; BZR ON; VAR
R10 Mini-mullion reader; Wiegand; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smar
RDR; RP10; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; WIEG; PIG; BLK; LED RED; FLSH GRN; BZR ON; OPT T
R10 Mini-mullion reader; Wiegand; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smar
RDR; RP10; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; WIEG; TERM; BLK; LED RED; FLSH GRN; BZR ON; OPT
RDR; RP15; MULTICLASS; SE E; LF STD; HF SEOS/MA; WIEG; PIG; BLK; STD-2. LED RED; FLSH GRN; BZR ON; OPT TAN
R15 Mullion reader; Wiegand; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCL
RDR; RP15; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; WIEG; PIG; BLK; LED RED; FLSH GRN; BZR ON; OPT T
R15 Mullion reader; Wiegand; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCL
RDR; RP15; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; WIEG; TERM; BLK; LED RED; FLSH GRN; BZR ON; OPT
RDR; RP40; MULTICLASS; SE E; LF FSK ONLY; HF SEOS; WIEG; PIG; BLK; STD-2; LED RED; FLSH GRN; BZR ON; VAR BI
RDR; RP40; MULTICLASS; SE E; LF FSK ONLY; HF SEOS; WIEG; TERM; BLK; STD-2; LED RED; FLSH GRN; BZR ON; VAR
RDR; RP40; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; WIEG; PIG; BLK; LED RED; FLSH GRN; BZR ON; OPT T
R40 Standard wall switch reader; Wiegand; HID Prox; AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetoo
RDR; RP40; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS/MA; WIEG; TERM; BLK; LED RED; FLSH GRN; BZR ON; OPT
RDR; RP15; MULTICLASS; SE REV E; STD PROX; STD; WIEGAND; TERM; BLK; STD 1 SECURITY; LED RED; FLASH GRN;
RDR; RP40; MULTICLASS; SE REV E; STD PROX; STD; WIEGAND; TERM; BLK; STD 1 SECURITY; LED RED; FLASH GRN;
RDR; RPK40; MULTICLASS; SE REV E; KPD; STD PROX; STD; WIEGAND; TERM; BLK; STD 1 SECURITY; LED RED; FLASH
RDR; RP10; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS; WIEG; PIG; BLK; STD-1; ELITE; LED RED; FLSH GRN; BZR O
RDR; RP15; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS; WIEG; PIG; BLK; ELITE KEYS; LED RED; FLSH GRN; BZR ON
RDR; RP40; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS; WIEG; PIG; BLK; ELITE KEYS; LED RED; FLSH GRN; BZR ON
RDR; RPK40; MULTICLASS; SE E; LF STD; HF STD/SIO/SEOS; WIEG; PIG; BLK; ELITE KEYS; LED RED; FLSH GRN; BZR O
MiniProx Proximity Reader (HID # 5365EKP00)

5427 CK standard omnikey USB Enrollment reader; iCLASS Seos®; HID Prox®; iCLASS SE®; MIFARE Classic® and MIF ProxPro Proximity Reader (HID # 5355AGN00)
ProxPro Proximity Reader with Keypad (HID # 5355AGK00)
ProxPro II Proximity Reader (HID # 5455BKN00)
ThinLine II Switch Plate Proximity Reader (HID # 5395CK100)
RDR; U90; ICLASS; SE REV E; NO PROX; UHF; 865-868 MHZ; STD; WIEGAND; TERM; BK; STD 1 SECURITY(HID Part N
RDR; U90; ICLASS; SE REV E; NO PROX; UHF; 902-928 MHZ; STD; WIEGAND; TERM; BK; STD 1 SECURITY
Signo20K; Mullion w/Keypad; 13.56mHz &125kHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; Standard Profile; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo20K; Mullion w/Keypad; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; 13.56mHz Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; Smart Profile; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo20K; Mullion w/Keypad; 13.56mHz Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY STANDARD CREDEI
Signo20K; Mullion w/Keypad; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY SEOS CREDENTIAL
Signo20K; Mullion w/Keypad; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY SMART CREDENTIA
SIGNO 20K;BLK/SLVR;PIG;CRD PFL T3-CSTM;MA ENB;MOBA9Y7;BLE:ON;WIEG;CSN SUPR;EACH;4-B MSG;NOPAR;LI
Signo20K; Mullion w/Keypad; 13.56mHz &125kHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; Standard Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo20K; Mullion w/Keypad; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo20K; Mullion w/Keypad; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; 13.56mHz Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; Smart Profile; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo20K; Mullion w/Keypad; 13.56mHz Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20K; Mullion w/Keypad; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY STANDARD CREDI
Signo20K; Mullion w/Keypad; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY SEOS CREDENTI
Signo20K; Mullion w/Keypad; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY SMART CREDEN
Signo20; Mullion; 13.56mHz &125kHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20; Mullion; Standard Profile; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo20; Mullion; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20; Mullion; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20; Mullion; 13.56mHz Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20; Mullion; Smart Profile; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo20; Mullion; 13.56mHz Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo20; Mullion; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY STANDARD CREDENTIAL PROFI
Signo20; Mullion; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY SEOS CREDENTIAL PROFILE OP
Signo20; Mullion; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY SMART CREDENTIAL PROFILE C
SIGNO 20;BLK/SLVR;PIG;CRD PFL T3-CSTM;MA ENB;MOBA9Y7;BLE:ON;WIEG;CSN SUPR;EM:32-B;MAP1:DF;ICE175
Signo20; Mullion; 13.56mHz &125kHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20; Mullion; Standard Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo20; Mullion; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20; Mullion; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo20; Mullion; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20; Mullion; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo20; Mullion; 13.56mHz Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE

Signo20; Mullion; Smart Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo20; Mullion; 13.56mHz Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo20; Mullion; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY STANDARD CREDENTIAL PRO
Signo20; Mullion; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY SEOS CREDENTIAL PROFILE (C
Signo20; Mullion; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY SMART CREDENTIAL PROFIL
SIGNO 20;BLK/SLVR;TERM;CRD PFL T3-CSTM;MA ENB;MOBA9Y7;BLE:ON;WIEG;CSN SUPR;EM:32-B;MAP1:DF;ICE1
Signo40K; Wall mount w/Keypad; 13.56mHz &125kHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; Standard Profile; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo40K; Wall mount w/Keypad; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; 13.56mHz Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; Smart Profile; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo40K; Wall mount w/Keypad; 13.56mHz Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY STANDARD CRI
Signo40K; Wall mount w/Keypad; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY SEOS CREDENT
Signo40K; Wall mount w/Keypad; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY SMART CREDEI
Signo40K; Wall mount w/Keypad; 13.56mHz &125kHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; Standard Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo40K; Wall mount w/Keypad; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo40K; Wall mount w/Keypad; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; 13.56mHz Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; Smart Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo40K; Wall mount w/Keypad; 13.56mHz Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40K; Wall mount w/Keypad; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY STANDARD (C
Signo40K; Wall mount w/Keypad; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY SEOS CREDE
Signo40K; Wall mount w/Keypad; 13.56mHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY SMART CREI
Signo40; Wall mount; 13.56mHz &125kHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40; Wall mount; Standard Profile; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo40; Wall mount; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40; Wall mount; Seos Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40; Wall mount; 13.56mHz Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40; Wall mount; Smart Profile; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; Avigilon Logo
Signo40; Wall mount; 13.56mHz Profile ; OSDP/Wiegand; Pigtail; Mobile Ready; BLE
Signo40; Wall mount; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY STANDARD CREDENTIAL PF
Signo40; Wall mount; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY SEOS CREDENTIAL PROFILE
Signo40; Wall mount; 13.56mHz; OSDP/Wiegand; Pigtail; Mobile Ready; BLE; PRIORITY SMART CREDENTIAL PROFIL
SIGNO 40;BLK/SLVR;PIG;CRD PFL T3-CSTM;MA ENB;MOBA9Y7;BLE:ON;WIEG;CSN SUPR;EM:32-B;MAP1:DF;ICE175
Signo40; Wall mount; 13.56mHz &125kHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40; Wall mount; Standard Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo40; Wall mount; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40; Wall mount; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo40; Wall mount; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40; Wall mount; Seos Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40; Wall mount; 13.56mHz Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE
Signo40; Wall mount; Smart Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE; Avigilon Logo
Signo40; Wall mount; 13.56mHz Profile ; OSDP/Wiegand; Terminal; Mobile Ready; BLE

Signo40; Wall mount; 13.56MHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY STANDARD CREDENTIAL
 Signo40; Wall mount; 13.56MHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY SEOS CREDENTIAL PROF
 Signo40; Wall mount; 13.56MHz; OSDP/Wiegand; Terminal; Mobile Ready; BLE; PRIORITY SMART CREDENTIAL PR
 SIGNO 40;BLK/SLVR;TERM;CRD PFL T3-CSTM;MA ENB;MOBA9Y7;BLE:ON;WIEG;CSN SUPR;EM:32-B;MAP1:DF;ICE1
 R10 Mini-mullion spacer; black 0.5" with metal plate
 R15 Mullion spacer; black 0.5" with metal plate
 R40 Standard wall switch; black 0.5" with metal plate
 RK40 Standard wall switch with keypad; black 0.5" with metal plate
 R40 Standard wall switch; black 1.0" with metal plate
 HID SIGNO 20 SERIES; 0.5 INCH SPACER; BLACK
 HID SIGNO 40 SERIES; 0.5 INCH SPACER; BLACK
 R40/RP40 ICLASS/MULTICLASS; SE RDR BLE OSDP UPGRADE KIT; 1 BLE OSDP MODULE; 1 METALIC BACKPLATE STIK
 Programming Kit for Bluetooth®/Ultralight® C/MIFARE® Classic & Classic EV1/MIFARE Plus®/DESFire® EV2 & EV3/1
 SE8 - 125 kHz EM + HID module for Architect Blue reader - Standard reader black - 125 kHz EM + HID module. 125
 UHF EPC1 Gen2 Enrollment Kit SWEDGE: ARC UHF desktop reader - ETSI - USB (cable included) + SWEDGE Softwar
 UHF EPC1 Gen2 Enrollment Kit SWEDGE: ARC UHF desktop reader - FCC - USB (cable included) + SWEDGE Softwar
 ARCS-H/BT - Architect® Blue Desktop reader/enroller - Secure storage EAL5+ - Secure Read only - USB + WEDGE w
 ARCS-H/BT - Architect® Blue Desktop reader/enroller - Secure storage EAL5+ - Secure Read only - USB + WEDGE w
 Architect Series Programming Kit + Fingerprint module
 SE8M - 125 kHz Multi-technology module for Architect Blue reader - Standard reader black - 125 kHz Multi-techno
 SE9 Architect® Blue QR Code / Barcode module - QR and Barcode module for Standard reader black
 NON PROGRAMED ARC1S/BT - Architect® One Blue Mullion reader - Secure storage EAL5+ - Secure Read only - TTI
 NON PROGRAMED ARC1S/BT - Architect® One Blue Mullion reader - OSDP™ v1 & v2 secure protocol - Secure stor
 NON PROGRAMED ARCS-A/BT - Architect® Blue Upgradable Standard reader black - Wiegand Interface- Secure stc
 NON PROGRAMED ARCS-B/BT - Architect® Blue Upgradable Keypad reader black - Wiegand Interface - Secure stor
 Bluetooth Standard Reader black with touchscreen - Wiegand 26 bits (No logo on cover by default)
 NON PROGRAMED ARCS-iM/BT - Architect® Blue Hybrid 125 kHz Multi-technology + 13.56 MHz + Bluetooth® Upg
 NON PROGRAMED ARCS-JM/BT - Architect® Blue Hybrid 125 kHz Multi-technology + 13.56 MHz + Bluetooth® Upg
 ARCS-D/BT - 13.56 MHz + Bluetooth® biometric reader
 NON PROGRAMED ARCS-A/BT - Architect® Blue Upgradable Standard reader - OSDP™ v1 & v2 secure protocol - Se
 NON PROGRAMED ARCS-AQ/BT - Architect® Blue Upgradable QR Code; Bluetooth® & RFID reader - OSDP™ v1 & v
 NON PROGRAMED ARCS-B/BT - Architect® Blue Upgradable Keypad reader - OSDP™ v1 & v2 secure protocol - Seci
 NON PROGRAMED ARCS-BQ/BT Architect® Blue Upgradable QR Code; Bluetooth® & RFID Keypad reader - OSDP™
 NON PROGRAMED ARCS-C/BT - Architect® Blue Upgradable Touchscreen reader - OSDP™ v1 & v2 secure protocol
 Metal mounting plate for Architect® bio readers-RFID&Keypad versions
 SNA - SPECTRE nano UHF - USA Upper Band 902-928 MHz- USB cable & ULTRYS software included
 Biometric module - Black
 Stackable spacer with cable passage for Architect® Blue reader - Black
 Stackable spacer with cable passage for Architect® One Blue mullion reader - Black
 3 m / 4.9 ft UHF SPECTRE antenna cable - TNC Reverse
 VIRDI fingerprint smart card reader with live fingerprint detection embedded. Supports fingerprint; HID iClass Carc
 Reader bundle including AC-VT-READ-BIO-RFID-AC2000IC and power supply with type C plug for Europe
 Reader bundle including AC-VT-READ-BIO-RFID-AC2000IC and power supply with type B plug for North America
 Reader bundle including AC-VT-READ-BIO-RFID-AC2000IC and power supply with type G plug for United Kingdom
 VIRDI fingerprint smart card reader with live fingerprint detection embedded. Supports fingerprint; HID prox Card;
 Reader bundle including AC-VT-READ-BIO-RFID-AC2000Prox and power supply with type C plug for Europe
 Reader bundle including AC-VT-READ-BIO-RFID-AC2000Prox and power supply with type B plug for North America

Reader bundle including AC-VT-READ-BIO-RFID-AC2000Prox and power supply with type G plug for United Kingdom
 ViRDI fingerprint smart card reader with live fingerprint detection embedded. Supports fingerprint; Mifare 13.56M
 Reader bundle including AC-VT-READ-BIO-RFID-AC2000SC and power supply with type C plug for Europe
 Reader bundle including AC-VT-READ-BIO-RFID-AC2000SC and power supply with type B plug for North America
 Reader bundle including AC-VT-READ-BIO-RFID-AC2000SC and power supply with type G plug for United Kingdom
 ViRDI Fingerprint and card enrollment reader with touchscreen keypad; live fingerprint detection embedded; sup
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000IC and power supply with type C plug for Europe
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000IC and power supply with type B plug for North America
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000IC and power supply with type G plug for United Kingdom
 ViRDI Fingerprint and card enrollment reader with touchscreen keypad; live fingerprint detection embedded; sup
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000Prox and power supply with type C plug for Europe
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000Prox and power supply with type B plug for North America
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000Prox and power supply with type G plug for United Kingdom
 ViRDI Fingerprint and card enrollment reader with touchscreen keypad; live fingerprint detection embedded; sup
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000SC-BLK and power supply with type C plug for Europe
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000SC-BLK and power supply with type B plug for North America
 Reader bundle including AC-VT-READ-BIO-RFID-AC5000SC-BLK and power supply with type G plug for United Kingdom
 ViRDI Fingerprint and card enrollment USB reader; live fingerprint detection embedded; Fingerprint Platen Area: 16
 ViRDI Fingerprint and card enrollment reader; live fingerprint detection embedded; supports Mifare 13.56Mhz Car
 ASSA ABLOY SARGENT Cylindrical Lever Lock Latch; 2-3/8" Backset; Satin Stainless Steel; For 10-Line Cylindrical Lev
 Allegion Schlage 12.0" x 3.5" x .075" Decorative Plate (no Screws necessary) - (Under Lock)
 ASSA ABLOY Aperio Programming Application Tool Kit APA-10-PC; Includes USB Flash Drive; Programming Applic
 ASSA ABLOY Aperio® hubs are certified for use with the ASSA ABLOY external (omnidirectional) antenna EXT-10-AI
 ASSA ABLOY - USB Radio Dongle(ASSA ABLOY Part Number: APD-10-USB)
 Omni-Directional Remote Indoor/Outdoor Antenna Module. Includes Antenna; 15' Coax; Coax Whip. For indoor use
 Bi-Directional Remote Indoor Antenna Module. Includes Antenna; 15' Coax; Coax Whip. For indoor use with PIM40
 Directional remote indoor/outdoor antenna module with 6dB Gain 1. Includes Antenna; 15' Coax; Coax Whip; Arti
 Antenna Grounding Kit (for outdoor mounting). Could be used with ANT400-REM-I/O; ANT400-REM-I/O+6DB; AN
 Electronic Lock Communication Module Kit
 Schlage COM400P Communication Module Kit; Satin chrome
 Schlage COM400P Communication Module Kit; Aged bronze
 GWE — ENGAGE Gateway with RS-485 & IP (PoE) connectivity. Supports up to 10 ENGAGE enabled devices with M
 Panel Interface Board (supports 2 doors)(Allegion Part Number: PIB300-2D)
 900 MHz Panel Interface Module for 16 door intelligent controller (AC-MER-CONT-LP1501 Sold Separately) for AD
 900 MHz Panel Interface Module for 16 or 64 door intelligent controller (AC-MER-CONT-LP1501; AC-MER-CONT-LI
 Panel Interface Module (supports 2 doors) Wiegand (Data1/Data2) or magnetic stripe (Clock & Data) output. Inclu
 Relay Board (for PIB300-2D or PIM400-TD2)(Allegion Part Number: RLBD)
 Wireless Portable Reader with keypad (with Multi-Technology Reader Module) Handheld; battery operated unit w
 AD-400 Eight (8) battery conversion kit in grey (Allegion Schlage Part #: 8B-626).
 Communication Module Kit for AD-300 Classroom/Storeroom (70) function. Compatible with Cylindrical; Mortise; M
 Wireless AD-400 Communication Kit Module Cover with Indicator
 AD-400 Smart Technology iClass compatible reader module in grey (Allegion Part #: SI-626).
 AD-400 Smart Technology iClass compatible reader + keypad module in grey (Allegion Part #: SIK-626).
 Wireless Test Kit; Pre-Installed Test Kit; Complete with WPR400-DT; PIM400-TD2; 593PI; Power Supply; Charger; C
 Schlage USB and 2-pin Android cable for Schlage Utility Software (SUS) mobile app for Android devices
 AD-300 Hardwired Communication Kit (Cover with Indicator Lens; RS485 Communication PCB) Classroom/Storero
 Upgrades NDE80 Product to NDEB; NDEB Inside Escutcheon Assembly (with Main PCBA)

--	--	--	--	--	--	--

ality | MT - Multi-Technology | RHO - Rhodes Handle | 626 - Satin Chrome Finis | J - Less Full Size Interchangeak

| MT - Multi-Technology | RHO - Rhodes Handle | 626 - Satin Chrome Finis | J - Less Full Size Interchangeable C
| MT - Multi-Technology | RHO - Rhodes Handle | 626 - Satin Chrome Finis | J - Less Full Size Interchangeable C
MT - Multi-Technology | RHO - Rhodes Handle | 626 - Satin Chrome Finis | J - Less Full Size Interchangeable Co

ng Information form with ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/d>

; OSDP TAMP ENBLD; TEST KEYS; POLL=75MS; A/V OFF; KPF; ASCII; BFFRD 1 KEY; FIPS 200-BIT; IPM OFF; UART (3ZR ON; OPT TAMP; OPEN COLL; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; FIPS 64-BIT REVERSE BCD; IPM OFF; U/ 3ZR ON; OPT TAMP; OPEN COLL; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; FIPS 200-BIT; IPM OFF; UART OFF; WIE)LL; OSDP TAMP ENBLD; TEST KEYS; POLL=75MS; A/V OFF; KPF; ASCII; BFFRD 1 KEY; FIPS 200-BIT; IPM OFF; UAR

↓; BZR ON; OPT TAMP; OPEN COLL; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; FIPS 75-BIT; IPM OFF; UART OFF; WIE
↓; BZR ON; OPT TAMP; OPEN COLL; FIPS 200-BIT; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; IPM OFF; UART OFF; WIE
↓; BZR ON; OPT TAMP; OPEN COLL; FIPS 75-BIT; KPF; BFFRD 1 KEY; DOR COMPL; NO PAR; 8-BIT MSG; IPM OFF; UA

↓; OSDP TAMP ENBLD; TEST KEYS; POLL=75MS; A/V OFF; KPF; ASCII; BFFRD 1 KEY; FIPS 200-BIT; IPM OFF; UART

↓; OSDP TAMP ENBLD; TEST KEYS; POLL=75MS; A/V OFF; KPF; ASCII; BFFRD 1 KEY; FIPS 75-BIT; IPM OFF; UART

↓; OSDP TAMP ENBLD; TEST KEYS; POLL=75MS; A/V OFF; KPF; ASCII; BFFRD 1 KEY; FIPS 64-BIT; IPM OFF; UART

↓; BZR ON; OPT TAMP; OPEN COLL; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; FIPS 75-BIT; IPM OFF; UART OFF; WIE

↓; BZR ON; OPT TAMP; OPEN COLL; FIPS 200-BIT; KPF; BFFRD 1 KEY; DOR COMPL; NO PAR; 8-BIT MSG; IPM OFF; U

↓; BZR ON; OPT TAMP; OPEN COLL; FIPS 75-BIT; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; IPM OFF; UART OFF; WIE

↓; BZR ON; OPT TAMP; OPEN COLL; FIPS 75-BIT; KPF; BFFRD 1 TO 5 KEYS; PAR; USER ENTRD FC; 26-BIT MSG; IPM

↓; BZR ON; OPT TAMP; OPEN COLL; FIPS 64-BIT; RVRS BCD; KPF; BFFRD 1 KEY; DOR COMPL; NO PAR; 8-BIT MSG; I

↓; BZR ON; OPT TAMP; OPEN COLL; FIPS 200-BIT; KPF; BFFRD 1 KEY; DOR COMPL; NO PAR; 8-BIT MSG; IPM OFF

↓; BZR ON; OPT TAMP; OPEN COLL; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; FIPS 200-BIT; IPM OFF; UART OFF; \

↓; BZR ON; OPT TAMP; OPEN COLL; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; FIPS 75-BIT; IPM OFF; UART OFF; \

↓; BZR ON; OPT TAMP; OPEN COLL; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; FIPS 75-BIT; LCD 1F; IPM OFF; U

↓; BZR ON; OPT TAMP; OPEN COLL; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; FIPS 75-BIT; LCD 1F; A/V OFF; OSDP V2; OPT TAMP; OPEN COLL; OSDP TAMP ENBLD; TEST KEYS; POLL=75MS; KPF; ASCII; XMIT CMP

formation form with ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/docu>

th ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/documents/how-to-order>

lemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide <https://www.h>

g Information form with ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/do>

ASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/docu>

ering Information form with ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/docu>

rmation form with ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/docu>

iation form with ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/docu>

; Information form with ALL orders found in the pivCLASS How To Order Guide <https://www.hidglobal.com/docu>

ise lock and handles not included and must be ordered separately)(Available only in the USA and Canada)

ment handle set (Mortise lock and handles not included and must be ordered separately) (Available only in the
ise lock and handles not included and must be ordered separately) (Available only in the USA and Canada)

iar latch (anticard) deadlock the latch. Backset 50mm - 2 3/8. ASA strike; screws and dust box included. (Availat

ns like Schindler PORT protocole. Feature only available individually and is not included in any package.(Availab

ation; billed annually thereafter - Requires Annual Subscription Renewal (0028-2) (Available only in the USA and

4KBytes; SALTO Design; 1 color; pack of 50); Portable Programming Device (PPD800); Ncoder (ECB04B0); XS4 2.
t alarms and also sends emails to the operators generated by the events. (Available only in the USA and Canada

cess SPACE ID System package - Partitional functionalities (department operator) (Available only in the USA and

e included. To be used with KPB03. Exit signal when bar is depressed included. (Available only in the USA and C

to integrate with third party products. ANSI - North American - Single gang mount reader; Black; Transparent C
to integrate with third party products. Mullion - narrow reader; Black; Transparent Cover; US version; Includes

Desfire + Bluetooth LE + HSE. Standard -G Handle Standard spindle - 2 3/4 backset (Available only in the USA and Canada)
Desfire + Bluetooth LE + HSE. Standard - standard square spindles; finishes and handles.(Available only in the US and Canada)
DESFire + Bluetooth LE + HSE. Standard - standard square spindles; finishes and handles. (Available only in the US and Canada)
Desfire + Bluetooth LE + HSE. Standard - standard square spindles; finishes and handles. (Available only in the US and Canada)
override. Mifare Desfire + Bluetooth LE + HSE. Standard -G Handle Standard Spindle 2 3/4 backset. satin Chrome finish
override. Mifare Desfire + Bluetooth LE + HSE. Standard - standard square spindles; finishes and handles. Mechanical
override. Mifare Desfire + Bluetooth LE + HSE. Standard - standard square spindles; finishes and handles. Mechanical

Technology:Wireless - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)
DESFire: Standard - standard square spindles; finishes and handles. (Available only in the USA and Canada)
with audit housing; (mechanical cylinder not included; for technical specifications consult SALTO). Technology:

audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles; finishes and handles. (Available only in the US and Canada)
audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles; finishes and handles. (Available only in the US and Canada)

Technology: Mifare + Bluetooth LE + HSE and standard square spindles; finishes and handles.(Available only in the US and Canada)

audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles; finishes and handles. (Available only in the US and Canada)
built in mechanical cylinder with audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles; finishes and handles.

audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles; finishes and handles. (Available only in the US and Canada)
audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles; finishes and handles. Mechanical cylinder
4 Electronic Half Escutcheon Ax660 for panic bar; 1 handle; any type; built in mechanical cylinder with audit . Technology: Mifare + Bluetooth LE + HSE
audit for concealed rod panic bars. Technology: Mifare + Bluetooth LE + HSEand standard square spindles; finishes and handles.

connector for mortise lock with micro-switch. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; connector for mortise lock with micro-switch. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; with audit housing; (mechanical cylinder not included; for technical specifications consult SALTO). Technology: system; built in mechanical cylinder with audit housing; (mechanical cylinder not included). Technology: Mifare connector for mortise lock; built in mechanical cylinder with audit housing;(mechanical cylinder not included). T with audit housing; (mechanical cylinder not included; for technical specifications consult SALTO). Technology:

es; any type. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available o

ly Escutcheon - ANSI Electronic Escutcheon Ax650; For ANSI mortise locks; 2 handles; any type. Technology: Mi

system. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in

system. Technology: Mifare + Bluetooth LE + HSE; Satin Stainless; G Handle. (Available only in the USA and Cana

not disturb" system. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. XS4

system. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in

urn 90°; with connector for mortise lock with micro-switch. Technology: Mifare + Bluetooth LE + HSE - 8 mm sq

connector for mortise lock with micro-switch. Technology: Mifare + Bluetooth LE + HSE; finishes and handles. (/

with audit housing; (mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE - 8 mm square

with audit housing; (mechanical cylinder not included; for technical specifications consult SALTO). Technology:

with audit housing; (mechanical cylinder not included; for technical specifications consult SALTO). Technology:

with audit housing; (mechanical cylinder not included; for technical specifications consult SALTO). Technology:

with audit housing; (mechanical cylinder not included; for technical specifications consult SALTO). Technology:

system; built in mechanical cylinder with audit housing; (mechanical cylinder not included). Technology: Mifare

system; built in mechanical cylinder with audit housing; (mechanical cylinder not included). Technology: Mifare

system; built in mechanical cylinder with audit housing; (mechanical cylinder not included). Technology: Mifare

ystem; built in mechanical cylinder with audit housing; (mechanical cylinder not included). Technology: Mifare
ystem; built in mechanical cylinder with audit housing; (mechanical cylinder not included). Technology: Mifare
ystem; built in mechanical cylinder with audit housing; (mechanical cylinder not included). Technology: Mifare
es; any type. inside thumbturn 90°; with connector for mortise lock with micro-switch. Technology: Mifare + Bl
with audit housing; (mechanical cylinder not included; for technical specifications consult SALTO). Technology:
onnector for mortise lock; built in mechanical cylinder with audit housing;(mechanical cylinder not included). T
itcheon Ax660; For ANSI mortise locks; 2 handles; any type; built in mechanical cylinder with audit housing; (me

s a WRLUD-SIC1 to be connected to the CU. Mounting bracket included. Cable and WRLUD-SIC1 not included. (/

val at a facility using a tablet computer. Runs on Windows®; an Apple® iPad® or an Android® tablet computer. C

lution and reflection free scans of ID's and passports under white light and IR. The ICON Scanner therefore pro

osch intrusion panel; ViRIDI BEManager integration; Replication; Hot Stand By Auto Failover; SQL collaboration,

ACM Professional; Enterprise of Virtual system. One license is required for each ACM Embedded Controller to k

al appliance | embedded 64 bit Linux OS & Open LDAP for configuration database | Access Control Manager Sec
ippliance | embedded 64 bit Linux OS & Open LDAP for configuration database | Access Control Manager Secur
al appliance | embedded 64 bit Linux OS & Open LDAP for configuration database | Access Control Manager Sec
appliance | embedded 64 bit Linux OS & Open LDAP for configuration database | Access Control Manager Sec

S & Open LDAP for configuration database | Access Control Manager Security Management Software | 1024 Reader
& Open LDAP for configuration database | Access Control Manager Security Management Software | 128 Reader
32 Open LDAP for configuration database | Access Control Manager Security Management Software | 16 Reader
S & Open LDAP for configuration database | Access Control Manager Security Management Software | 2048 Reader
& Open LDAP for configuration database | Access Control Manager Security Management Software | 256 Reader
32 Open LDAP for configuration database | Access Control Manager Security Management Software | 32 Reader
& Open LDAP for configuration database | Access Control Manager Security Management Software | 512 Reader
32 Open LDAP for configuration database | Access Control Manager Security Management Software | 64 Reader

er controller; includes the M5-IC as well as the 4 reader daughter board (Mercury Part Number: M5-2K)

th a 1K-byte memory. Constructed of durable ABS; it is backed by a lifetime warranty. Memory of the model
th a 4K-byte memory. Constructed of durable ABS; it is backed by a lifetime warranty (Minimum order is 50) (F

/. Manufactured from glossy PVC; it is appropriate for dye sublimation imaging (ISO style) (Minimum order is 50)
ry. Manufactured from glossy PVC; it is appropriate for dye sublimation imaging (ISO style) - with a magnetic stri

/. Manufactured from glossy PVC; it is appropriate for dye sublimation imaging (ISO style) (Minimum order is 50)
ry. Manufactured from glossy PVC; it is appropriate for dye sublimation imaging (ISO style) - with a magnetic stri

limation imaging with a magnetic stripe (Minimum order is 50) (Farpointe Data Part Number: PSM-2S-H)

redential with a 1K-byte memory. It is designed to be carried on a key ring; and includes a brass reinforcing eyelet

redential with a 4K-byte memory. It is designed to be carried on a key ring; and includes a brass reinforcing eyelet

1 RFID devices; including ID credentials; cell phones and wallets. The PDT-1 offers a read range up to 3.5 inches

ass eyelet; and is backed by a lifetime warranty (Minimum order 50) (Farpointe Data Part Number: PSK-3-H)

range 433 MHz (upon button push) and MIFARE® DESFire® EV2 2K memory smartcard insert 13.56-MHz Smart

range 433 MHz (upon button push) and w/ Farpointe 13.56-MHz 4K memory smartcard insert. (Farpointe Data

range 433 MHz (upon button push) and 125 kHz proximity operation. (Farpointe Data Part Number: WRT-2+H)

white with magnetic stripe on back; no slot punch (HID #: 2120BG1MNN); Minimum Order 100. Specify program (HID #: 2120BGGMNM); Minimum Order 100. Specify programming information for 125kHz Proximity and iCLA

s on Mobile-Enabled Readers. Require automated onboarding form to be filled. (LINK to Automated Onboarding

USTOM AVIGILON PACKAGING-SHRINK WRAP IN LOTS OF 50; PACK 100/BOX; LAM; AVIGILON LOGO; (AVIGILON

OM AVIGILON PACKAGING-SHRINK WRAP IN LOTS OF 50; PACK 100/BOX; LAM; (AVIGILON FORMAT- NO PROG

TCHING ICLASS #; NO SLOT; NO PROX #; LAM; Minimum Order 100 (HID Part Number: 5106PG1MNN)

GLOSS; MATCHING ICLASS #; NO SLOT; NO PROX #; Minimum Order 100 (HID Part Number: 5106PGGMNN)

-GLOSS; B-GLOSS; NO ICLASS #; NO PROX #; NO SLOT; LAM; Minimum Order 100 (HID Part Number: 5106RGGN

ncurrent users) valid for one year in an HID Origo account (linked to the Organization ID). Please provide the or
umber of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Org;

il Matching Internal/External – Peel-off self-adhesive back; Minimum Order 100 (HID Part Number: 3300PKSMI

.MER-CON–MR52 (Mercury hardware sold separately). Includes painted steel enclosure; removable pre drilled
MER-CON–MR52 (Mercury hardware sold separately). The advantage of a dual voltage power supply is the abilit
ONT-2DR (Mercury hardware sold separately). Includes painted steel enclosure; removable pre drilled back plat
INT-2DR (Mercury hardware sold separately). The advantage of a dual voltage power supply is the ability to pow
-CON–MR52 (Mercury hardware sold separately). Includes painted steel enclosure; removable pre drilled back
CON–MR52 (Mercury hardware sold separately). The advantage of a dual voltage power supply is the ability to
ER-CON–MR52 (Mercury hardware sold separately). Includes painted steel enclosure; removable pre drilled bac
R-CON–MR52 (Mercury hardware sold separately). The advantage of a dual voltage power supply is the ability t
y power system. Primary power for the B100 is derived from an main FPO power supply and the B100 steps the
ol and is typically supplied as part of a system or purchased as an expansion piece to an existing system. The C4
control and is typically supplied as part of a system or purchased as an expansion piece to an existing system. T

y a solid state circuit breaker (D8P) rated at 2.5A each. Each output is programmable to either of the two volta

configurations for maximum design flexibility. The modular mounting pattern on the back wall allows flexible

in the cabinet. Comes with door lock and two (2) keys. Weight: 24 lb. Size: 20" x 24" x 4.5"(LifeSafety Power Pai
is available within the cabinet. Comes with door lock and two (2) keys. Weight: 26 lb. Size: 20" x 24" x 4.5"(Life
12V or 24V; 8Ah batteries is available within the cabinet. Comes with door lock and two (2) keys. Weight: 24 lb

*** Battery space for 12V or 24V; 8Ah batteries is available within the cabinet. Comes with door lock and two

. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Secur
. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Secur
. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Secur
n flexibility; functionality and savings to access system designers. MCLASS enclosures are engineered to house F

re alarm interface (FAI); disable voltage on FAI or provide a constant output voltage ATM style fuse: 3A/per out fire alarm interface (FAI); disable voltage on FAI or provide a constant output voltage Solid state circuit breaker M1) is an offline switchmode power supply battery charger system. The unit is user selectable for 12 or 24VDC. all voltages; microprocessor battery charging; 80Ah charge capability; continuous and switched DC outputs; eig microprocessor battery charging; charger software algorithm minimizes effects of deep battery discharge; cont

ax; class 2 power limited | 8 relay lock control outputs fused at 3A per output; each output selectable for FAI; fa 4200; or CU4EB8 Modules (sold seperately) in one compact and secure UL Listed solution. This unit is a 150W 1 Lock Outputs/8 Auxiliary Outputs. Backplate mounting for LP1502; LP4502; LP2500; MR52; MR16IN; E4M Enclo ; 120 VAC; 8 Lock Outputs / 16 Auxiliary Outputs; Size: 24.0H x 20.0W x 6.5D in (60.96 x 50.8 x 16.51 cm); 8 Doc 4200; or CU4EB8 Modules (sold seperately) in one compact and secure UL Listed solution. This unit is a 12V anc ass 2 power limited output | 8 auxiliary DC outputs class 2 power limited at 2.5A per output | Eight output sma ss 2 power limited output | Eight output smart distribution module; fused at 3A per output | Four port network igne as a general purpose power supply to provide uninterrupted power for locks; auxiliary equipment and ac ; microprocessor battery charging; charger software algorithm minimizes effects of deep battery discharge; cor

IC outputs class 2 power limited at 2.5A per output | Eight output smart distribution module; fused at 3A per o IC outputs class 2 power limited at 2.5A per output | Eight output smart distribution module; fused at 3A per o IC outputs class 2 power limited at 2.5A per output | 16 output smart distribution module; fused at 3A per out

ired for MERCURY controllers (sold seperately). ProWire enables the specification and installation of standar ax; class 2 power limited | 16 DC auxiliary outputs class 2 power limited at 2.5A per output; each output selecta igne as a general purpose power supply to provide uninterrupted power for locks; auxiliary equipment and ac ; microprocessor battery charging; charger software algorithm minimizes effects of deep battery discharge; coi

max; class 2 power limited | 8 DC auxiliary outputs class 2 power limited at 2.5A per output; each output selectal ; microprocessor battery charging; charger software algorithm minimizes effects of deep battery discharge; co

; 40 network managed fused outputs; 16 Doors; Panduit; Prewired for one LP1502 and seven MR52 boards; Er

compact and secure UL listed solution. ProWire system are prewired for power to the access control modules; fa ned as a general purpose power supply to provide uninterrupted power for locks; auxiliary equipment and acce 4200; or CU4EB8 Modules (sold seperately) in one compact and secure UL Listed solution. This unit is a 75W 12 in offline switchmode 75 watt power supply-battery charger specifically designed for the lifesafety industry. Cap microprocessor battery charging; charger software algorithm minimizes effects of deep battery discharge; continu ; class 2 power limited | 4 relay lock control outputs fused at 3A per output; each output selectable for FAI; fails 4200; or CU4EB8 Modules (sold seperately) in one compact and secure UL Listed solution. This unit is a 75W 12 4200; or CU4EB8 Modules (sold seperately) in one compact and secure UL Listed solution. This unit is a 75W 12 s 2 power limited output | Eight output smart distribution module; fused at 3A per output | Four port network act and secure UL list solution. 75W Total Output Power | 12VDC/6A or 24VDC/3A 5-18VDC @ 4A Max. | FPO 4200; or CU4EB8 Modules (sold seperately) in one compact and secure UL Listed solution. This unit is a 75W 12 4200; or CU4EB8 Modules (sold seperately) in one compact and secure UL Listed solution. This unit is a 75W 12 e power supply-battery charger specifically designed for the lifesafety industry. Capable of providing two powe

f Enclosure; inputs for two parallel readers. Requires 12 or 24 VDC power supply (Non-stock item)(Allegion Part

/ to location requiring mullion mount; and integrates both a contactless smartcard reader (13.56-MHz) and a ke
ly to location requiring mullion mount; and integrates both a contactless smartcard reader (13.56-MHz) and a k

American single-gang wall switch box; and other flat surfaces (Stock Item) (Farpointe Data Part Number: Delta
mounting to a standard European-sized (60 mm) wall switch box; and other flat surfaces (Non Stock Item) (Farp
standard North American sized single-gang wall box; and integrates both a contactless smartcard reader (13.56-

ed single-gang wall box; and integrates both a proximity reader and keypad into a single-unit making it ideal for

ed single-gang wall box; and integrates both a proximity reader and keypad into a single-unit making it ideal for
rking lots and high-volume employee entrances (Non Stock Item)(Farpointe Data Part Number: P-710-H)

ering read ranges of up to 20-inches (508 mm). The longer read range of the P-900 adds convenience to a wide |

1 HID® 125-kHz Proximity protocols; single-gang mount. (Non-stock item) (Farpointe Data Part Number: MCR-50

uts and install similar to a Pyramid Series Proximity® reader; making for easy integration with most access control systems (61-m); and is ideal for applications involving vehicle or disabled access (Stock Item) (Farpointe Data Part Number: 900NTNNEK00000-A001)

OSDP TAMP ENBLD; TEST KEY; POLL=75MS; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; UART OFF; WIEG OFF (HID Part #: 900NMPNEKEA); OSDP TAMP ENBLD; TEST KEY; POLL=75MS; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; UART OFF; WIEG OFF (HID Part #: 900NMPNEKEA); OSDP TAMP ENBLD; TEST KEY; POLL=75MS; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; UART OFF; WIEG OFF (HID Part #: 900NMPNEKEA); OSDP TAMP ENBLD; TEST KEY; POLL=75MS; CSN 32-BIT MSB; KPF; ASCII; BFFRD 1 KEY; EM4102 32-BIT; IPM OFF (HID Part #: 900NMPNEKEA)

MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 900NMPNEKEA)

MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 900NMPNEKEA)

MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 910NMPNEKEA)

MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 910NMPNEKEA)

Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 920NMPNEKEA)

Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 900NMPNEKEA)

Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 900NMPNEKEA)

MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 910NMPNEKEA)

MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 910NMPNEKEA)

Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 900NMPNEKEA)

Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 900NMPNEKEA)

EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail; Avigilon logo (HID Part #: 900NTNNEK00000-A001)

SIO); MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0000
assic (SIO); MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 921NTNNEK0000C

MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 920PTI
MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail; Avigilon logo (HID
os; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail

SH GRN; BZR ON; OPT TAMP; OPEN COLL; CSN 32-BIT MSB; IPM OFF (HID Part #: 900LTNNEK00017)

CLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled;
PEN COLL; OSDP TAMP ENBLD; TEST KEY; POLL=75MS; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; UART OFF; V
CLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled;
TAMP; OPEN COLL; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; MOBILE-READY (HID Part #: 900PMPTEKMA00
Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigta

Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Term
Smart; iCLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile e
N COLL; OSDP TAMP ENBLD; TEST KEY; POLL=75MS; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; UART OFF; WIE
Smart; iCLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile e
PEN COLL; OSDP TAMP ENBLD; TEST KEY; POLL=75MS; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; UART OFF; V

t; iCLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabl
AMP; OPEN COLL; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; MOBILE-READY (HID Part #: 900PMNNEKMA003)

t; iCLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabl
TAMP; OPEN COLL; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; MOBILE-READY (HID Part #: 900PMNTEKMA0C
MP; OPEN COLL; I'M ALIVE; VAR OUTPUT PER SIO; IPM OFF; VEL ON; MOBILE READY (HID Part #: 910PBNNEK20

.ASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pi
AMP; OPEN COLL; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; MOBILE-READY (HID Part #: 910PMNNEKMA003)

.ASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Te
TAMP; OPEN COLL; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; MOBILE-READY (HID Part #: 910PMNTEKMA0C

AMP; OPEN COLL; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; MOBILE-READY (HID Part #: 920PMNNEKMA003)

with Smart; iCLASS Seos; SE; SR; Standard; MIFARE Classic (SIO); MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobil
TAMP; OPEN COLL; CSN 32-BIT MSB; EM4102 32-BIT; IPM OFF; MOBILE-READY (HID Part #: 920PMNTEKMA0C

N; CSN 32-BIT MSB; KPF; BFFRD 1 KEY; NO PAR; 4-BIT MSG; IPM OFF (HID Part #: 921PTNNEKE0000)

NTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 20K PIGTAIL MODEL - Profile T0 includes the following NFC
PROFILE OPTION (T1) FOR THE SIGNO READER 20K PIGTAIL MODEL - Profile T1 includes the following NFC/BLE/
L PROFILE OPTION (T2) FOR THE SIGNO READER 20K PIGTAIL MODEL - Profile T2 includes the following NFC/BL
EN:13;EM:32-B;MAP1:DF;ICE1758;LED:RED;FLSH:GRN;BZR;KBD:RED;KBZR;VIS:ON;SRF:ON;VEL:OFF;TAP

DENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 20K TERMINAL STRIP MODEL - Profile T0 includes the fc
AL PROFILE OPTION (T1) FOR THE SIGNO READER 20K TERMINAL STRIP MODEL - Profile T1 includes the followir
TIAL PROFILE OPTION (T2) FOR THE SIGNO READER 20K TERMINAL STRIP MODEL - Profile T2 includes the follow

LE OPTION (T0) FOR THE SIGNO READER 20 PIGTAIL MODEL - Profile T0 includes the following NFC/BLE/High Fr
TION (T1) FOR THE SIGNO READER 20 PIGTAIL MODEL - Profile T1 includes the following NFC/BLE/High Frequen
OPTION (T2) FOR THE SIGNO READER 20 PIGTAIL MODEL - Profile T2 includes the following NFC/BLE/High Frequ

PROFILE OPTION (T0) FOR THE SIGNO READER 20 TERMINAL STRIP MODEL - Profile T0 includes the following NFC/
OPTION (T1) FOR THE SIGNO READER 20 TERMINAL STRIP MODEL - Profile T1 includes the following NFC/BLE/H
E OPTION (T2) FOR THE SIGNO READER 20 TERMINAL STRIP MODEL - Profile T2 includes the following NFC/BLE,

CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 40K PIGTAIL MODEL - Profile T0 includes the following
IAL PROFILE OPTION (T1) FOR THE SIGNO READER 40K PIGTAIL MODEL - Profile T1 includes the following NFC/I
NTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 40K PIGTAIL MODEL - Profile T2 includes the following NFC

CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 40K TERMINAL STRIP MODEL - Profile T0 includes th
:NTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 40K TERMINAL STRIP MODEL - Profile T1 includes the foll
DENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 40K TERMINAL STRIP MODEL - Profile T2 includes the fc

ROFILE OPTION (T0) FOR THE SIGNO READER 40 PIGTAIL MODEL - Profile T0 includes the following NFC/BLE/Hig
: OPTION (T1) FOR THE SIGNO READER 40 PIGTAIL MODEL - Profile T1 includes the following NFC/BLE/High Frec
LE OPTION (T2) FOR THE SIGNO READER 40 PIGTAIL MODEL - Profile T2 includes the following NFC/BLE/High Fr

. PROFILE OPTION (T0) FOR THE SIGNO READER 40 TERMINAL STRIP MODEL - Profile T0 includes the following NFC/BLUETOOTH FILE OPTION (T1) FOR THE SIGNO READER 40 TERMINAL STRIP MODEL - Profile T1 includes the following NFC/BLUETOOTH PROFILE OPTION (T2) FOR THE SIGNO READER 40 TERMINAL STRIP MODEL - Profile T2 includes the following NFC/BLUETOOTH

KHz Single Format Module; In addition to EM Format; it can be configured to read either HID Prox 26bit or 37bit

ology module. All the following can be selected; and the reader send information as raw data. HID Prox – 26; 35

Interface - 3m cable with connector - NO LOGO- Mullion Reader Black Wiegand 26bit - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECURE STORAGE EAL5+ - RS485 interface - 3m cable with connector - NO LOGO - Mullion Reader Black OSDP v1 & v2 - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECURE STORAGE EAL5+ - Secure Read only - TTL interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECURE STORAGE EAL5+ - Secure Read only - TTL interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECURE STORAGE EAL5+ - Secure Read only

Standard Multi-technology Reader black Wiegand Infrared Standard Multi-technology Keypad Reader black Wiegand Infrared Standard Multi-technology Keypad Reader black Wiegand Infrared

Secure storage EAL5+ - RS485 interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT v1 & v2 secure protocol - Secure storage EAL5+ - RS485 interface - NO LOGO - Standard Reader black with QR module Secure storage EAL5+ - RS485 interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT v1 & v2 secure protocol - Secure storage EAL5+ - RS485 interface - NO LOGO - Standard reader black with Keypad Secure storage EAL5+ - RS485 interface - NO LOGO - Standard reader black with touchscreen OSDP - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT v1 & v2 secure protocol

; User Capacity: 10;000; Finger Capacity: 1;500; TCP/IP Server Communication; No LCD; No Function Key; blue LED

; User Capacity : 10;000; Finger Capacity: 1;500; TCP/IP Server Communication; No LCD; No Function Key; blue LED

13.56Mhz Card & PIN Authentication; User Capacity: 1;500; Finger Capacity: 1500; TCP/IP Server Communication; No

Supports HID iClass Card & PIN authentication. User Capacity : 20;000; Finger Capacity: 20;000; IP 65 Weatherproof

Supports HID Prox Card & PIN authentication. User Capacity : 20;000; Finger Capacity: 20;000; IP 65 Weatherproof;

Supports Mifare 13.56Mhz Card & PIN authentication. User Capacity : 20;000; Finger Capacity: 20;000; IP 65 Weath

Card (Read & Write); Fingerprint Platen Area: 16 x 19.6mm / Image Size: 15 x 17mm; Read /Write - supports TOC

Access Control Tool Software and License Files; Aperio Instructions (electronic files); Trittech Tribec USB Radio Dongle (AF-NT). The external antenna may be used to obtain more even radio coverage (in the form of a doughnut) around

included Wall/Post Mounting Hardware. For indoor use with PIM400 and/or WRI400. Requires MGB+MCA5 Ant

Mercury Security` 1DR and 64DR (AC-MER-CONT-1DR and AC-MER-CONT-64DR Sold Separately) access control p

Series wireless devices; powered by Mercury Security. Encrypted with AES-128 bit keys; Certifications: FCC Part 15.247 (Class B); AC-MER-CONT-LP2500 and AC-MER-CONT-LP4502 Sold Separately) (Up to 16 wireless access devices supported); Weatherproof Enclosure (7.1" x 7.1"); Internal Antenna with ability to add Remote Antenna. Requires 12 VDC

Access Functions (Cylindrical; Mortise and Exit Chassis) Privacy/Apartment Functions (Mortise Deadbolt Chassis) 6:1

Avigilon - Unity Access - US Price List - MSRP - USD

--	--	--	--	--	--	--	--	--	--

0 Controller - Ethernet (CU42E0TUS) and 2 Mullion LE DESFire/Mifare readers (Available only in the USA and C

cover; US version; Includes UBOX 42 controller in a case with translucent cover and black ANSI rectangular BLE
UBOX 42 controller in a case with translucent cover and black mullion BLE Mifare DESFire reader. (Available o

anical cylinder not included. (Available on in the USA and Canada) (Replacement for CB260N70CSB3)

cylinder not included; for technical specifications consult SALTO. Gain durability feature included by default. Fc
echnology: Mifare + Bluetooth LE + HSE and standard square spindles; finishes and handles. (Available only in 1
as and handles. Mechanical cylinder not included. Half escutcheon model; only compatible for Von Duprin 98 /

Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | Privacy Button | ANSI | N lever | satin ss (Available only in the USA and Canada)

8 mm square spindle; finishes and handles. XS4 Original+ | BLE | Mifare | HSE | Dark Bronze | Black Rdr | ANSI | N lever (Available only in the USA and Canada)

8 mm square spindle; finishes and handles. XS4 Original+ | BLE | Mifare | DESFire | HSE | Black Rdr | KO | Entrance | ANSI | A lever (Available only in the USA and Canada)

Mifare + Bluetooth LE + HSE - 8 mm split square spindle; finishes and handles. (Available only in the USA and Canada)

Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada). Mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle; finishes and handles. (Available only in the USA and Canada)

Configurable self-registration screen can support any field including fields designated as required. Provides ability to

be migrated. License includes migration of Cardholders into Identities and conversion of the ACM EC into a HIC

curity Management Software | 1024 Reader Count Software License | One (1) ACM Verify | ACC Video Integra
rity Management Software | 16 Reader Count Software License | One (1) ACM Verify | ACC Video Integration
curity Management Software | 2048 Reader Count Software License | One (1) ACM Verify | ACC Video Integra
urity Management Software | 512 Reader Count Software License | One (1) ACM Verify | ACC Video Integratic

Reader Count Software License | One (1) ACM Verify | ACC Video Integration | Five (5) partitions | Identities CSV export
Reader Count Software License | One (1) ACM Verify | ACC Video Integration | Five (5) partitions | Identities CSV export
Reader Count Software License | One (1) ACM Verify | ACC Video Integration | Five (5) partitions | Identities CSV export
Reader Count Software License | One (1) ACM Verify | ACC Video Integration | Five (5) partitions | Identities CSV export
Reader Count Software License | One (1) ACM Verify | ACC Video Integration | Five (5) partitions | Identities CSV export
Reader Count Software License | One (1) ACM Verify | ACC Video Integration | Five (5) partitions | Identities CSV export
Reader Count Software License | One (1) ACM Verify | ACC Video Integration | Five (5) partitions | Identities CSV export
Reader Count Software License | One (1) ACM Verify | ACC Video Integration | Five (5) partitions | Identities CSV export

; (88.9 mm) when used with a P-500. Model P-PDT-1-H is 125 HID kHz compatible; while PDT-1-A is 125 kHz A'

g: <https://managementservices.hidglobal.com/faces/maUserOnBoardingStart>) (HID Part Number: ADMIN-SEC9X-C

organization and credential access control data format information (Organization ID; Organization Name; MOB c
anization ID). Price is pro-rate: full-month till the end of the contract. Minimum Order Quantity: 20 (HID Part N

back plate; controller standoffs and mounting screws and a 150 watt 12V/12A or 24V/6A power supply-batter
y to power Mercury boards and door locks. Includes a painted steel enclosure; removable pre drilled back plai
te; controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery charger. 1
wer both Mercury boards and door locks from the same supply. Includes a painted steel enclosure; removable
plate; controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery charg
power both Mercury boards and door locks from the same supply. Includes a painted steel enclosure; remova
ck plate; controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery cha
to power both Mercury boards and door locks from the same supply. Includes a painted steel enclosure; remo
e FPO voltage down to the user defined range (typically 12VDC). B100 delivers up to 4A maximum current at 1.
l provides four (4) access control inputs capable of voltage or dry contact activation and four (4) relay controlle
he C8 provides eight (8) access control inputs capable of voltage or dry contact activation and eight (8) relay c

ges available when used in a dual voltage power system; or to the continuous output or the resettable output

positioning of FlexPower modules within the enclosure. E series enclosures are black powdercoated steel. All

urity™ access panels (sold separately) in one compact; secure UL294 listed system. The E6M1 enclosures cover
urity™ access panels (sold separately) in one compact; secure UL294 listed system. The E6M1 enclosures cover
urity® access panels (sold separately) in one compact; secure system. The E8M can be configured for a maximu
FlexPower® power management boards alongside Mercury Security® access panels in one compact; secure sys

no power outputs; user selectable for 12 or 24 VDC; the unit is configured in a painted-steel; locking enclosure
uous and switched DC outputs; eight 12 or 24VDC auxiliary outputs fused at 3A (Class 2 power limited versior
able of voltage or dry contact activation and eight (8) controlled and monitored OUTPUTS; with each output r

enable monitoring; reporting and control of the power system. Enables remote testing of two battery sets (1:
sure has two D8P auxiliary distribution modules for 16 class II power limited outputs. Battery space for 12V or
cury panels and two (2) I/O modules; 6 placed in the main box and 4 on the door. Enclosure has two C8 lock c
/ or 24V; 8Ah batteries is available. Enclosure comes standard with installed AC on/off switch; a low battery di
control modules for 16 distributed lock outputs and two D8P auxiliary distribution modules for 16 class II power

t chassis; UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75B-C4PNZ)
t chassis; UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75B-C4PZ)
t chassis; UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75B-M8PNZ)

thernet port to a micro-b USB connector; allowing direct connection of the NetLink to an LP series controller's
at 3A per output | Enclosure; Size 18. (16W x 20H x 4.5D) with Mercury backplate (Non-stock item)(LifeSafety
3A per output | Network communication module 2nd Gen. | Enclosure; Size 18. (16W x 20H x 4.5D) with Mer
power limited at 2.5A | Four port monitoring module | Enclosure size: 30" x 23" x 6.5" | 47 lbs | Wired for MR!
it power limited at 2.5A | Enclosure size: 30" x 23" x 6.5" | 47 lbs | Wired for MR52/EP1502. NOTE: All ProWir
it 2.5A | Enclosure size: 36" x 30" x 4.5" | 73 lbs | Wired for MR52/EP1502. NOTE: All ProWire Unified Power v
it 2.5A | Enclosure size: 36" x 30" x 4.5" | 73 lbs | Wired for all MR52s. NOTE: All ProWire Unified Power wall r
!.5A | Four port monitoring module | Enclosure size: 36" x 30" x 4.5" | 73 lbs | Wired for MR52/EP1502. NOTE
!.5A | Four port monitoring module | Enclosure size: 36" x 30" x 4.5" | 73 lbs | Wired for All MR52s. NOTE: All

idays; and schedules. PREREQUISITES: AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not includ
nd is not included. Service will be delivered remotely and requires remote access to the customers environme
days; and schedules. PREREQUISITES: AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not include
days; and schedules. PREREQUISITES: AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not include
collaboration licensing is required and is not included. Service will be delivered remotely and requires remote
boration licensing is required and is not included. Service will be delivered remotely and requires remote acce
n licensing is required and is not included. Service will be delivered remotely and requires remote access to th
ACM LDAP collaboration licensing is required and is not included. Service will be delivered remotely and requ
Oracle collaboration licensing is required and is not included. Service will be delivered remotely and requires
collaboration licensing is required and is not included. Service will be delivered remotely and requires remot
lows-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest AF
indows-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest
roles. PREREQUISITES: Separate Windows-based server (virtual is acceptable) to host the synchronization servi
s-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API lic
ws-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API l
-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API lice

NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFire EV1/EV2

NFC/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFire EV1/EV2

Allowing NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFire EV1/EV2

Allowing NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFire EV1/EV2

High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFire EV1/EV2

High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFire EV1/EV2 (

BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DE
/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFir

; NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFA
C/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE C

re following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCL
ollowing NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS

gh Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFire EV
requency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DESFire EV1/E

NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DE
BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE); Seos; iCLASS SE®; iCLASS SR®; iCLASS®; MIFARE DE

Interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration program
Black Wiegand interface - NO LOGO -Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configu

OSDP - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming

Load and QR module OSDP - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration pr

f; TCP/IP server communication. Power Supply not included. (VIRDI Part Number: AC5000PlusiClass)

erproof & PoE 13W; TCP/IP server communication. Power Supply Not Included.(VIRDI Part Number: AC5000PI

(Template on Card) (VIRDI Part Number: FOH02SC) Note - This product is not available for sale in Spain and So

the hub. Please note that the antenna does not extend the maximum range of the Aperio® hub. The Aperio® h

t 15; Industry Canada(IC); RoHS; UL294 Listed when connected to UL294 power supply; Dimensions: 10.43" X
ch as AD-400 locks per PIM) for AD Series wireless devices; powered by Mercury Security. Certifications: NEM,

Avigilon - Unity Access - US Price List - MSRP - USD

--	--	--	--	--	--	--	--	--	--

'9957 concealed vertical rod panic bar. Gain durability feature included by default. For exterior use; consider a

lity to display PDF or HTML file for visitors to review and acknowledge or agree to terms. Utilizes intuitive touc

o VertX EVO V1000 controller. The ACM system does require the appropriate number of HID licensing (AC-SW-

ition | Five (5) partitions | Identities CSV export; recurring; one-time; long & short format | Total reader capacity
| Five (5) partitions | Identities CSV export; recurring; one-time; long & short format | Total reader capacity ca
ition | Five (5) partitions | Identities CSV export; recurring; one-time; long & short format | Total reader capac
on | Five (5) partitions | Identities CSV export; recurring; one-time; long & short format | Total reader capacity

AV export; recurring; one-time; long & short format | Total reader capacity can be expanded from 1024 to 2048 reader
AV export; recurring; one-time; long & short format | Total reader capacity can be expanded from 128 to 2048 reader
AV export; recurring; one-time; long & short format | Total reader capacity can be expanded from 16 to 2048 reader
AV export; recurring; one-time; long & short format | Total reader capacity cannot be expanded | Supports up to 1024 reader
AV export; recurring; one-time; long & short format | Total reader capacity can be expanded from 256 to 2048 reader
AV export; recurring; one-time; long & short format | Total reader capacity can be expanded from 32 to 2048 reader
AV export; recurring; one-time; long & short format | Total reader capacity can be expanded from 512 to 2048 reader
AV export; recurring; one-time; long & short format | Total reader capacity can be expanded from 64 to 2048 reader

or ICE and format: facility/site code; card number range; etc.). Require automated onboarding form to be compl

y charger. The power supply is pre-wired to eight Class 2; Power Limited (CL2PL) outputs (D8P Board) deliverin
te; controller standoffs and mounting screws. System includes one 150 watt 12V/12A pre-wired to sixteen Cla
The power supply is pre-wired to eight Class 2; Power Limited (CL2PL) outputs (D8P Board) delivering a regulat
pre drilled back plate; controller standoffs and mounting screws and a 75 watt 12V/2A and 24V/2A power sup
er. The power supply is pre-wired to eight Class 2; Power Limited (CL2PL) outputs (D8P Board) delivering a reg
ble pre drilled back plate; controller standoffs and mounting screws and a 75 watt 12V/2A and 24V/2A power
rger. The power supply is pre-wired to eight Class 2; Power Limited (CL2PL) outputs (D8P Board) delivering a re
vable pre drilled back plate; controller standoffs and mounting screws and a 150 watt 12V/4A and 24V/4A pov

controlled outputs; individually fuse protected at 3A per output.(LifeSafety Power Part Number: C8)

enclosures come with installed door ground strap; lockset and tamper switch. 20 x 16 x 4.5" (510 x 410 x 120

a door count from eight to eighteen with dual voltage distribution and network monitoring. To prevent damage
a door count from four to eight with dual voltage distribution and network monitoring. To prevent damage to
item. The E8M2 can be configured for a maximum of sixteen doors with dual voltage distribution.To prevent d

the second is programmable for either fail-safe or fail-secure operation; activated when the fire alarm disconnection (AI); eight opto isolated; NO/NC; access control inputs; eight relay lock control outputs; programmable for either fail-safe or fail-secure operation (also available); fire alarm input (FAI); eight opto isolated; NO/NC; access control inputs; eight relay lock control outputs

Bus1 or Bus2 | E4 enclosure size 24H x 20W x 4.5D with Mercury back plate; Prewired; Tiewrap; 8 doors; Mercury outputs capable of voltage or dry contact activation; and eight fused outputs programmable for failsafe / failsecure

eight access control inputs capable of voltage or dry contact activation; and eight outputs programmable for failsafe / failsecure. Enclosure size 20W x 24H x 4.5D) with backplate which can hold up to four Mercury boards. Battery space available in front of enclosure

the unit provides multiple outputs; fire alarm interface; AC fault reporting; system faultreporting; form 'C' fault reporting (also available); fire alarm input (FAI); sixteen opto isolated; NO/NC; access control inputs; sixteen relay lock control outputs

Module | Enclosure 20W x 24H x 4.5D with backplate and door mount which can hold up to eight Mercury boards. Module | Enclosure 30W x 23H x 6.5D with Mercury backplate and door mount option (Lifesafety Power Part #: FPO2)

powering module | E4 enclosure size 24H x 20W x 4.5D with Mercury back plate and door mount kit; Panduit; 8 Doors the unit provides multiple outputs; fire alarm interface; AC fault reporting; system faultreporting; form 'C' fault reporting (also available); fire alarm input (FAI); sixteen opto isolated; NO/NC; access control inputs; sixteen relay lock control outputs

powering module E6 enclosure size 30H x 23W x 6.5D with Mercury back plate. (LifeSafety Power Part Number: FPO2) the unit provides multiple outputs; fire alarm interface; AC fault reporting; system faultreporting; form 'C' fault reporting (also available); fire alarm input (FAI); sixteen opto isolated; NO/NC; access control inputs; sixteen relay lock control outputs

the unit provides multiple outputs; fire alarm interface; AC fault reporting; system faultreporting; form 'C' fault reporting (also available); fire alarm input (FAI); sixteen opto isolated; NO/NC; access control inputs; sixteen relay lock control outputs. Access enclosures are painted steel with five removable controller backplates and include lock; two (2) keys and tamper switch; locking enclosure with tamper switch and integral battery space. One output provides continuous output power for system use; the second provides relay lock control outputs; failsafe or failsecure; and FAI – each output fused for 3A (Class 2 power limited version)

outputs capable of voltage or dry contact activation; and four fused outputs programmable for failsafe / failsecure. Access enclosures are painted steel with five removable controller backplates and include lock; two (2) keys and tamper switch; locking enclosure with tamper switch and integral battery space. One output provides continuous output power for system use; the second provides relay lock control outputs; failsafe or failsecure; and FAI – each output fused for 3A (Class 2 power limited version)

Voltage Ripple | System Efficiency: 85% | System BTU Rating: 33 BTU/Hr. 2.5A Class 2 power limited outputs; processing enclosures are painted steel with two removable controller backplates and include lock; two (2) keys and tamper switch; locking enclosure with tamper switch and integral battery space. One output provides continuous output power for system use; the second provides relay lock control outputs; failsafe or failsecure; and FAI – each output fused for 3A (Class 2 power limited version)

DESFire EV1/EV2 (SIO)/EV3; MIFARE Classic (SIO); MIFARE DESFire EV1/EV2 (CSN); MIFARE Classic (CSN)

®; MIFARE DESFire EV1/EV2 (SIO)/EV3; MIFARE Classic (SIO); MIFARE DESFire EV1/EV2 (CSN); MIFARE Classic (CSN)

Fire EV1/EV2 (SIO)/EV3; MIFARE Classic (SIO); MIFARE DESFire EV1/EV2 (CSN); MIFARE Classic (CSN)

RE DESFire EV1/EV2 (SIO)/EV3; MIFARE Classic (SIO); MIFARE DESFire EV1/EV2 (CSN); MIFARE Classic (CSN)

.ASS®; MIFARE DESFire EV1/EV2 (SIO)/EV3; MIFARE Classic (SIO); MIFARE DESFire EV1/EV2 (CSN); MIFARE Clas:

E DESFire EV1/EV2 (SIO)/EV3; MIFARE Classic (SIO); MIFARE DESFire EV1/EV2 (CSN); MIFARE Classic (CSN)

Units are for indoor use only; Operating Temperature: 32°F (0 °C) to 113°F (45 °C) and Humidity: < 95% maximum

7.28" X 3.79" (26.49cm X 18.49 cm X 9.63 cm); Weight 2.8 lbs (1.27 kg)(Allegion Part Number: PIM400-1501-L1-A 1; 4; 4X; 6; UL 294; FCC Part 15; Industry Canada (IC); RoHS; Dimensions (H x W x D): 6.3" x 3.2" x 2.2" (16.0 cm x 8.1 cm x 5.6 cm))

Avigilon - Unity Access - US Price List - MSRP - USD

--	--	--	--	--	--	--	--	--	--

:h screen menu. Alerts employee being visited via email when visitor has completed self registration process a

Capacity can be expanded from 1024 to 2048 readers; in increments of 16; with the purchase of the desired quantity of AC-...
Capacity can be expanded from 16 to 2048 readers; in increments of 16; with the purchase of the desired quantity of AC-...
Capacity cannot be expanded | Supports up to 512 controllers | 500K identities and 150M stored events and Fifty (50) ...
Capacity can be expanded from 512 to 2048 readers; in increments of 16; with the purchase of the desired quantity of

pleted. (LINK to Automated Onboarding: <https://managementservices.hidglobal.com/faces/maUserOnBoardingSta>

ing a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply f
ss 2; Power Limited (CL2PL) outputs (two D8P Boards) delivering regulated independent power connection to
:ed independent power connection to Mercury boards and auxiliary equipment. The power supply features du
upply-battery charger. The power supply is pre-wired to four Class 2; Power Limited (CL2PL) outputs (C4P Board
ulated independent power connection to Mercury boards and auxiliary equipment. The power supply features
supply-battery charger. The power supply is pre-wired to eight Class 2; Power Limited (CL2PL) outputs (D8P B
egulated independent power connection to Mercury boards and auxiliary equipment. The power supply featur
ver supply-battery charger. The power supply is pre-wired to eight Class 2; Power Limited (CL2PL) outputs (D8

ge to system electronics; the backplate(s) separate from the enclosure for access hardware mounting in the sh
system electronics; the backplate(s) separate from the enclosure for access hardware mounting in the shop w
amage to system electronics; the backplates separate from the enclosure for access hardware mounting in the

ct is initiated. Also providing 16 auxiliary power distributed outputs; the unit has provisions for mounting a var
or 12 or 24VDC; failsafe or failsecure; and FAI; fault detection reporting with delay; system can be web-manage
trol outputs; programmable for either 12 or 24VDC; failsafe or failsecure; and FAI; fault detection reporting wi

re operation at either 12 or 24 VDC and controlled by the integrated fire alarm interface circuit on the FPO. Or

afe / failsecure operation at either 12 or 24 VDC and controlled by the integrated fire alarm interface circuit on

elay contacts and a host of features and functions designed to support the access control industry.(LifeSafety |
lock control outputs; programmable for either 12 or 24VDC; failsafe or failsecure; and FAI; fault detection repo

elay contacts and a host of features and functions designed to support the access control industry.(LifeSafety |
lock control outputs; programmable for either 12 or 24VDC; failsafe or failsecure; and FAI; fault detection repc

lock control outputs; programmable for either 12 or 24VDC; failsafe or failsecure; and FAI; fault detection repc

ay contacts and a host of features and functions designed to support the access control industry.(LifeSafety Po
d tamper switch. Size: 20.00H x 16.00W x 4.50D in. (50.00 x 40.00 x 11.50 cm) | Weight: 18 lbs.; Pre-installed k
ower for system use; the second is programmable for either fail-safe or fail-secure operation; activated when
n also available). Fault detection reporting with delay; system can be web-managed (w/ NetLink module); 120

operation at either 12 or 24 VDC and controlled by the integrated fire alarm interface circuit on the FPO. Salto
e operation at either 12 or 24 VDC and controlled by the integrated fire alarm interface circuit on the FPO. Onc

rogramma failsafe/failsecure; remote power cycle; monitor voltage and current on eac programmable limits; di
amper switch. Size: 20.00H x 16.00W x 4.50D in. (50.00 x 40.00 x 11.50 cm) | Weight: 18 lbs.; Pre-installed bra
amper switch. Size: 20.00H x 16.00W x 4.50D in. (50.00 x 40.00 x 11.50 cm) | Weight: 18 lbs.; Pre-installed bra
cond is programmable for either fail-safe or fail-secure operation; activated when the fire alarm disconnect is i

; the second is programmable for either fail-safe or fail-secure operation; activated when the fire alarm discon
rol outputs; programmable for either 12 or 24VDC; failsafe or failsecure; and FAI; fault detection reporting with

nect module and dual door lock key sets. Enclosure weight: 77 lb. Size: 36" x 30" x 4.5". CE approved. UL/CU
r limited outputs. Battery space for 12V or 24V; 8Ah batteries is available. Enclosure comes standard with inst

alled AC on/off switch; a low battery disconnect module and dual door lock key sets. Enclosure weight: 75 lb. 9

owers network drop fees; Reduces cybersecurity risks; Makes managed power possible in installations where a

on's order acknowledgment; all changes to an accepted purchase order will be subject to a Change Order charg
all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the net deliverab
ler. After 48 hours of Avigilon's order acknowledgment; all changes to an accepted purchase order will be subj
ted purchase order will be subject to a Change Order charge of 30% of the net deliverable value. Returns and
rdgment; all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the n
ment; all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the net d

ict or service cannot be purchased without a valid SOW. SOWs can be obtained through an Access Control sale

t or service cannot be purchased without a valid SOW. SOWs can be obtained through an Access Control sales
t or service cannot be purchased without a valid SOW. SOWs can be obtained through an Access Control sales

e customers environment. This product or service cannot be purchased without a valid SOW. SOWs can be ok
the customers environment. This product or service cannot be purchased without a valid SOW. SOWs can be
tely and requires remote access to the customers environment. This product or service cannot be purchased v
customers environment. This product or service cannot be purchased without a valid SOW. SOWs can be obtai
customers environment. This product or service cannot be purchased without a valid SOW. SOWs can be obta
customers environment. This product or service cannot be purchased without a valid SOW. SOWs can be obtaine

Avigilon - Unity Access - US Price List - MSRP - USD

--	--	--	--	--	--	--	--	--	--

nd is checked-in. Enables badge to be printed upon check-in at the main guard station. Stores visitor record in

Quantity of AC-SW-LIC-16RCU-6-P; 16 Reader Count Software Licenses | Supports up to 512 controllers | 500K identities
AC-SW-LIC-16RCU-6-P; 16 Reader Count Software Licenses | Supports up to 512 controllers | 500K identities and
50 simultaneous operators (via browser) | Three (3) year appliance hardware warranty begins at date of ship
AC-SW-LIC-16RCU-6-P; 16 Reader Count Software Licenses | Supports up to 512 controllers | 500K identities

riety of Mercury boards in the cabinet proper (E4M) and cabinet door (EM1). The unit is configured in painted; d (w/ NetLink module); 120V/230VAC; locking enclosure: 16" X 20" X 4.5"; ten year warranty; US/Canada age; th delay; system can be web-managed (w/ NetLink module); 120V/230VAC; locking enclosure: 16" X 20" X 4.5'

ne D8 module provides eight fused outputs and each output is configurable for 12 or 24VDC operation. SALTO

n the FPO. All inputs / outputs are software controlled for remote operation. One D8 module provides eight fu

orting with delay; system can be web-managed (w/ NetLink module); 120V/230VAC; locking enclosure; 20" X 2'

orting with delay; system can be web-managed (w/ NetLink module); 120V/230VAC; locking enclosure; 20" X 2

orting with delay; system can be web-managed (w/ NetLink module); 120V/230VAC; locking enclosure; 20" X 2

the fire alarm disconnect is initiated. Size: 16" x 20" x 4.5"; Weight: 13 lb. (LifeSafety Power Part Number: FPO V/230VAC; locking enclosure: 12" X 14" X 4.5"; ten year warranty; US/Canada agency listed for access; securit

access enclosures are painted steel with two removable controller backplates and include lock; two (2) keys a e D8 module provides eight fused outputs and each output is configurable for 12 or 24VDC operation. SALTO a

nect is initiated. Size: 16" x 20" x 4.5"; Weight: 13 lb. (LifeSafety Power Part Number: FPO75-E2BP2)

h delay; system can be web-managed (w/ NetLink module); 120V/230VAC; locking enclosure: 16" X 20" X 4.5";

alled AC on/off switch; a low battery disconnect module and dual door lock key sets. Enclosure weight: 77 lb.

ge of 30% of the net deliverable value. Returns and cancellations of an order or portion of an order that include
le value. Returns and cancellations of an order or portion of an order that includes deliverables that have bee
ect to a Change Order charge of 30% of the net deliverable value. Returns and cancellations of an order or por
cancellations of an order or portion of an order that includes deliverables that have been manufactured and p
net deliverable value. Returns and cancellations of an order or portion of an order that includes deliverables th
eliverable value. Returns and cancellations of an order or portion of an order that includes deliverables that ha

Avigilon - Unity Access - US Price List - MSRP - USD

--	--	--	--	--	--	--	--	--	--

ties and 150M stored events and Fifty (50) simultaneous operators (via browser) | Three (3) year appliance ha
150M stored events and Fifty (50) simultaneous operators (via browser) | Three (3) year appliance hardware
and 150M stored events and Fifty (50) simultaneous operators (via browser) | Three (3) year appliance hardw

· sold separately) to enable monitoring; reporting and control of the power system from Access Control Manager
;put (two C8 Boards) for independent relay lock power. Both power supplies features dual outputs (12 & 24vol
ately) to enable monitoring; reporting and control of the power system from Access Control Manager (ACM) li
re power supply features dual outputs (12 & 24volts DC); form 'C' fault relay contacts; a fire alarm input and n
parately) to enable monitoring; reporting and control of the power system from Access Control Manager (ACM
Board) for independent relay lock power. The power supply features dual outputs (12 & 24volts DC); form 'C'
separately) to enable monitoring; reporting and control of the power system from Access Control Manager (A
(C8 Board) for independent relay lock power. The power supply features dual outputs (12 & 24volts DC); form

; steel; locking enclosure with tamper switch and integral battery space. Size: 20" x 24" x 4.5"; Weight: 21 lb. (L
ncy listed for access; security; fire; CCTV; mass notification (LifeSafety Power Part Number: FPO150-B100C8D
"; ten year warranty; US/Canada agency listed for access; security; fire; CCTV; mass notification (LifeSafety Po

access enclosures are painted steel with four removable controller backplates and include lock; two (2) keys a

ised outputs and each output is configurable for 12 or 24VDC operation. SALTO access enclosures are painted

4" X 4.5"; ten year warranty; US/Canada agency listed for access; security; fire; CCTV; mass notification (LifeSa

4" X 4.5"; ten year warranty; US/Canada agency listed for access; security; fire; CCTV; mass notification (LifeS

4" X 4.5"; ten year warranty; US/Canada agency listed for access; security; fire; CCTV; mass notification (LifeS

ind tamper switch. Size: 14.00H x 12.00W x 4.50D in. (35.00 x 31.00 x 11.50 cm) | Weight: 14 lbs; Pre-installed
access enclosures are painted steel with three removable controller backplates and include lock; two (2) keys a

; ten year warranty; US/Canada agency listed for access; security; fire; CCTV; mass notification (LifeSafety Pow

Size: 36" x 30" x 6.5". CE approved. UL/CUL listed with Mercury panels installed. (LifeSafety Power Part Numl

es deliverables that have been manufactured and prepped for shipping will be applied with a 50% restocking fi
n manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Power Part #: I
rtion of an order that includes deliverables that have been manufactured and prepped for shipping will be app
repped for shipping will be applied with a 50% restocking fee. (Lifesafety Power Part #: FPO150/250-2C83D8P
at have been manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Po
ave been manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Power I

Avigilon - Unity Access - US Price List - MSRP - USD

--	--	--	--	--	--	--	--	--	--

izer (ACM) link. Battery space for two 12V; 8Ah batteries is available in cabinet. Cabinet size: 20" x 24" x 6.5" with DC); form 'C' fault relay contacts; a fire alarm input and network interface (interface module sold separately). Battery space for two 12V; 8Ah batteries is available in cabinet (unless using two AC-MER-CONT-1DR). Cabinet size: 16" x 20" x 4.5" with door network interface (interface module sold separately) to enable monitoring; reporting and control of the power. Battery space for two 12V; 8Ah batteries is available in cabinet. Cabinet size: 20" x 24" x 6.5" with door fault relay contacts; a fire alarm input and network interface (interface module sold separately) to enable monitoring. Battery space for two 12V; 8Ah batteries is available in cabinet. Cabinet size: 16" x 20" x 4.5" with door fault relay contacts; a fire alarm input and network interface (interface module sold separately) to enable monitoring. Battery space for two 12V; 8Ah batteries is available in cabinet. Cabinet size: 20" x 24" x 6.5" with door fault relay contacts; a fire alarm input and network interface (interface module sold separately) to enable monitoring.

and tamper switch. Size: 24.00H x 20.00W x 6.50D in. (61.00 x 50.00 x 17.50 cm) | Weight: 38 lbs.; Pre-installed

steel with four removable controller backplates and include lock; two (2) keys and tamper switch. Size: 24.00H

and tamper switch. Size: 20.00H x 16.00W x 4.50D in. (50.00 x 40.00 x 11.50 cm) | Weight: 18 lbs.; Pre-installed

Avigilon - Unity Access - US Price List - MSRP - USD

--	--	--	--	--	--	--	--	--	--

with door lock; tamper switch and two (2) keys. Weight 25 lb.(LifeSafety Power Part Number: FPO150-D8PE4M1) to enable monitoring; reporting and control of the power system from Access Control Manager (ACM) link. Cabinet size: 12" x 14" x 4.5" with door lock; tamper switch and two (2) keys. Weight 14 lb.(LifeSafety Power Part system from Access Control Manager (ACM) link. Battery space for two 12V; 8Ah batteries is available in cabinet size: 12" x 14" x 4.5" with door lock; tamper switch and two (2) keys. Weight 19 lb.(LifeSafety Power Part Number: FPO75-D8PE2M) monitoring; reporting and control of the power system from Access Control Manager (ACM) link. Battery space for cabinet size: 12" x 14" x 4.5" with door lock; tamper switch and two (2) keys. Weight 25 lb.(LifeSafety Power Part Number: FPO75-D8PE4M) monitoring; reporting and control of the power system from Access Control Manager (ACM) link. Battery space

1 x 20.00W x 6.50D in. (61.00 x 50.00 x 17.50 cm) | Weight: 38 lbs.; Pre-installed brackets for four (4) SALTO cc

Avigilon - Unity Access - US Price List - MSRP - USD

--	--	--	--	--	--

Cabinet size: 20" x 24" x 6.5" with door lock and two (2) keys.

net (unless using two AC-MER-CONT-1DR). Cabinet size: 12" x

r two 12V; 8Ah batteries is available in cabinet. Cabinet size

ce for two 12V; 8Ah batteries is available in cabinet. Cabinet

